BAHAGIAN F2
SENARAI KUANTITI

PERKHIDMATAN MEMBEKAL ALAT GANTI DAN AKSESORI KOMPUTER UNTUK KEGUNAAN PEJABAT MAJLIS BANDARAYA ISKANDAR PUTERI BAGI TAHUN 2026 / 2027

RINGKASAN SENARAI KUANTITI

BIL.	BAHAGIAN	MUKA SURAT	JUMLAH (RM)
1	**PAPARAN & VISUAL**	F2/2	
2	**AUDIO & KOMUNIKASI**	F2/6	
3	**WIRELESS VIDEO**	F2/12	
4	**KABEL VIDEO & DATA**	F2/15	
5	**PERKAKASAN DALAMAN**	F2/18	
6	**SAMBUNGAN PERANTI**	F2/23	
7	**INPUT DEVICE**	F2/27	
8	**PERALATAN RANGKAIAN**	F2/36	
9	**BEKALAN KUASA**	F2/38	
10	**PERALATAN KESELAMATAN**	F2/43	
11	**AKSESORI PINTAR**	F2/47	
12	**ERGONOMIK & AKSESORI MEJA**	F2/49	
13	**PERALATAN KHAS**	F2/54	
14	**AKSESORI PERANTI**	F2/55	
15	**AKSESORI KAMERA**	F2/57	
16	**PERANTI MUDAH ALIH**	F2/59	
JUMLAH KESELURUHAN			

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>A</td><td>PAPARAN & VISUAL</td><td></td><td></td><td></td><td></td></tr>
<tr><td>A.1</td><td>FEELWORLD FW759 7 INCH FIELD MONITOR ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>1. JENIS MONITOR</td><td>FIELD MONITOR 7" UNTUK KAMERA / VIDEO</td></tr>
<tr><td>2. PAPARAN (DISPLAY)</td><td>IPS LCD, 7.0" DIAGONAL</td></tr>
<tr><td>3. RESOLUSI</td><td>1280 × 800 (HD+ / 16:10)</td></tr>
<tr><td>4. BRIGHTNESS & CONTRAST</td><td>BRIGHTNESS MIN. 400 CD/M²; CONTRAST > 800:1</td></tr>
<tr><td rowspan="2">5. INPUT / CONNECTIVITY</td><td>• HDMI INPUT (4K UHD SUPPORT)</td></tr>
<tr><td>• AV COMPOSITE INPUT</td></tr>
<tr><td>6. SOKONGAN VIDEO FORMAT</td><td>480I/P, 576I/P, 720P, 1080I/P, 4K UHD @ UP TO 30HZ</td></tr>
<tr><td>7. FUNGSI VIDEO ASSIST</td><td>FOKUS PEAKING, SAFE AREA MARKER, IMAGE FLIP, IMAGE FREEZE, CHECK FIELD</td></tr>
<tr><td rowspan="2">8. AUDIO</td><td>• STEREO SPEAKER</td></tr>
<tr><td>• 3.5MM HEADPHONE JACK</td></tr>
<tr><td rowspan="2">9. REKA BENTUK & DIMENSI</td><td>• SLIM & RINGAN (< 300G)</td></tr>
<tr><td>• KETEBALAN SEKITAR 17 MM</td></tr>
<tr><td>10. KOMPATIBILITI POWER / BATTERY</td><td>SONY L-SERIES BATTERY PLATE (NP-F970 COMPATIBLE) / DC POWER INPUT</td></tr>
<tr><td>12. AKSESORI STANDARD</td><td>MINI HDMI CABLE, SUNSHADE, HOT SHOE MOUNT, HDMI LOCK</td></tr>
<tr><td>13. JAMINAN</td><td>MINIMUM 12 BULAN DARI TARIKH PENGHANTARAN</td></tr>
</table></td><td>UNIT</td><td>1</td><td></td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>A.2</td><td>ARZOPA ARZOPA Z3FC GREY ATAU YANG SETARA
<table>
<tr><td>ITEM</td><td>SPESIFIKASI MINIMUM</td></tr>
<tr><td>SAIZ SKRIN</td><td>16.1 INCI</td></tr>
<tr><td>RESOLUSI PAPARAN</td><td>MINIMUM 2560 × 1440 (QHD)</td></tr>
<tr><td>PANEL</td><td>IPS (178°)</td></tr>
<tr><td>REFRESH RATE</td><td>180 HZ</td></tr>
<tr><td>ADAPTIVE SYNC</td><td>AMD FREESYNC ATAU SETARA</td></tr>
<tr><td>WARNA & BRIGHTNESS</td><td>BRIGHTNESS 350 NITS; GAMUT WARNA SRGB 95%</td></tr>
<tr><td rowspan="2">INPUT/PORTS</td><td>• USB-C (FULL-FUNCTION) 2</td></tr>
<tr><td>• MINI HDMI 1</td></tr>
<tr><td>SOKONGAN HDR</td><td>HDR10</td></tr>
<tr><td>AUDIO</td><td>PEMBESAR SUARA TERBINA 2 CHANNEL</td></tr>
<tr><td>POWER DELIVERY (PD)</td><td>USB-C PD SUPPORT (MINIMUM 5V/3A)</td></tr>
<tr><td>AKSESORI STANDARD</td><td>CABLES: USB-C TO USB-C, USB-C TO HDMI TANGKAPAN SIGNAL, PROTECTIVE CASE / STAND</td></tr>
<tr><td>JAMINAN</td><td>MINIMUM 12 BULAN DARI TARIKH PENGHANTARAN</td></tr>
</table></td><td>UNIT</td><td>1</td><td></td><td></td></tr>
<tr><td>A.3</td><td>3D HOLOGRAM PROJECTOR 50CM ATAU YANG SETARA
<table>
<tr><td>ITEM</td><td>SPESIFIKASI MINIMUM</td></tr>
<tr><td>DISPLAY TYPE</td><td>LED ROTATING HOLOGRAPHIC FAN DISPLAY</td></tr>
<tr><td>FAN DIAMETER</td><td>~50 CM</td></tr>
<tr><td>DISPLAY RESOLUTION</td><td>±1024 × 1024 PIXELS (TYPICAL)</td></tr>
<tr><td>BRIGHTNESS</td><td>HIGH BRIGHTNESS LED (VISIBLE INDOOR & SEMI-OUTDOOR)</td></tr>
<tr><td>VIEWING ANGLE</td><td>160° – 176° WIDE VIEWING ANGLE</td></tr>
<tr><td>FRAME RATE</td><td>UP TO 30 FPS</td></tr>
<tr><td>SUPPORTED MEDIA</td><td>MP4, AVI, GIF, JPG, PNG</td></tr>
<tr><td>CONTROL METHOD</td><td>MOBILE APP / WIFI / SD CARD</td></tr>
<tr><td>STORAGE</td><td>MICROSD / TF CARD SUPPORT</td></tr>
<tr><td>CONNECTIVITY</td><td>WIFI 2.4 GHZ</td></tr>
<tr><td>MOUNTING</td><td>WALL MOUNT / BRACKET MOUNTING</td></tr>
<tr><td>POWER INPUT</td><td>AC 100–240V ADAPTER</td></tr>
<tr><td>POWER CONSUMPTION</td><td>±10–20 W</td></tr>
<tr><td>OPERATING TEMPERATURE</td><td>-10 °C ~ 45 °C</td></tr>
<tr><td>NOISE LEVEL</td><td>LOW NOISE MOTOR ROTATION</td></tr>
</table></td><td>UNIT</td><td>1</td><td></td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>A.4</td><td>TEAMGEE P2 PRO / P2 PORTABLE TRIPLE MONITOR ATAU YANG SETARA

<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>PRODUCT TYPE</td><td>PORTABLE LAPTOP SCREEN EXTENDER / TRIPLE MONITOR SYSTEM</td></tr>
<tr><td>DISPLAY QUANTITY</td><td>DUAL EXTERNAL MONITOR (LEFT & RIGHT) FOR LAPTOP</td></tr>
<tr><td>SCREEN SIZE</td><td>MINIMUM 12" IPS PANEL (EACH SCREEN)</td></tr>
<tr><td>DISPLAY TECHNOLOGY</td><td>IPS LCD PANEL WITH WIDE VIEWING ANGLE (178°)</td></tr>
<tr><td>RESOLUTION</td><td>FULL HD 1920 × 1080 PER SCREEN</td></tr>
<tr><td>ASPECT RATIO</td><td>16:9</td></tr>
<tr><td>BRIGHTNESS</td><td>MINIMUM 250 CD/M²</td></tr>
<tr><td>CONTRAST RATIO</td><td>800:1</td></tr>
<tr><td>REFRESH RATE</td><td>60 HZ</td></tr>
<tr><td>COLOUR SUPPORT</td><td>16.7 MILLION COLOURS (8-BIT COLOUR)</td></tr>
<tr><td>CONNECTIVITY</td><td>USB-C (DISPLAYPORT ALT MODE) & HDMI INPUT SUPPORT</td></tr>
<tr><td>POWER SOURCE</td><td>POWERED VIA LAPTOP USB-C OR USB-A (NO EXTERNAL ADAPTER REQUIRED)</td></tr>
<tr><td>COMPATIBILITY</td><td>SUPPORTS WINDOWS 10/11, MACOS & SELECTED ANDROID DEVICES</td></tr>
<tr><td>LAPTOP SIZE SUPPORT</td><td>COMPATIBLE WITH LAPTOP SCREEN SIZE 13" – 17.3"</td></tr>
<tr><td>MOUNTING MECHANISM</td><td>ADJUSTABLE CLAMP MOUNTING FRAME WITH REAR KICKSTAND SUPPORT</td></tr>
<tr><td>SCREEN ADJUSTMENT</td><td>ADJUSTABLE TILT ANGLE 180° ROTATION / FOLDING DESIGN</td></tr>
<tr><td>PORTABILITY</td><td>FOLDABLE PORTABLE DESIGN WITH PROTECTIVE CARRY CASE</td></tr>
<tr><td>INSTALLATION</td><td>PLUG & PLAY (NO DRIVER INSTALLATION REQUIRED)</td></tr>
<tr><td>AUDIO</td><td>BUILT-IN STEREO SPEAKER OR AUDIO PASSTHROUGH VIA HDMI/USB</td></tr>
<tr><td>ACCESSORIES</td><td>USB-C CABLE, USB-A TO USB-C CABLE, HDMI CABLE, MOUNTING FRAME, CARRY POUCH</td></tr>
<tr><td>APPLICATION</td><td>MULTITASKING WORKSTATION, MONITORING DASHBOARD, REMOTE ADMINISTRATION & PRESENTATION</td></tr>
<tr><td>WARRANTY</td><td>MINIMUM 12 MONTHS</td></tr>
</table>
</td><td>UNIT</td><td>1</td><td></td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>A.5</td><td>GIGABYTE M27Q X MONITOR ATAU YANG SETARA
<table>
<tr><td>ITEM</td><td>SPESIFIKASI MINIMUM</td></tr>
<tr><td>PRODUCT TYPE</td><td>27" PROFESSIONAL IPS MONITOR</td></tr>
<tr><td>PANEL SIZE</td><td>27 INCH</td></tr>
<tr><td>PANEL TYPE</td><td>SUPERSPEED IPS (SS IPS)</td></tr>
<tr><td>NATIVE RESOLUTION</td><td>2560 × 1440 (QHD)</td></tr>
<tr><td>ASPECT RATIO</td><td>16:9</td></tr>
<tr><td>REFRESH RATE</td><td>UP TO 240 HZ</td></tr>
<tr><td>RESPONSE TIME</td><td>1 MS (GTG)</td></tr>
<tr><td>BRIGHTNESS</td><td>TYPICAL 400 CD/M²</td></tr>
<tr><td>CONTRAST RATIO</td><td>1000:1</td></tr>
<tr><td>COLOUR GAMUT</td><td>100% SRGB / 92% DCI-P3</td></tr>
<tr><td>HDR SUPPORT</td><td>VESA DISPLAYHDR 400</td></tr>
<tr><td>VIEWING ANGLE</td><td>178° (H/V)</td></tr>
<tr><td>ADAPTIVE SYNC</td><td>AMD FREESYNC PREMIUM & NVIDIA G-SYNC COMPATIBLE</td></tr>
<tr><td>VIDEO INPUTS</td><td>2 × HDMI 2.0, 1 × DISPLAYPORT 1.4</td></tr>
<tr><td>USB-C</td><td>1 × USB-C (DISPLAY + DATA + CHARGING)</td></tr>
<tr><td>USB HUB</td><td>2 × USB 3.0 DOWNSTREAM</td></tr>
<tr><td>KVM FEATURE</td><td>BUILT-IN KVM SWITCH (CONTROL 2 DEVICES WITH 1 KEYBOARD & MOUSE)</td></tr>
<tr><td>AUDIO</td><td>3.5 MM HEADPHONE OUT</td></tr>
<tr><td>STAND ADJUSTMENT</td><td>TILT, HEIGHT ADJUSTMENT, SWIVEL</td></tr>
<tr><td>MOUNTING</td><td>VESA 100 × 100 MM</td></tr>
<tr><td>POWER</td><td>AC 100–240V, 50/60HZ</td></tr>
<tr><td>SPECIAL FEATURES</td><td>OSD SIDEKICK SOFTWARE, AIM STABILIZER, LOW BLUE LIGHT, FLICKER-FREE</td></tr>
<tr><td>WARRANTY</td><td>MINIMUM 3 YEARS</td></tr>
</table></td><td>UNIT</td><td>1</td><td></td><td></td></tr>
<tr><td colspan="5">JUMLAH KESELURUHAN (BIL A)</td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>B</td><td>AUDIO & KOMUNIKASI</td><td></td><td></td><td></td><td></td></tr>
<tr><td>B.1</td><td>EDIFIER R1700BTS BOOKSHELF SPEAKER ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>JENIS SPEAKER</td><td>2.0 BOOKSHELF SPEAKER AKTIF (WITH BUILT-IN AMPLIFIER)</td></tr>
<tr><td>AMPLIFIER & POWER OUTPUT</td><td>TOTAL RMS 66 W (15 W × 2 TWEETER + 18 W × 2 MIDBASS)</td></tr>
<tr><td>BLUETOOTH CONNECTIVITY</td><td>BLUETOOTH V5.0 DENGAN APTX HD</td></tr>
<tr><td rowspan="2">DRIVER UNITS</td><td>• 4" MIDBASS DRIVER ×2</td></tr>
<tr><td>• 19 MM SILK DOME TWEETER ×2</td></tr>
<tr><td>FREQUENCY RESPONSE</td><td>52 HZ – 20 KHZ</td></tr>
<tr><td>SIGNAL-TO-NOISE RATIO</td><td>85 DB(A)</td></tr>
<tr><td rowspan="2">AUDIO INPUTS</td><td>• DUAL RCA LINE-IN</td></tr>
<tr><td>• BLUETOOTH</td></tr>
<tr><td>SUBWOOFER OUTPUT</td><td>SUB-OUT UNTUK EXTERNAL SUBWOOFER</td></tr>
<tr><td>CONTROLS & EXTRAS</td><td>SIDE PANEL KNOBS + REMOTE CONTROL</td></tr>
<tr><td>ENCLOSURE</td><td>MDF WOOD ENCLOSURE (ACOUSTIC RESONANCE REDUCTION)</td></tr>
<tr><td>JAMINAN</td><td>MINIMUM 12 BULAN</td></tr>
</table></td><td>UNIT</td><td>1</td><td></td><td></td></tr>
<tr><td>B.2</td><td>TP-LINK BLUETOOTH 5.3 NANO USB (UB500) ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>1. JENIS PERANTI</td><td>BLUETOOTH USB NANO ADAPTER</td></tr>
<tr><td>2. STANDARD BLUETOOTH</td><td>BLUETOOTH 5.3 (TERMASUK BLE SUPPORT)</td></tr>
<tr><td>3. BACKWARD COMPATIBILITY</td><td>BACKWARD COMPATIBLE DENGAN BT 5.2/5.0/4.0/3.0/2.1</td></tr>
<tr><td>4. INTERFACE USB</td><td>USB TYPE-A (USB 2.0)</td></tr>
<tr><td>5. RANGE & CONNECTIVITY</td><td>SEHINGGA ~10-20 M</td></tr>
<tr><td>6. OPERATING SYSTEMS</td><td>WINDOWS 11/10/8.1/7</td></tr>
<tr><td>7. MULTI-DEVICE SUPPORT</td><td>SUPPORTS CONNECTION OF 7 BLUETOOTH DEVICES SIMULTANEOUSLY</td></tr>
<tr><td>8. POWER & PLUG-AND-PLAY</td><td>USB BUS-POWERED; PLUG-AND-PLAY</td></tr>
<tr><td>9. DIMENSI FIZIKAL</td><td>NANO FORM FACTOR</td></tr>
<tr><td>10. OPERATING CONDITIONS</td><td>TEMPERATURE: 0 °C–40 °C</td></tr>
<tr><td>11. WARRANTY</td><td>MINIMUM 12 BULAN</td></tr>
</table></td><td>UNIT</td><td>1</td><td></td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>B.3</td><td>KEBIDUMEI BLUETOOTH 6.0 AUDIO RECEIVER ATAU YANG SETARA
<table><tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr><tr><td>1. JENIS PERANTI</td><td>BLUETOOTH 6.0 USB AUDIO RECEIVER & ADAPTER (TRANSMITTER/RECEIVER)</td></tr><tr><td>2. BLUETOOTH STANDARD</td><td>BLUETOOTH 5.4 / 6.0 BACKWARD COMPATIBLE DENGAN 5.3/5.2/5.1/5.0/4.0</td></tr><tr><td>3. INTERFACE USB</td><td>USB TYPE-A (USB 2.0)</td></tr><tr><td>4. JARAK OPERASI</td><td>MINIMUM 10–20 M</td></tr><tr><td>5. AUDIO CODEC</td><td>SUPPORT A2DP, SBC, AAC 48 KHZ CD-QUALITY</td></tr><tr><td>6. MULTI-DEVICE SUPPORT</td><td>SOKONGAN SEHINGGA 5 DEVICES SERENTAK</td></tr><tr><td>7. SISTEM OPERASI</td><td>PLUG-AND-PLAY</td></tr><tr><td>8. DIMENSI FIZIKAL</td><td>NANO USB FORM FACTOR</td></tr><tr><td>9. OPERATING CONDITIONS</td><td>OPERATING TEMP: -20°C - 70°C</td></tr><tr><td>10. WARRANTY</td><td>MINIMUM 12 BULAN</td></tr></table></td><td>UNIT</td><td>1</td><td></td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>B.4</td><td>JABRA SPEAK2 75 MS SPEAKERPHONE WITH LINK380A DONGLE ATAU YANG SETARA

<table><tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr><tr><td>DEVICE TYPE</td><td>PORTABLE USB & BLUETOOTH SPEAKERPHONE (CONFERENCE SPEAKER)</td></tr><tr><td>CERTIFIED PLATFORM</td><td>MICROSOFT TEAMS CERTIFIED (MS VERSION)</td></tr><tr><td>CONNECTIVITY</td><td>USB-C WIRED • BLUETOOTH 5.2 • USB-A DONGLE (LINK380A)</td></tr><tr><td>WIRELESS RANGE</td><td>UP TO ~30 M (OPEN ENVIRONMENT)</td></tr><tr><td>MICROPHONE SYSTEM</td><td>4-MICROPHONE BEAMFORMING ARRAY (360° VOICE PICKUP)</td></tr><tr><td>SPEAKER SIZE</td><td>65 MM FULL-RANGE SPEAKER</td></tr><tr><td>AUDIO PROCESSING</td><td>FULL-DUPLEX AUDIO + ECHO CANCELLATION + NOISE SUPPRESSION</td></tr><tr><td>VOICE PICKUP RANGE</td><td>±2.5 M RADIUS (MEETING TABLE COVERAGE)</td></tr><tr><td>FREQUENCY RESPONSE (SPEAKER)</td><td>~80 HZ – 20 KHZ</td></tr><tr><td>FREQUENCY RESPONSE (MIC)</td><td>~150 HZ – 14 KHZ</td></tr><tr><td>SUPPORTED MODES</td><td>MUSIC MODE & VOICE CONFERENCE MODE</td></tr><tr><td>BLUETOOTH PAIRING</td><td>UP TO 8 DEVICES (2 ACTIVE SIMULTANEOUSLY)</td></tr><tr><td>USB DONGLE</td><td>JABRA LINK380A USB-A WIRELESS ADAPTER</td></tr><tr><td>BATTERY TYPE</td><td>BUILT-IN RECHARGEABLE LI-ION</td></tr><tr><td>BATTERY CAPACITY</td><td>~4700 MAH</td></tr><tr><td>BATTERY LIFE</td><td>UP TO ±32 HOURS TALK TIME</td></tr><tr><td>CHARGING TIME</td><td>±2.5 HOURS</td></tr><tr><td>CHARGING PORT</td><td>USB-C</td></tr><tr><td>WATER/DUST PROTECTION</td><td>IP64 (DUST RESISTANT & SPLASH RESISTANT)</td></tr></table></td><td>UNIT</td><td>1</td><td></td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>B.5</td><td>BEHRINGER MPA40BT-PRO PORTABLE SPEAKER WITH 2 WIRELESS MIC ATAU YANG SETARA
<table><tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr><tr><td>PRODUCT TYPE</td><td>PORTABLE BATTERY POWERED PUBLIC ADDRESS (PA) SPEAKER SYSTEM</td></tr><tr><td>SPEAKER CONFIGURATION</td><td>MINIMUM 8" FULL-RANGE SPEAKER DRIVER</td></tr><tr><td>AMPLIFIER POWER</td><td>MINIMUM 40 WATTS RMS CLASS-D AMPLIFIER</td></tr><tr><td>FREQUENCY RESPONSE</td><td>APPROX. 50 HZ – 18 KHZ</td></tr><tr><td>MAXIMUM SOUND PRESSURE LEVEL</td><td>100 DB SPL</td></tr><tr><td>AUDIO INPUTS</td><td>MINIMUM 2 × MICROPHONE INPUT (6.3 MM JACK) & 1 × AUX / LINE INPUT</td></tr><tr><td>WIRELESS CONNECTIVITY</td><td>BLUETOOTH AUDIO STREAMING SUPPORT</td></tr><tr><td>BUILT-IN MIXER</td><td>INTEGRATED 2-CHANNEL MIXER WITH INDEPENDENT VOLUME CONTROL</td></tr><tr><td>TONE CONTROL</td><td>MASTER BASS & TREBLE EQUALIZER CONTROL</td></tr><tr><td>WIRELESS MICROPHONE</td><td>COMPLETE WITH 2 × UHF WIRELESS HANDHELD MICROPHONE SET</td></tr><tr><td>WIRELESS MIC RANGE</td><td>MINIMUM 15 – 25 METERS OPERATING DISTANCE (LINE-OF-SIGHT)</td></tr><tr><td>MICROPHONE RECEIVER</td><td>BUILT-IN OR EXTERNAL COMPATIBLE WIRELESS RECEIVER MODULE</td></tr><tr><td>AUDIO OUTPUT</td><td>LINE OUT / LINK OUTPUT FOR ADDITIONAL SPEAKER (IF AVAILABLE)</td></tr><tr><td>BATTERY TYPE</td><td>BUILT-IN RECHARGEABLE BATTERY</td></tr><tr><td>BATTERY OPERATION TIME</td><td>MINIMUM 8 HOURS CONTINUOUS OPERATION</td></tr><tr><td>CHARGING</td><td>AC CHARGING 220–240V, 50/60HZ</td></tr><tr><td>PORTABILITY</td><td>INTEGRATED CARRY HANDLE & LIGHTWEIGHT PORTABLE DESIGN</td></tr><tr><td>MOUNTING</td><td>COMPATIBLE WITH STANDARD SPEAKER TRIPOD STAND (35 MM POLE MOUNT)</td></tr><tr><td>ENCLOSURE</td><td>IMPACT-RESISTANT ABS CABINET</td></tr><tr><td>INDICATORS</td><td>POWER, CHARGING & SIGNAL STATUS INDICATORS</td></tr><tr><td>ADDITIONAL FEATURES</td><td>USB/SD MP3 PLAYER SUPPORT (IF AVAILABLE)</td></tr><tr><td>APPLICATION</td><td>OUTDOOR EVENT, PUBLIC ANNOUNCEMENT, TRAINING, BRIEFING &</td></tr></table></td><td>UNIT</td><td>1</td><td></td><td></td></tr>
</table>

DIJANA OLEH , 11.11.2026

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>B.6</td><td>BOYA BOYALINK 2.4GHZ WIRELESS MICROPHONE SYSTEM ATAU YANG SETARA
<table><tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr><tr><td>DEVICE TYPE</td><td>WIRELESS LAVALIER MICROPHONE SYSTEM</td></tr><tr><td>TRANSMISSION TECHNOLOGY</td><td>2.4 GHZ DIGITAL WIRELESS TRANSMISSION</td></tr><tr><td>MICROPHONE TYPE</td><td>BUILT-IN OMNIDIRECTIONAL CONDENSER MICROPHONE</td></tr><tr><td>CHANNEL</td><td>DUAL TRANSMITTER (2-PERSON RECORDING)</td></tr><tr><td>FREQUENCY RESPONSE</td><td>20 HZ – 20 KHZ</td></tr><tr><td>TRANSMISSION RANGE</td><td>UP TO APPROX. 100 M (LINE-OF-SIGHT)</td></tr><tr><td>LATENCY</td><td>VERY LOW LATENCY REAL-TIME AUDIO MONITORING</td></tr><tr><td>NOISE REDUCTION</td><td>BUILT-IN DSP NOISE REDUCTION</td></tr><tr><td>OUTPUT INTERFACE</td><td>USB-C, LIGHTNING & 3.5 MM TRS/TRRS (INTERCHANGEABLE ADAPTER)</td></tr><tr><td>COMPATIBILITY</td><td>SMARTPHONE (ANDROID/IPHONE), CAMERA, LAPTOP, TABLET</td></tr><tr><td>GAIN CONTROL</td><td>ADJUSTABLE INPUT GAIN ON RECEIVER</td></tr><tr><td>MONITORING</td><td>REAL-TIME AUDIO MONITORING SUPPORTED</td></tr></table></td><td>UNIT</td><td>1</td><td></td><td></td></tr>
<tr><td>B.7</td><td>LOGITECH ZONE VIBE 100 HEADPHONE ATAU YANG SETARA
<table><tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr><tr><td>DEVICE TYPE</td><td>WIRELESS STEREO HEADSET WITH MICROPHONE</td></tr><tr><td>WEARING STYLE</td><td>OVER-EAR (LIGHTWEIGHT OFFICE DESIGN)</td></tr><tr><td>CONNECTIVITY</td><td>BLUETOOTH 5.2 WIRELESS</td></tr><tr><td>WIRELESS RANGE</td><td>UP TO APPROX. 30 M (OPEN SPACE)</td></tr><tr><td>DRIVER SIZE</td><td>40 MM AUDIO DRIVERS</td></tr><tr><td>FREQUENCY RESPONSE (HEADPHONE)</td><td>20 HZ – 20 KHZ</td></tr><tr><td>IMPEDANCE</td><td>~45 OHMS</td></tr><tr><td>COMPATIBILITY</td><td>WINDOWS, MACOS, ANDROID, IOS, TABLETS</td></tr><tr><td>MULTIPOINT CONNECTION</td><td>YES (2 DEVICES SIMULTANEOUSLY)</td></tr></table></td><td>UNIT</td><td>1</td><td></td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>B.8</td><td>RETEVIS AILUNCE HA2 WALKIE TALKIE ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>RADIO TYPE</td><td>DUAL-BAND ANALOG HANDHELD TRANSCEIVER</td></tr>
<tr><td>FREQUENCY RANGE</td><td>VHF: 136-174 MHZ • UHF: 400-470 MHZ</td></tr>
<tr><td>RF OUTPUT POWER</td><td>HIGH 8 W • MEDIUM 4 W • LOW 1 W SELECTABLE</td></tr>
<tr><td>CHANNEL CAPACITY</td><td>UP TO 128 PROGRAMMABLE CHANNELS</td></tr>
<tr><td>CHANNEL SPACING</td><td>12.5 KHZ (NARROWBAND) / 25 KHZ (WIDEBAND)</td></tr>
<tr><td>MODULATION</td><td>ANALOG FM (F3E)</td></tr>
<tr><td>FREQUENCY STABILITY</td><td>±2.5 PPM</td></tr>
<tr><td>OPERATING VOLTAGE</td><td>7.4 V DC</td></tr>
<tr><td>BATTERY TYPE</td><td>RECHARGEABLE LI-ION BATTERY PACK</td></tr>
<tr><td>BATTERY CAPACITY</td><td>2800 MAH</td></tr>
<tr><td>BATTERY LIFE</td><td>±14–20 HOURS (5-5-90 DUTY CYCLE TYPICAL)</td></tr>
<tr><td>RECEIVER SENSITIVITY</td><td>0.18 ?V (12 DB SINAD)</td></tr>
<tr><td>AUDIO OUTPUT POWER</td><td>1 W HIGH-POWER SPEAKER</td></tr>
<tr><td>ANTENNA</td><td>DETACHABLE HIGH-GAIN DUAL-BAND ANTENNA (SMA-FEMALE)</td></tr>
<tr><td>WATERPROOF RATING</td><td>IP67 (DUST-TIGHT & HEAVY RAIN RESISTANT)</td></tr>
<tr><td>WEIGHT</td><td>±300 G (BATTERY + ANTENNA)</td></tr>
<tr><td>ACCESSORY CONNECTOR</td><td>KENWOOD-TYPE 2-PIN (EARPIECE & SHOULDER MIC COMPATIBLE)</td></tr>
</table></td><td>UNIT</td><td>1</td><td></td><td></td></tr>
<tr><td colspan="5">JUMLAH KESELURUHAN (BIL B)</td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>C</td><td>WIRELESS VIDEO</td><td></td><td></td><td></td><td></td></tr>
<tr><td>C.1</td><td>HOLLYLAND PYRO H WIRELESS VIDEO TRANSMISSION (TX + RX) ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>DEVICE TYPE</td><td>WIRELESS HDMI VIDEO TRANSMISSION SYSTEM (TX + RX)</td></tr>
<tr><td>TRANSMISSION TECHNOLOGY</td><td>5 GHZ WIRELESS VIDEO (HOLLYLAND AUTO DUAL-BAND HOPPING)</td></tr>
<tr><td>MAX TRANSMISSION RANGE</td><td>UP TO ±400 M (LINE-OF-SIGHT)</td></tr>
<tr><td>LATENCY</td><td>~60 MS (LOW LATENCY MONITORING)</td></tr>
<tr><td>VIDEO RESOLUTION</td><td>UP TO 1080P60 FULL HD</td></tr>
<tr><td>FREQUENCY BANDS</td><td>5.1 – 5.8 GHZ ISM BAND</td></tr>
<tr><td>CHANNELS</td><td>AUTO CHANNEL SCAN & INTERFERENCE AVOIDANCE</td></tr>
<tr><td>INPUTS (TX)</td><td>1× HDMI INPUT</td></tr>
<tr><td>OUTPUTS (RX)</td><td>1× HDMI OUTPUT</td></tr>
<tr><td>LOOP OUT (TX)</td><td>HDMI LOOP-OUT FOR ON-CAMERA MONITOR</td></tr>
<tr><td>AUDIO SUPPORT</td><td>EMBEDDED HDMI AUDIO</td></tr>
<tr><td>ANTENNA</td><td>EXTERNAL DETACHABLE DUAL ANTENNAS</td></tr>
<tr><td>POWER INPUT</td><td>USB-C (5–12V)</td></tr>
<tr><td>BATTERY SUPPORT</td><td>SONY NP-F BATTERY COMPATIBLE (F550/F750/F970)</td></tr>
<tr><td>POWER CONSUMPTION</td><td>~6 W</td></tr>
</table></td><td>UNIT</td><td>1</td><td></td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>C.2</td><td>HOLLYLAND PYRO H WIRELESS VIDEO TRANSMISSION (RX) ATAU YANG SETARA
<table><tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr><tr><td>DEVICE TYPE</td><td>WIRELESS VIDEO RECEIVER (RX ONLY)</td></tr><tr><td>COMPATIBLE SYSTEM</td><td>HOLLYLAND PYRO H TRANSMITTER (TX)</td></tr><tr><td>TRANSMISSION BAND</td><td>5 GHZ WIRELESS VIDEO</td></tr><tr><td>MAX RANGE</td><td>UP TO ±400 M LINE-OF-SIGHT (BERGANTUNG PERSEKITARAN)</td></tr><tr><td>LATENCY</td><td>~60 MS</td></tr><tr><td>VIDEO OUTPUT</td><td>1× HDMI OUTPUT</td></tr><tr><td>SUPPORTED RESOLUTION</td><td>UP TO 1080P60 FULL HD</td></tr><tr><td>AUDIO</td><td>EMBEDDED HDMI AUDIO PASS-THROUGH</td></tr><tr><td>CHANNEL SELECTION</td><td>AUTO SCAN & INTERFERENCE AVOIDANCE</td></tr><tr><td>MONITORING</td><td>REAL-TIME CAMERA MONITORING</td></tr><tr><td>ANTENNA</td><td>DUAL EXTERNAL ANTENNAS (DETACHABLE)</td></tr><tr><td>POWER INPUT</td><td>USB-C (5–12V DC)</td></tr><tr><td>BATTERY SUPPORT</td><td>SONY NP-F BATTERY (F550 / F750 / F970)</td></tr><tr><td>POWER CONSUMPTION</td><td>~6 W</td></tr></table></td><td>UNIT</td><td>1</td><td></td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>C.3</td><td>LEMORELE R15 WIRELESS SCREEN SHARING DEVICE ATAU YANG SETARA
<table><tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr><tr><td>DEVICE TYPE</td><td>WIRELESS HDMI SCREEN SHARING SYSTEM (TX + RX)</td></tr><tr><td>TRANSMISSION TECHNOLOGY</td><td>5 GHZ WIRELESS CASTING (POINT-TO-POINT)</td></tr><tr><td>MAX RESOLUTION</td><td>UP TO 1080P FULL HD</td></tr><tr><td>LATENCY</td><td>~50–80 MS (PRESENTATION LATENCY)</td></tr><tr><td>TRANSMISSION RANGE</td><td>±30 M LINE-OF-SIGHT (MEETING ROOM)</td></tr><tr><td>TRANSMITTER (TX)</td><td>USB-C PLUG-AND-PLAY (LAPTOP / TABLET / PHONE)</td></tr><tr><td>RECEIVER (RX)</td><td>HDMI OUTPUT TO TV / PROJECTOR</td></tr><tr><td>POWER INPUT (RX)</td><td>USB-A / USB-C 5V</td></tr><tr><td>OPERATING MODE</td><td>NO WIFI NETWORK REQUIRED</td></tr><tr><td>COMPATIBILITY</td><td>WINDOWS / MACOS / ANDROID / IPADOS (USB-C DP ALT MODE)</td></tr><tr><td>AUDIO</td><td>HDMI AUDIO PASS-THROUGH</td></tr><tr><td>PAIRING</td><td>PRE-PAIRED FACTORY SET</td></tr><tr><td>SECURITY</td><td>PRIVATE PEER-TO-PEER CONNECTION</td></tr></table></td><td>UNIT</td><td>1</td><td></td><td></td></tr>
<tr><td colspan="5">JUMLAH KESELURUHAN (BIL C)</td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>D</td><td>KABEL VIDEO & DATA</td><td></td><td></td><td></td><td></td></tr>
<tr><td>D.1</td><td>KAMEHA KA169R HDMI CABLE 50M ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>1. JENIS KABEL</td><td>ACTIVE HYBRID FIBER HDMI CABLE (OUTDOOR-GRADE ARMOURED)</td></tr>
<tr><td>2. MODEL</td><td>KAMEHA KA169R ATAU SETARA</td></tr>
<tr><td>3. STANDARD HDMI</td><td>HDMI 2.0 / 18 GBPS COMPLIANT</td></tr>
<tr><td>4. LENGTH</td><td>50 M ± 0.3 M</td></tr>
<tr><td>5. SUPPORTED RESOLUTIONS</td><td>UP TO 4K@60 HZ & 1080P (HDTV/PC)</td></tr>
<tr><td>6. HDCP & EDID</td><td>SUPPORT HDCP1.4 / HDCP2.2 & BI-DIRECTIONAL EDID</td></tr>
<tr><td>7. CONNECTOR</td><td>HDMI TYPE-A MALE (STANDARD)</td></tr>
<tr><td>8. CABLE CONSTRUCTION</td><td>ARMOURED HYBRID FIBER + COPPER CONDUCTORS (HIGH CRUSH/ TENSILE RESISTANCE)</td></tr>
<tr><td>9. POWER</td><td>NO EXTERNAL POWER REQUIRED (SELF-POWERED THROUGH HDMI)</td></tr>
<tr><td>10. OPERATING / STORAGE</td><td>-40 °C TO 80 °C</td></tr>
<tr><td>11. PHYSICAL</td><td>MAX OUTER DIAMETER ~5.8 MM</td></tr>
</table></td><td>UNIT</td><td>1</td><td></td><td></td></tr>
<tr><td>D.2</td><td>KAMEHA KA211 HDMI ARMORED CABLE 100M ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>1. JENIS KABEL</td><td>ACTIVE ARMORED FIBER HDMI CABLE</td></tr>
<tr><td>2. MODEL</td><td>KAMEHA KA211 ATAU SETARA</td></tr>
<tr><td>3. STANDARD HDMI</td><td>HDMI 2.1 COMPLIANT, 48 GBPS</td></tr>
<tr><td>4. PANJANG KABEL</td><td>100 M ± TOLERANSI PEMASANGAN</td></tr>
<tr><td rowspan="3">5. SUPPORTED RESOLUTIONS</td><td>• 8K@60 HZ</td></tr>
<tr><td>• 4K@120 HZ</td></tr>
<tr><td>• 4K@60 HZ & KE BAWAH</td></tr>
<tr><td>6. ADVANCED HDMI FEATURES</td><td>EARC, ALLM, VRR, QFT, QMS (VARIABLE REFRESH & FAST TRANSPORT)</td></tr>
<tr><td>7. AUDIO & CODEC SUPPORT</td><td>DTS:X, DOLBY TRUEHD, DOLBY ATMOS, DOLBY VISION, HDR</td></tr>
<tr><td>8. HDCP</td><td>HDCP 1.4, 2.0 & 2.2</td></tr>
<tr><td>9. CONNECTOR</td><td>HDMI TYPE-A MALE TO MALE</td></tr>
<tr><td>10. CONSTRUCTION</td><td>ARMORED OPTICAL FIBER + COPPER HYBRID, DURABLE HOUSING</td></tr>
</table></td><td>UNIT</td><td>1</td><td></td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>D.3</td><td>UGREEN 240W THUNDERBOLT 5 CABLE ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>1. JENIS KABEL</td><td>THUNDERBOLT 5 CERTIFIED / USB4 GEN4 TYPE-C CABLE</td></tr>
<tr><td>2. MAX POWER DELIVERY (PD)</td><td>240W (48V × 5A PD 3.1)</td></tr>
<tr><td>3. DATA TRANSFER BANDWIDTH</td><td>80 GBPS BIDIRECTIONAL</td></tr>
<tr><td>4. VIDEO OUTPUT SUPPORT</td><td>• 16K@60 HZ • DUAL 8K@60 HZ • TRIPLE 4K@144 HZ</td></tr>
<tr><td>5. BACKWARD COMPATIBILITY</td><td>THUNDERBOLT 4/3, USB4, USB-C GEN 3.2/2.0</td></tr>
<tr><td>6. CONNECTOR TYPE</td><td>USB-C MALE TO USB-C MALE (24-PIN)</td></tr>
<tr><td>7. CABLE CONSTRUCTION</td><td>SHIELDED BRAIDED / REINFORCED MATERIAL WITH E-MARKER CHIP</td></tr>
<tr><td>8. E-MARKER / SAFETY</td><td>BUILT-IN E-MARKER CHIP, OVER-VOLTAGE, OVER-CURRENT & OVER-TEMP PROTECTION</td></tr>
<tr><td>9. LENGTH</td><td>TYPICALLY 1 M ± TOLERANCE</td></tr>
<tr><td>10. OPERATING / STORAGE CONDITIONS</td><td>OPERATING: 0–45 °C STORAGE: -15–70 °C</td></tr>
<tr><td>11. COMPLIANCE / CERTS</td><td>INTEL THUNDERBOLT CERTIFICATION (AS APPLICABLE)</td></tr>
</table></td><td>UNIT</td><td>1</td><td></td><td></td></tr>
<tr><td>D.4</td><td>UGREEN DP 1.4 8K60HZ CABLE 3M ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>1. JENIS KABEL</td><td>DISPLAYPORT 1.4 MALE-TO-MALE CABLE</td></tr>
<tr><td>2. MODEL / SERIES</td><td>DP 1.4 8K60HZ – 3 M</td></tr>
<tr><td>3. SUPPORTED RESOLUTION</td><td>• 8K @ 60 HZ • 4K @ 144 HZ • 2K @ 165 HZ</td></tr>
<tr><td>4. BANDWIDTH</td><td>32.4 GBPS (VESA DP1.4)</td></tr>
<tr><td>5. AUDIO SUPPORT</td><td>DIGITAL AUDIO (7.1, 5.1 LPCM)</td></tr>
<tr><td>6. CONNECTOR MATERIAL</td><td>GOLD-PLATED DISPLAYPORT MALE CONNECTORS</td></tr>
<tr><td>7. CABLE CONSTRUCTION</td><td>NYLON BRAIDED JACKET + TRIPLE-SHIELDING</td></tr>
<tr><td>8. CABLE LENGTH</td><td>3 M</td></tr>
<tr><td>9. BACKWARD COMPATIBILITY</td><td>COMPATIBLE DP1.3 / DP1.2 / DP1.1</td></tr>
<tr><td>10. MODE SUPPORT</td><td>MIRROR & EXTEND DISPLAY MODES</td></tr>
<tr><td>11. COMPLIANCE</td><td>VESA DISPLAYPORT 1.4 / HDCP</td></tr>
<tr><td>12. OPERATING CONDITIONS</td><td>STANDARD AMBIENT USE</td></tr>
</table></td><td>UNIT</td><td>1</td><td></td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>D.5</td><td>VENTION MINI HDMI TO HDMI CABLE ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>CABLE TYPE</td><td>MINI HDMI TO STANDARD HDMI CABLE</td></tr>
<tr><td>HDMI VERSION</td><td>HDMI 2.0 COMPLIANT</td></tr>
<tr><td>RESOLUTION SUPPORT</td><td>UP TO 4K @ 60HZ (3840 × 2160)</td></tr>
<tr><td>BANDWIDTH</td><td>UP TO 18 GBPS HIGH-SPEED TRANSMISSION</td></tr>
<tr><td>VIDEO FEATURES</td><td>HDR VIDEO, 3D VIDEO, DEEP COLOR SUPPORT</td></tr>
<tr><td>AUDIO SUPPORT</td><td>MULTI-CHANNEL DIGITAL AUDIO (DOLBY / DTS PASS-THROUGH)</td></tr>
<tr><td>CONNECTOR MATERIAL</td><td>GOLD-PLATED CORROSION-RESISTANT CONNECTORS</td></tr>
<tr><td>CONDUCTOR MATERIAL</td><td>OXYGEN-FREE COPPER (OFC) CORE</td></tr>
<tr><td>SHIELDING</td><td>MULTI-LAYER SHIELDING (FOIL + BRAIDED SHIELDING)</td></tr>
<tr><td>JACKET TYPE</td><td>PVC OR NYLON BRAIDED OUTER JACKET (MODEL DEPENDENT)</td></tr>
<tr><td>PLUG TYPE</td><td>MINI HDMI TYPE-C (MALE) TO HDMI TYPE-A (MALE)</td></tr>
<tr><td>PLUG & PLAY</td><td>YES (NO DRIVER REQUIRED)</td></tr>
<tr><td>COMPATIBILITY</td><td>DSLR CAMERA, MIRRORLESS CAMERA, FIELD MONITOR, PROJECTOR, TV, CAPTURE CARD</td></tr>
</table></td><td>UNIT</td><td>1</td><td></td><td></td></tr>
<tr><td colspan="5">JUMLAH KESELURUHAN (BIL D)</td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>E</td><td>PERKAKASAN DALAMAN</td><td></td><td></td><td></td><td></td></tr>
<tr><td>E.1</td><td>KINGSTON NV3 NVME SSD 1TB ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>1. FORM FACTOR</td><td>NVME PCIE 4.0 X4 SSD, M.2 2280</td></tr>
<tr><td>2. KAPASITI</td><td>1 TB USABLE STORAGE (MINIMUM 1 TB)</td></tr>
<tr><td>3. INTERFACE</td><td>PCIE GEN4 X4 (NVME 1.4)</td></tr>
<tr><td rowspan="2">4. SEQUENTIAL PERFORMANCE</td><td>READ 6000 MB/S</td></tr>
<tr><td>WRITE 4000 MB/S</td></tr>
<tr><td rowspan="2">5. NAND & ENDURANCE</td><td>3D NAND</td></tr>
<tr><td>ENDURANCE TBW 320 TB</td></tr>
<tr><td>6. RELIABILITY</td><td>MTBF 2,000,000 JAM</td></tr>
<tr><td rowspan="2">7. OPERATING CONDITIONS</td><td>OPERATING TEMP: 0 °C–70 °C</td></tr>
<tr><td>STORAGE TEMP: -40 °C–85 °C</td></tr>
<tr><td>8. PHYSICAL</td><td>DIMENSION: 22 MM × 80 MM</td></tr>
<tr><td>9. WARRANTY</td><td>MINIMUM 5 TAHUN LIMITED WARRANTY ATAU SETARA</td></tr>
</table></td><td>UNIT</td><td>1</td><td></td><td></td></tr>
<tr><td>E.2</td><td>GIGABYTE GEFORCE RTX 5060 WINDFORCE MAX OC 8G GDDR7 ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>GPU ARCHITECTURE</td><td>NVIDIA ADA-NEXT ARCHITECTURE</td></tr>
<tr><td>GRAPHICS PROCESSOR</td><td>GEFORCE RTX 5060</td></tr>
<tr><td>CUDA CORES</td><td>~3840 CORES</td></tr>
<tr><td>BOOST CLOCK</td><td>±2.5 GHZ (FACTORY OVERCLOCK – WINDFORCE OC)</td></tr>
<tr><td>MEMORY TYPE</td><td>GDDR7</td></tr>
<tr><td>MEMORY SIZE</td><td>8 GB</td></tr>
<tr><td>MEMORY INTERFACE</td><td>128-BIT</td></tr>
<tr><td>MEMORY SPEED</td><td>±28 GBPS EFFECTIVE</td></tr>
<tr><td>MEMORY BANDWIDTH</td><td>~448 GB/S</td></tr>
<tr><td>RAY TRACING CORES</td><td>3RD/4TH GEN RT CORES (HARDWARE RAY TRACING)</td></tr>
<tr><td>TENSOR CORES</td><td>AI TENSOR CORES (DLSS / AI ACCELERATION)</td></tr>
<tr><td>PCI EXPRESS</td><td>PCIE 4.0 X8 INTERFACE</td></tr>
<tr><td>MAX RESOLUTION</td><td>UP TO 7680 × 4320 (8K)</td></tr>
<tr><td>MULTI-DISPLAY SUPPORT</td><td>UP TO 4 DISPLAYS</td></tr>
</table></td><td>UNIT</td><td>1</td><td></td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>E.3</td><td>MICRON 16GB DDR4 ECC UDIMM CL22 ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>MEMORY TYPE</td><td>DDR4 ECC UDIMM (ERROR-CORRECTING CODE UNBUFFERED DIMM)</td></tr>
<tr><td>CAPACITY</td><td>16 GB</td></tr>
<tr><td>SPEED</td><td>3200 MT/S (PC4-25600)</td></tr>
<tr><td>CAS LATENCY</td><td>CL22</td></tr>
<tr><td>MODULE FORM FACTOR</td><td>288-PIN DIMM</td></tr>
<tr><td>VOLTAGE</td><td>1.2 V</td></tr>
<tr><td>DATA WIDTH</td><td>72-BIT (64-BIT DATA + 8-BIT ECC PARITY)</td></tr>
<tr><td>BUFFERED TYPE</td><td>UNBUFFERED (UDIMM)</td></tr>
<tr><td>ECC SUPPORT</td><td>YES – SINGLE-BIT ERROR CORRECTION</td></tr>
<tr><td>OPERATING TEMPERATURE</td><td>0 °C – 85 °C</td></tr>
<tr><td>COMPATIBILITY</td><td>SERVER & WORKSTATION</td></tr>
</table></td><td>UNIT</td><td>1</td><td></td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>E.4</td><td>COOLER MASTER MWE GOLD 750 - FULL MODULAR ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>PRODUCT TYPE</td><td>ATX FULLY MODULAR POWER SUPPLY UNIT</td></tr>
<tr><td>RATED POWER OUTPUT</td><td>750 WATTS</td></tr>
<tr><td>EFFICIENCY CERTIFICATION</td><td>80 PLUS GOLD</td></tr>
<tr><td>TYPICAL EFFICIENCY</td><td>UP TO ~90% EFFICIENCY AT TYPICAL LOAD</td></tr>
<tr><td>INPUT VOLTAGE</td><td>100 – 240V AC</td></tr>
<tr><td>INPUT FREQUENCY</td><td>50 – 60 HZ</td></tr>
<tr><td>POWER FACTOR CORRECTION</td><td>ACTIVE PFC</td></tr>
<tr><td>PROTECTION FEATURES</td><td>OVP, UVP, OPP, OTP, SCP, OCP PROTECTION</td></tr>
<tr><td>+12V RAIL</td><td>SINGLE RAIL DESIGN</td></tr>
<tr><td>+12V MAXIMUM OUTPUT</td><td>UP TO 744 W</td></tr>
<tr><td>+5V RAIL</td><td>20 A</td></tr>
<tr><td>+3.3V RAIL</td><td>20 A</td></tr>
<tr><td>STANDBY POWER</td><td>+5VSB 3 A</td></tr>
<tr><td>MODULARITY</td><td>FULLY MODULAR CABLE MANAGEMENT</td></tr>
<tr><td>COOLING FAN</td><td>120 MM HDB (HYDRO DYNAMIC BEARING) FAN</td></tr>
<tr><td>FAN CONTROL</td><td>TEMPERATURE CONTROLLED SMART FAN</td></tr>
<tr><td>MTBF</td><td>>100,000 HOURS</td></tr>
<tr><td>OPERATING TEMPERATURE</td><td>0°C – 50°C AMBIENT</td></tr>
<tr><td>FORM FACTOR</td><td>ATX</td></tr>
<tr><td>DIMENSIONS</td><td>APPROX. 160 × 150 × 86 MM</td></tr>
<tr><td>MAIN CONNECTOR</td><td>1 × 24-PIN ATX</td></tr>
<tr><td>CPU CONNECTOR</td><td>2 × 8-PIN (4+4) EPS</td></tr>
<tr><td>PCIE CONNECTOR</td><td>4 × 6+2 PIN PCIE</td></tr>
<tr><td>SATA CONNECTOR</td><td>8</td></tr>
<tr><td>PERIPHERAL CONNECTOR</td><td>4 × MOLEX</td></tr>
<tr><td>CABLE TYPE</td><td>FLAT BLACK MODULAR CABLES</td></tr>
<tr><td>DESIGN TOPOLOGY</td><td>DC-TO-DC VOLTAGE REGULATION</td></tr>
</table></td><td>UNIT</td><td>1</td><td></td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>E.5</td><td>ADATA DDR5 RAM 16GB (DESKTOP) ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>PRODUCT TYPE</td><td>DESKTOP MEMORY MODULE (RAM)</td></tr>
<tr><td>MEMORY TYPE</td><td>DDR5 SDRAM</td></tr>
<tr><td>CAPACITY</td><td>16GB (1 × 16GB MODULE)</td></tr>
<tr><td>FORM FACTOR</td><td>288-PIN U-DIMM (DESKTOP)</td></tr>
<tr><td>MEMORY SPEED</td><td>UP TO 5600 MHZ</td></tr>
<tr><td>JEDEC BASE SPEED</td><td>4800 MHZ</td></tr>
<tr><td>CAS LATENCY</td><td>APPROX. CL46</td></tr>
<tr><td>VOLTAGE</td><td>1.1V OPERATING VOLTAGE</td></tr>
<tr><td>ERROR CORRECTION</td><td>ON-DIE ECC (INTERNAL ERROR CORRECTION)</td></tr>
<tr><td>POWER MANAGEMENT</td><td>BUILT-IN PMIC (POWER MANAGEMENT IC)</td></tr>
<tr><td>BANDWIDTH</td><td>UP TO ~38.4 GB/S DATA BANDWIDTH</td></tr>
<tr><td>COMPATIBILITY</td><td>LATEST INTEL & AMD DESKTOP PLATFORMS</td></tr>
<tr><td>PERFORMANCE FEATURE</td><td>HIGHER FREQUENCY VS DDR4-3200</td></tr>
<tr><td>UPGRADE SUPPORT</td><td>SINGLE-MODULE UPGRADE COMPATIBLE</td></tr>
<tr><td>WARRANTY</td><td>LIMITED LIFETIME WARRANTY</td></tr>
</table></td><td>UNIT</td><td>1</td><td></td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>E.6</td><td>AIGO GP650 POWER SUPPLY ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>MINIMUM SPECIFICATION</th></tr>
<tr><td>PRODUCT TYPE</td><td>ATX DESKTOP COMPUTER POWER SUPPLY UNIT (PSU)</td></tr>
<tr><td>RATED POWER</td><td>650W</td></tr>
<tr><td>PEAK POWER</td><td>UP TO 750W – 850W</td></tr>
<tr><td>EFFICIENCY CERTIFICATION</td><td>80 PLUS BRONZE</td></tr>
<tr><td>EFFICIENCY</td><td>APPROXIMATELY UP TO 80–85% EFFICIENCY</td></tr>
<tr><td>FORM FACTOR</td><td>INTEL ATX 12V STANDARD</td></tr>
<tr><td>PFC TYPE</td><td>ACTIVE PFC</td></tr>
<tr><td>COOLING SYSTEM</td><td>120MM HYDRAULIC BEARING COOLING FAN</td></tr>
<tr><td>INPUT VOLTAGE</td><td>160V – 264V AC</td></tr>
<tr><td>INPUT FREQUENCY</td><td>50–60 HZ</td></tr>
<tr><td>PROTECTION FEATURES</td><td>OCP, OVP, UVP, SCP, OPP, OTP PROTECTION</td></tr>
<tr><td rowspan="5">CONNECTOR</td><td>1 × 20+4 PIN ATX</td></tr>
<tr><td>2 × 4+4 PIN CPU</td></tr>
<tr><td>4 × 6+2 PIN PCIE</td></tr>
<tr><td>4 × SATA POWER CONNECTORS</td></tr>
<tr><td>2 × MOLEX CONNECTORS</td></tr>
<tr><td>COOLING CONTROL</td><td>PWM TEMPERATURE CONTROL FAN</td></tr>
<tr><td>COMPATIBILITY</td><td>SUPPORTS INTEL AND AMD PLATFORM</td></tr>
</table></td><td>UNIT</td><td>1</td><td></td><td></td></tr>
<tr><td colspan="5">JUMLAH KESELURUHAN (BIL E)</td><td></td></tr>
</table>

BIL.	KETERANGAN	UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)
F	SAMBUNGAN PERANTI				

BIL.	KETERANGAN	UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)
F.1	UGREEN 10GBPS 9-IN-1 USB-C HUB ATAU YANG SETARA	UNIT	1		

ITEM	SPESIFIKASI MINIMUM
DEVICE TYPE	USB-C MULTIPORT DOCKING HUB
HOST INTERFACE	USB-C MALE CONNECTOR
USB STANDARD	USB 3.2 GEN 2
MAXIMUM DATA SPEED	UP TO 10 GBPS
PLUG & PLAY	YES (NO DRIVER INSTALLATION REQUIRED)
HOUSING MATERIAL	ALUMINIUM ALLOY (PASSIVE HEAT DISSIPATION)
CABLE LENGTH	BUILT-IN CABLE ±15–20 CM
HDMI OUTPUT	4K @ 60HZ (3840 × 2160)
USB-C POWER DELIVERY	UP TO 100W PASSTHROUGH CHARGING (85–95W TO LAPTOP)
USB-C DATA PORT	10 GBPS HIGH-SPEED DATA
USB-A 3.2 GEN2	10 GBPS (EXTERNAL SSD / STORAGE)
USB-A 3.0 ×2	5 GBPS (KEYBOARD, MOUSE, PRINTER)
RJ45 LAN	GIGABIT ETHERNET 10/100/1000 MBPS
SD CARD SLOT	SD / SDHC / SDXC (UHS-I)
MICROSD SLOT	MICROSD / MICROSDHC / MICROSDXC
MAXIMUM DISPLAY RESOLUTION	3840 × 2160 @ 60HZ
DISPLAY MODE	MIRROR & EXTENDED DISPLAY
VIDEO STANDARD	DISPLAYPORT ALT MODE VIA USB-C
HDR	SUPPORTED (DEPENDING ON LAPTOP & MONITOR)
CHARGING PROTOCOL	USB-C POWER DELIVERY (PD 3.0)
POWER INPUT	UP TO 100W
LAPTOP CHARGING	CHARGING SUPPORTED WHILE ALL PORTS ARE IN USE
NETWORK CONTROLLER	GIGABIT ETHERNET CONTROLLER
LAN SPEED	10 / 100 / 1000 MBPS AUTO-NEGOTIATION
LAN DRIVER	AUTO-DETECT WINDOWS / MACOS / LINUX
MEMORY CARD STANDARD	UHS-I
CARD READER SPEED	±104 MB/S (THEORETICAL)
SIMULTANEOUS READING	SD & MICROSD SIMULTANEOUSLY
SYSTEM COMPATIBILITY	WINDOWS 10/11, MACOS, LINUX (BASIC), IPADOS USB-C, ANDROID USB-C DP ALT MODE
COOLING SYSTEM	PASSIVE COOLING VIA ALUMINIUM HOUSING

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>F.2</td><td>UGREEN 6-IN-1 USB HUB ATAU YANG SETARA
<table><tr><td>ITEM</td><td>SPESIFIKASI MINIMUM</td></tr><tr><td>HDMI OUTPUT</td><td>1 × HDMI SEHINGGA 4K @ 60HZ</td></tr><tr><td>USB-A</td><td>2 × USB-A 3.2 GEN2 (10GBPS DATA TRANSFER)</td></tr><tr><td>USB-C DATA</td><td>1 × USB-C 3.2 GEN2 (10GBPS DATA TRANSFER)</td></tr><tr><td>USB-C PD</td><td>1 × USB-C POWER DELIVERY SEHINGGA 100W PASSTHROUGH CHARGING</td></tr><tr><td>LAN PORT</td><td>1 × RJ45 GIGABIT ETHERNET (10/100/1000 MBPS)</td></tr></table></td><td>UNIT</td><td>1</td><td></td><td></td></tr>
<tr><td>F.3</td><td>VENTION 15-IN-1 USB-C MST DOCKING STATION ATAU YANG SETARA
<table><tr><td>ITEM</td><td>SPESIFIKASI MINIMUM</td></tr><tr><td>EXPANSION PORTS</td><td>15-IN-1 PORTS: HDMI, DISPLAYPORT (MST), USB-A, USB-C, RJ45 ETHERNET, SD/TF CARD READER, 3.5MM AUDIO JACK</td></tr><tr><td>MULTI-DISPLAY SUPPORT</td><td>SUPPORTS MST (MULTI-STREAM TRANSPORT) FOR MULTIPLE EXTERNAL DISPLAYS</td></tr><tr><td>DATA TRANSFER</td><td>USB 3.2 HIGH-SPEED DATA TRANSMISSION</td></tr><tr><td>POWER DELIVERY</td><td>USB-C POWER DELIVERY PASS-THROUGH CHARGING SUPPORTED</td></tr><tr><td>NETWORK INTERFACE</td><td>GIGABIT ETHERNET VIA RJ45 PORT</td></tr><tr><td>CARD READER</td><td>SD AND MICROSD (TF) MEMORY CARD SUPPORT</td></tr><tr><td>AUDIO</td><td>3.5 MM HEADPHONE / MICROPHONE COMBO PORT</td></tr><tr><td>HOUSING MATERIAL</td><td>ALUMINIUM BODY WITH TPU PROTECTIVE FINISHING</td></tr><tr><td>COMPATIBILITY</td><td>USB-C LAPTOPS SUPPORTING DISPLAYPORT ALT MODE</td></tr><tr><td>INSTALLATION</td><td>PLUG-AND-PLAY (NO ADDITIONAL DRIVER REQUIRED)</td></tr></table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>F.4</td><td>UGREEN USB 3.0 EXTENSION CABLE 3M
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>PRODUCT TYPE</td><td>USB 3.0 EXTENSION CABLE (MALE TO FEMALE)</td></tr>
<tr><td>CABLE LENGTH</td><td>3 METER (±10%)</td></tr>
<tr><td>USB STANDARD</td><td>USB 3.0 SUPERSPEED</td></tr>
<tr><td>DATA TRANSFER RATE</td><td>UP TO 5 GBPS</td></tr>
<tr><td>CONNECTOR TYPE</td><td>USB TYPE-A MALE TO USB TYPE-A FEMALE</td></tr>
<tr><td>BACKWARD COMPATIBILITY</td><td>COMPATIBLE WITH USB 2.0 & USB 1.1 DEVICES</td></tr>
<tr><td>CONDUCTOR MATERIAL</td><td>TINNED COPPER / HIGH-CONDUCTIVITY COPPER CORE</td></tr>
<tr><td>SHIELDING</td><td>MULTI-LAYER SHIELDING (ALUMINIUM FOIL + BRAIDED SHIELDING)</td></tr>
<tr><td>CONNECTOR PLATING</td><td>GOLD-PLATED CONNECTORS FOR CORROSION RESISTANCE</td></tr>
<tr><td>CABLE GAUGE</td><td>APPROX. 24/28 AWG (DATA & POWER LINES)</td></tr>
<tr><td>POWER SUPPORT</td><td>SUPPORTS USB BUS-POWERED DEVICES (KEYBOARD, MOUSE, FLASH DRIVE, WEBCAM, DONGLE)</td></tr>
<tr><td>INSULATION</td><td>PVC OR EQUIVALENT DURABLE OUTER JACKET</td></tr>
<tr><td>PLUG & PLAY</td><td>NO DRIVER REQUIRED</td></tr>
<tr><td>OPERATING SYSTEM SUPPORT</td><td>WINDOWS, MACOS, LINUX COMPATIBLE</td></tr>
<tr><td>APPLICATION</td><td>EXTENSION FOR USB PERIPHERALS SUCH AS KEYBOARD, MOUSE, PRINTER, WEBCAM, WIFI/BLUETOOTH ADAPTER & STORAGE DEVICES</td></tr>
<tr><td>SAFETY</td><td>OVER-SIGNAL LOSS PROTECTION WITH STABLE DATA TRANSMISSION</td></tr>
<tr><td>WARRANTY</td><td>MINIMUM 12 MONTHS</td></tr>
</table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
<tr><td colspan="5">JUMLAH KESELURUHAN (BIL F)</td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>G</td><td>INPUT DEVICE</td><td></td><td></td><td></td><td></td></tr>
<tr><td>G.1</td><td>APPLE MAGIC KEYBOARD FOR IPAD PRO 11 INCH M4/M5 ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>1. JENIS PERANTI</td><td>AKSESORI KEYBOARD & TRACKPAD UNTUK IPAD</td></tr>
<tr><td>2. MODEL & COMPATIBILITY</td><td>IPAD PRO 11-INCH (M5) & BACKWARD COMPATIBLE M4</td></tr>
<tr><td>3. KEYBOARD TYPE</td><td>FULL-SIZE BACKLIT KEYBOARD DENGAN SCISSOR MECHANISM</td></tr>
<tr><td>4. TRACKPAD</td><td>LARGE GLASS TRACKPAD WITH HAPTIC FEEDBACK</td></tr>
<tr><td>5. FUNCTION ROW</td><td>14-KEY FUNCTION ROW (BRIGHTNESS, VOLUME, MEDIA, ETC.)</td></tr>
<tr><td>6. CONNECTIVITY / INTERFACE</td><td>MAGNETIC ATTACH + USB-C PASS-THROUGH CHARGING</td></tr>
<tr><td>7. VIEWING ADJUSTABILITY</td><td>FLOATING CANTILEVER DESIGN UNTUK MULTIPLE ANGLES</td></tr>
<tr><td>8. PROTECTION / FORM FACTOR</td><td>FRONT & BACK PROTECTION CASE FOR IPAD</td></tr>
<tr><td>9. MATERIAL & BUILD</td><td>ALUMINIUM PALM REST & PREMIUM BUILD QUALITY</td></tr>
</table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>G.2</td><td>KEYCHRON BLACK MYTH WUKONG WIRELESS MECHANICAL (DELUXE EDITION) ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>PRODUCT TYPE</td><td>WIRELESS MECHANICAL KEYBOARD – DELUXE EDITION THEMED BUNDLE</td></tr>
<tr><td>LAYOUT</td><td>75% ANSI COMPACT LAYOUT (WITH FUNCTION ROW, WITHOUT NUMERIC KEYPAD)</td></tr>
<tr><td>MOUNTING STRUCTURE</td><td>GASKET MOUNT DESIGN</td></tr>
<tr><td>BODY MATERIAL</td><td>ALUMINIUM TOP FRAME WITH REINFORCED BASE CONSTRUCTION</td></tr>
<tr><td>PLATE MATERIAL</td><td>STEEL / ALUMINIUM SWITCH PLATE</td></tr>
<tr><td>SWITCH TYPE</td><td>MECHANICAL TACTILE SWITCH – BLUISH WHITE (NON-CLICKY, LOW NOISE)</td></tr>
<tr><td>SWITCH FEEDBACK</td><td>TACTILE FEEDBACK SUITABLE FOR LONG TYPING SESSIONS</td></tr>
<tr><td>HOT-SWAP SUPPORT</td><td>YES (COMPATIBLE WITH 3-PIN & 5-PIN MX SWITCHES)</td></tr>
<tr><td>CONNECTIVITY</td><td>USB-C WIRED, 2.4 GHZ WIRELESS RECEIVER, BLUETOOTH 5.1</td></tr>
<tr><td>MULTI-DEVICE PAIRING</td><td>MINIMUM 3 BLUETOOTH DEVICES</td></tr>
<tr><td>POLLING RATE</td><td>UP TO 1000 HZ (WIRED & 2.4 GHZ)</td></tr>
<tr><td>KEY ROLLOVER</td><td>FULL N-KEY ROLLOVER (NKRO)</td></tr>
<tr><td>BACKLIGHT</td><td>PER-KEY RGB BACKLIGHT (SOUTH-FACING LED)</td></tr>
<tr><td>PROGRAMMABILITY</td><td>QMK / VIA PROGRAMMABLE FIRMWARE WITH MACRO SUPPORT</td></tr>
<tr><td>ONBOARD MEMORY</td><td>PROFILE & MACRO STORAGE SUPPORTED</td></tr>
<tr><td>KEYCAPS</td><td>PREMIUM THEMED PBT KEYCAPS (SPECIAL EDITION DYE-SUBLIMATION / DOUBLE-SHOT)</td></tr>
<tr><td>STEM COMPATIBILITY</td><td>MX-STYLE CROSS STEM COMPATIBLE</td></tr>
<tr><td>ROTARY ENCODER</td><td>PROGRAMMABLE CONTROL KNOB INCLUDED</td></tr>
<tr><td>BATTERY</td><td>BUILT-IN RECHARGEABLE BATTERY 4000 MAH</td></tr>
<tr><td>CHARGING INTERFACE</td><td>DETACHABLE USB-C CABLE</td></tr>
<tr><td>COMPATIBILITY</td><td>WINDOWS, MACOS & LINUX COMPATIBLE</td></tr>
<tr><td>TYPING ANGLE</td><td>ADJUSTABLE MULTI-ANGLE FEET</td></tr>
<tr><td>DELUXE ACCESSORIES</td><td>THEMED DESK MAT, ARTISAN / EXTRA</td></tr>
</table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>G.3</td><td>LENOVO PREFERRED PRO II USB KEYBOARD ATAU YANG SETARA
<table>
<tr><td>ITEM</td><td>SPESIFIKASI MINIMUM</td></tr>
<tr><td>KEYBOARD TYPE</td><td>FULL-SIZE WIRED MEMBRANE KEYBOARD</td></tr>
<tr><td>LAYOUT</td><td>STANDARD 104-KEY (FULL SIZE WITH NUMPAD)</td></tr>
<tr><td>INTERFACE</td><td>USB TYPE-A</td></tr>
<tr><td>KEY TECHNOLOGY</td><td>QUIET MEMBRANE SWITCH (LOW-FORCE ACTUATION)</td></tr>
<tr><td>KEY PROFILE</td><td>LOW-PROFILE ERGONOMIC KEYS</td></tr>
<tr><td>KEY LIFE CYCLE</td><td>±10 MILLION KEYSTROKES (TYPICAL MEMBRANE RATING)</td></tr>
<tr><td>MULTIMEDIA KEYS</td><td>DEDICATED HOTKEYS (VOLUME, MUTE, MEDIA CONTROL)</td></tr>
<tr><td>SHORTCUT KEYS</td><td>WINDOWS FUNCTION SHORTCUTS (FN KEY SUPPORT)</td></tr>
<tr><td>SPILL RESISTANCE</td><td>BASIC SPILL-RESISTANT DESIGN</td></tr>
<tr><td>LED INDICATORS</td><td>NUM LOCK • CAPS LOCK • SCROLL LOCK INDICATORS</td></tr>
<tr><td>CABLE LENGTH</td><td>±1.8 METER</td></tr>
<tr><td>PLUG & PLAY</td><td>YES</td></tr>
<tr><td>COMPATIBILITY</td><td>WINDOWS 7 / 8 / 10 / 11 • LINUX BASIC SUPPORT</td></tr>
<tr><td>POWER SOURCE</td><td>USB POWERED</td></tr>
</table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>G.4</td><td>LOGITECH SIGNATURE M650 MOUSE ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>CONNECTION TYPE</td><td>• LOGI BOLT USB RECEIVER (2.4 GHZ) • BLUETOOTH LOW ENERGY (BLE)</td></tr>
<tr><td>WIRELESS RANGE</td><td>UP TO 10 M (DEPENDING ON ENVIRONMENT)</td></tr>
<tr><td>SENSOR TECHNOLOGY</td><td>LOGITECH ADVANCED OPTICAL TRACKING</td></tr>
<tr><td>DPI (MIN–MAX)</td><td>400 - 4,000 DPI</td></tr>
<tr><td>BUTTONS</td><td>5 TOTAL: LEFT/RIGHT CLICK, BACK/FORWARD, SCROLL WHEEL (MIDDLE CLICK)</td></tr>
<tr><td>SMARTWHEEL SCROLLING</td><td>PRECISION LINE-BY-LINE OR FAST SCROLL (AUTO SWITCH)</td></tr>
<tr><td>SILENT TOUCH TECHNOLOGY</td><td>CLICK NOISE REDUCED 90 % VS STANDARD MOUSE</td></tr>
<tr><td>BATTERY</td><td>1× AA BATTERY (INCLUDED)</td></tr>
<tr><td>BATTERY LIFE</td><td>• LOGI BOLT: ~24 MONTHS • BLUETOOTH: ~20 MONTHS</td></tr>
<tr><td>INDICATOR LIGHTS</td><td>LED BATTERY & CONNECTIVITY INDICATORS</td></tr>
<tr><td>DIMENSIONS</td><td></td></tr>
<tr><td>WEIGHT</td><td>~101.4 G (WITH BATTERY)</td></tr>
<tr><td>COMPATIBILITY OS</td><td>WINDOWS, MACOS, LINUX, CHROMEOS, IPADOS, ANDROID</td></tr>
<tr><td>CUSTOMIZATION APP</td><td>SUPPORTED VIA LOGI OPTIONS+ (WINDOWS/MACOS)</td></tr>
<tr><td>SUSTAINABILITY MATERIAL</td><td>POST-CONSUMER RECYCLED PLASTIC (GRAPHITE 64 %)</td></tr>
</table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>G.5</td><td>ACER ERGONOMIC VERTICAL COMPUTER MOUSE ATAU YANG SETARA
<table><tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr><tr><td>DEVICE TYPE</td><td>ERGONOMIC VERTICAL COMPUTER MOUSE</td></tr><tr><td>CONNECTION TYPE</td><td>2.4 GHZ WIRELESS USB RECEIVER</td></tr><tr><td>SENSOR TYPE</td><td>OPTICAL SENSOR</td></tr><tr><td>DPI RESOLUTION</td><td>ADJUSTABLE DPI (TYPICALLY 800 / 1200 / 1600 DPI)</td></tr><tr><td>BUTTONS</td><td>6 BUTTONS (LEFT, RIGHT, SCROLL, DPI SWITCH, FORWARD, BACK)</td></tr><tr><td>ERGONOMIC DESIGN</td><td>VERTICAL HAND-SHAKE GRIP POSITION</td></tr><tr><td>SCROLL WHEEL</td><td>ANTI-SLIP RUBBERIZED WHEEL</td></tr><tr><td>COMPATIBILITY</td><td>WINDOWS / MACOS / LINUX BASIC SUPPORT</td></tr><tr><td>PLUG & PLAY</td><td>YES (NO DRIVER REQUIRED)</td></tr><tr><td>WIRELESS RANGE</td><td>±8–10 METERS</td></tr><tr><td>RECEIVER TYPE</td><td>NANO USB RECEIVER (2.4GHZ RF)</td></tr></table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>G.6</td><td>ZEBRA DS2278 (SR7U2100PRW) CORDLESS 2D BARCODE SCANNER ATAU YANG SETARA
<table><tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr><tr><td>JENIS PERANTI</td><td>CORDLESS 2D IMAGER BARCODE SCANNER</td></tr><tr><td>SCANNING TECHNOLOGY</td><td>AREA IMAGING (DIGITAL IMAGER SENSOR)</td></tr><tr><td>SUPPORTED CODES</td><td>1D & 2D BARCODE (QR CODE, DATAMATRIX, PDF417, CODE128, EAN, DLL)</td></tr><tr><td>CONNECTIVITY</td><td>BLUETOOTH WIRELESS</td></tr><tr><td>WIRELESS RANGE</td><td>±10 M (TYPICAL INDOOR)</td></tr><tr><td>INTERFACE SUPPORT</td><td>USB HID, USB COM, RS232 (VIA CRADLE)</td></tr><tr><td>AIMING PATTERN</td><td>LED AIMER</td></tr><tr><td>TRIGGER MODE</td><td>MANUAL TRIGGER & PRESENTATION MODE</td></tr><tr><td>MOTION TOLERANCE</td><td>±13 CM/SEC</td></tr><tr><td>DROP RESISTANCE</td><td>DROP RESISTANCE UP TO APPROXIMATELY 1.5 M ONTO A CONCRETE SURFACE</td></tr><tr><td>SEALING RATING</td><td>IP42</td></tr><tr><td>BATTERY TYPE</td><td>RECHARGEABLE LI-ION</td></tr><tr><td>BATTERY CAPACITY</td><td>±2400 MAH</td></tr><tr><td>SCAN PER CHARGE</td><td>±14,000 SCANS</td></tr><tr><td>CHARGING METHOD</td><td>CHARGING CRADLE (BASE STATION)</td></tr><tr><td>CHARGING TIME</td><td>±4 HOUR FULL</td></tr><tr><td>INDICATOR</td><td>LED + BEEP + VIBRATION FEEDBACK</td></tr></table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>G.7</td><td>DELL G3-15 KEYBOARD ATAU YANG SETARA
<table><tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr><tr><td>DEVICE TYPE</td><td>INTERNAL LAPTOP REPLACEMENT KEYBOARD</td></tr><tr><td>COMPATIBILITY SERIES</td><td>DELL G3 15 SERIES</td></tr><tr><td>KEYBOARD LAYOUT</td><td>FULL-SIZE LAPTOP LAYOUT WITH NUMERIC KEYPAD</td></tr><tr><td>BACKLIGHT</td><td>WHITE OR RED BACKLIT</td></tr><tr><td>INTERFACE</td><td>RIBBON CABLE</td></tr><tr><td>KEY TYPE</td><td>MEMBRANE SCISSOR-SWITCH LAPTOP KEYS</td></tr><tr><td>KEY MATERIAL</td><td>ABS KEYCAPS</td></tr><tr><td>LANGUAGE LAYOUT</td><td>US</td></tr><tr><td>INSTALLATION TYPE</td><td>INTERNAL REPLACEMENT</td></tr><tr><td>OPERATING VOLTAGE</td><td>POWERED VIA MOTHERBOARD CONNECTOR</td></tr><tr><td>FUNCTION KEYS</td><td>MULTIMEDIA HOTKEYS & FN SHORTCUTS SUPPORTED</td></tr></table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>G.8</td><td>KEYCHRON Q6 ULTRA MECHANICAL KEYBOARD ATAU YANG SETARA
<table><tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr><tr><td>PRODUCT TYPE</td><td>FULL-SIZE WIRELESS MAGNETIC MECHANICAL KEYBOARD</td></tr><tr><td>LAYOUT</td><td>100% ANSI LAYOUT WITH DEDICATED NUMERIC KEYPAD</td></tr><tr><td>MOUNTING STRUCTURE</td><td>DOUBLE-GASKET MOUNT DESIGN</td></tr><tr><td>BODY MATERIAL</td><td>CNC-MACHINED FULL ALUMINIUM CHASSIS</td></tr><tr><td>PLATE MATERIAL</td><td>ALUMINIUM / STEEL SWITCH PLATE</td></tr><tr><td>SWITCH TECHNOLOGY</td><td>HALL-EFFECT MAGNETIC SWITCH</td></tr><tr><td>KEY FEEL REQUIREMENT</td><td>TACTILE / BROWN-TYPE FEEDBACK (NON-CLICKY, LOW NOISE OPERATION)</td></tr><tr><td>ADJUSTABLE ACTUATION</td><td>APPROX. 0.1 MM – 4.0 MM ADJUSTABLE ACTUATION DISTANCE</td></tr><tr><td>RAPID TRIGGER</td><td>SUPPORTED (DYNAMIC RESET INPUT DETECTION)</td></tr><tr><td>CONNECTIVITY</td><td>USB-C WIRED, 2.4 GHZ WIRELESS RECEIVER, BLUETOOTH 5.3</td></tr><tr><td>MULTI-DEVICE PAIRING</td><td>MINIMUM 3 BLUETOOTH DEVICES</td></tr><tr><td>POLLING RATE</td><td>UP TO 8000 HZ (WIRED / 2.4 GHZ MODE)</td></tr><tr><td>KEY ROLLOVER</td><td>FULL N-KEY ROLLOVER (NKRO)</td></tr><tr><td>BACKLIGHT</td><td>PER-KEY RGB BACKLIGHT (SOUTH-FACING LED)</td></tr><tr><td>PROGRAMMABILITY</td><td>QMK / VIA PROGRAMMABLE FIRMWARE WITH MACRO SUPPORT</td></tr><tr><td>ONBOARD MEMORY</td><td>SUPPORT PROFILE AND MACRO STORAGE</td></tr><tr><td>COMPATIBILITY</td><td>WINDOWS, MACOS & LINUX COMPATIBLE</td></tr><tr><td>KEYCAP SUPPORT</td><td>COMPATIBLE WITH MX-STYLE KEYCAPS</td></tr><tr><td>ROTARY ENCODER</td><td>PROGRAMMABLE CONTROL KNOB INCLUDED</td></tr><tr><td>BATTERY</td><td>BUILT-IN RECHARGEABLE BATTERY 4000 MAH</td></tr><tr><td>CHARGING INTERFACE</td><td>DETACHABLE USB-C CABLE</td></tr><tr><td>TYPING ANGLE</td><td>ADJUSTABLE MULTI-ANGLE FEET</td></tr><tr><td>DIMENSIONS</td><td>APPROX. 440 × 137 × 31 MM</td></tr><tr><td>ACCESSORIES</td><td>USB-C CABLE, WIRELESS RECEIVER, KEYCAP PULLER, SWITCH PULLER, SPARE KEYCAPS</td></tr></table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>G.9</td><td>APPLE MAGIC MOUSE (USB C) DAN YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>PRODUCT TYPE</td><td>WIRELESS MULTI-TOUCH OPTICAL MOUSE</td></tr>
<tr><td>CONNECTIVITY</td><td>BLUETOOTH WIRELESS</td></tr>
<tr><td>SENSOR TYPE</td><td>OPTICAL TRACKING SENSOR</td></tr>
<tr><td>MULTI-TOUCH FEATURE</td><td>FULL MULTI-TOUCH GESTURE SURFACE (SCROLL, SWIPE, NAVIGATION)</td></tr>
<tr><td>COMPATIBILITY</td><td>MACOS COMPATIBLE (NATIVE), WINDOWS BASIC FUNCTION SUPPORTED</td></tr>
<tr><td>BUTTON CONFIGURATION</td><td>TOUCH SURFACE INTEGRATED LEFT & RIGHT CLICK</td></tr>
<tr><td>SCROLLING</td><td>TOUCH-SENSITIVE 360° SMOOTH SCROLLING</td></tr>
<tr><td>BATTERY TYPE</td><td>BUILT-IN RECHARGEABLE LITHIUM-ION BATTERY</td></tr>
<tr><td>CHARGING INTERFACE</td><td>USB-C CHARGING PORT</td></tr>
<tr><td>BATTERY LIFE</td><td>UP TO ±1 MONTH PER CHARGE (TYPICAL USAGE)</td></tr>
<tr><td>CHARGING CABLE</td><td>USB-C CHARGING CABLE INCLUDED</td></tr>
<tr><td>TRACKING TECHNOLOGY</td><td>LASER/OPTICAL PRECISION TRACKING</td></tr>
<tr><td>SURFACE REQUIREMENT</td><td>COMPATIBLE WITH MOST DESK SURFACES (RECOMMENDED MOUSEPAD)</td></tr>
<tr><td>OPERATING SYSTEM SUPPORT</td><td>MACOS (FULL FEATURE), WINDOWS / LINUX (BASIC CURSOR OPERATION)</td></tr>
<tr><td>GESTURE SUPPORT</td><td>SWIPE BETWEEN PAGES, SMART ZOOM, MOMENTUM SCROLLING</td></tr>
<tr><td>POWER MANAGEMENT</td><td>AUTOMATIC SLEEP & WAKE FUNCTION</td></tr>
<tr><td>INSTALLATION</td><td>PLUG & PLAY PAIRING VIA BLUETOOTH</td></tr>
<tr><td>COLOUR</td><td>WHITE / BLACK (SUBJECT TO AVAILABILITY)</td></tr>
<tr><td>APPLICATION</td><td>OFFICE PRODUCTIVITY, DOCUMENT EDITING, GENERAL COMPUTING</td></tr>
<tr><td>WARRANTY</td><td>MINIMUM 12 MONTHS</td></tr>
</table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
<tr><td colspan="5">JUMLAH KESELURUHAN (BIL G)</td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>H</td><td>PERALATAN RANGKAIAN</td><td></td><td></td><td></td><td></td></tr>
<tr><td>H.1</td><td>RJ45 CAT6A TOOL-FREE CONNECTOR ATAU YANG SETARA
<table><tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr><tr><td>1. COMPONENT TYPE</td><td>RJ45 TOOL-FREE MODULAR CONNECTOR (8P8C)</td></tr><tr><td>2. STANDARD</td><td>CATEGORY 6A (10GBASE-T) COMPLIANT</td></tr><tr><td>3. TOOL-FREE INSTALLATION</td><td>CRIMP TOOL FREE</td></tr><tr><td>4. SUPPORTED CABLE</td><td>CAT6A UTP/STP TWISTED PAIR CABLE</td></tr><tr><td>5. DATA RATE & BANDWIDTH</td><td>10 GBPS, BANDWIDTH 500 MHZ</td></tr><tr><td>6. WIRING SCHEME</td><td>T568A & T568B</td></tr><tr><td>7. CONDUCTOR / WIRE SIZE</td><td>SOLID/STRANDED CABLES 23–26 AWG</td></tr><tr><td>8. CONTACT MATERIAL</td><td>GOLD-PLATED PHOSPHOR BRONZE CONTACTS</td></tr><tr><td>9. CONTACT & IDC LIFE</td><td>750 MATING CYCLES</td></tr><tr><td>10. OPERATING TEMP</td><td>-10 °C TO 60 °C</td></tr><tr><td>11. PHYSICAL / HOUSING</td><td>DURABLE HOUSING</td></tr><tr><td>12. COMPLIANCE & CERTIFICATIONS</td><td>ISO/IEC 11801 / ANSI/TIA-568 STANDARDS (CAT6A)</td></tr></table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>H.2</td><td>NOYAFA NF8508 MULTIFUNCTION NETWORK CABLE TESTER ATAU YANG SETARA
<table><tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr><tr><td>1. JENIS PERANTI</td><td>MULTIFUNCTION NETWORK CABLE TESTER</td></tr><tr><td>2. SUPPORTED CABLE TYPES</td><td>RJ45 ETHERNET (CAT5/CAT6), RJ11 TELEPHONE, BNC COAX</td></tr><tr><td>3. MAIN FUNCTIONS</td><td>• WIRE MAPPING & CONTINUITY TEST• CABLE TRACING/SCAN• PORT FLASH (PORT IDENTIFICATION)• CABLE LENGTH MEASUREMENT• POE CHECK (AF/AT & NON-STANDARD DETECTION)• CRYSTAL HEAD QC TEST</td></tr><tr><td>4. OPTICAL FUNCTIONS</td><td>• OPTICAL POWER METER (OPM) SUPPORT MULTIPLE WAVELENGTHS• VISUAL FAULT LOCATOR (VFL) 10 MW LASER</td></tr><tr><td>5. NCV & SAFETY</td><td>NON-CONTACT VOLTAGE (NCV) DETECTION</td></tr><tr><td>6. DISPLAY</td><td>LCD DISPLAY WITH BACKLIGHT</td></tr><tr><td>7. POWER & BATTERY</td><td>RECHARGEABLE LITHIUM BATTERY (~3.7 V / ~1500 MAH) WITH USB-C CHARGING</td></tr><tr><td>8. MEASUREMENT RANGES</td><td>CABLE LENGTH MEASUREMENT UP TO ~200 M</td></tr><tr><td>9. OPERATING ENVIRONMENT</td><td>OPERATING TEMPERATURE ~0 °C TO ~40 °C</td></tr><tr><td>10. CONNECTIVITY / INTERFACES</td><td>RJ45, RJ11, OPTICAL PORTS (WITH ADAPTERS)</td></tr><tr><td>11. PHYSICAL</td><td>PORTABLE HANDHELD DESIGN</td></tr><tr><td>12. COMPLIANCE / CERTIFICATION</td><td>CE / FCC / OTHER SAFETY & EMC STANDARDS (AS APPLICABLE)</td></tr></table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
<tr><td colspan="5">JUMLAH KESELURUHAN (BIL H)</td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>I</td><td>BEKALAN KUASA</td><td></td><td></td><td></td><td></td></tr>
<tr><td>I.1</td><td>UGREEN 45W GAN CHARGER WITH RETRACTABLE USB-C CABLE ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>1. DEVICE TYPE</td><td>WALL CHARGER GAN FAST CHARGER DENGAN KABEL USB-C BUILT-IN RETRACTABLE</td></tr>
<tr><td>2. CHARGER TECHNOLOGY</td><td>GAN (GALLIUM NITRIDE) HIGH-EFFICIENCY FAST CHARGING</td></tr>
<tr><td>3. MAX OUTPUT POWER</td><td>45 W TOTAL</td></tr>
<tr><td>4. OUTPUT PORTS</td><td>• KABEL USB-C BUILT-IN (RETRACTABLE, ±0.7 M)• USB-C TAMBAHAN 1 PORT</td></tr>
<tr><td>5. SUPPORTED CHARGING PROTOCOLS</td><td>USB POWER DELIVERY (PD 3.0/2.0), PPS, QC 3.0, QC2.0, SCP, AFC, APPLE/SAMSUNG SAFE PROFILES</td></tr>
<tr><td>6. CABLE DESIGN</td><td>RETRACTABLE TPE CABLE (±69 CM EXTENDED) WITH AUTO RETRACT MECHANISM</td></tr>
<tr><td>7. SAFETY PROTECTIONS</td><td>PROTECTIONS: OVER-VOLTAGE, OVER-CURRENT, OVER-TEMPERATURE, SHORT-CIRCUIT, ETC.</td></tr>
<tr><td>8. INPUT VOLTAGE</td><td>100–240 VAC, 50/60 HZ</td></tr>
<tr><td>9. COMPATIBILITY DEVICES</td><td>SMARTPHONES, TABLETS, LAPTOPS WITH USB-C CHARGING</td></tr>
<tr><td>10. FORM FACTOR</td><td>COMPACT WALL-PLUG DESIGN, PORTABLE FOR TRAVEL</td></tr>
</table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>I.2</td><td>HEAVY DUTY IP66 WEATHERPROFF EXTENSION TRAILING SOCKET 15M ATAU YANG SETARA
<table><tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr><tr><td>DEVICE TYPE</td><td>HEAVY DUTY WEATHERPROOF EXTENSION TRAILING SOCKET</td></tr><tr><td>SOCKET OUTLETS</td><td>2-WAY OUTLET</td></tr><tr><td>INGRESS PROTECTION</td><td>IP66 WATERPROOF & DUSTPROOF</td></tr><tr><td>RATED POWER</td><td>UP TO 3000 W</td></tr><tr><td>RATED VOLTAGE</td><td>240 V AC (50 HZ)</td></tr><tr><td>RATED CURRENT</td><td>13 A</td></tr><tr><td>CABLE LENGTH</td><td>15 METER</td></tr><tr><td>CABLE TYPE</td><td>INDUSTRIAL RUBBER INSULATED CABLE</td></tr><tr><td>PLUG TYPE</td><td>UK / TYPE-G 3-PIN FUSED PLUG</td></tr><tr><td>SAFETY PROTECTION</td><td>SPLASH-PROOF COVER WITH SEALING GASKET</td></tr><tr><td>OVERLOAD PROTECTION</td><td>BUILT-IN FUSE PROTECTION</td></tr><tr><td>OPERATING ENVIRONMENT</td><td>INDOOR & OUTDOOR USE</td></tr><tr><td>CABLE JACKET</td><td>HEAVY DUTY WEATHER-RESISTANT INSULATION</td></tr><tr><td>MOUNTING</td><td>PORTABLE TRAILING CABLE / HANGABLE USE</td></tr></table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>I.3</td><td>MASTERPLUG SURGE PROTECTOR 4 GANG 2 USB (3.1A) 2 METER ATAU YANG SETARA
<table><tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr><tr><td>PRODUCT NAME / MODEL</td><td>MASTERPLUG SURGE PROTECTOR 4 GANG + 2 USB (3.1A) 2 M CABLE</td></tr><tr><td>MAINS SOCKETS</td><td>4 × UK TYPE G 13 A OUTLETS</td></tr><tr><td>USB PORTS</td><td>2 × USB-A CHARGING PORTS (SHARED 3.1 A TOTAL)</td></tr><tr><td>SURGE PROTECTION</td><td>YES - PROTECTS AGAINST SURGES & SPIKES</td></tr><tr><td>PEAK SURGE CURRENT / ENERGY</td><td>~13,000 A / ~370–375 J (MOV + GAS TUBE PROTECTION)</td></tr><tr><td>RESPONSE TIME</td><td>25 NS</td></tr><tr><td>INDICATORS</td><td>LED POWER INDICATOR & LED SURGE STATUS INDICATOR</td></tr><tr><td>POWER SWITCH</td><td>YES (MAINS POWER ON/OFF SWITCH)</td></tr><tr><td>SAFETY SHUTTERS</td><td>YES (SOCKET CHILD-SAFETY SHUTTERS)</td></tr><tr><td>CABLE LENGTH</td><td>2 METERS</td></tr><tr><td>INPUT RATING</td><td>13 A, 220–240 V AC (STANDARD MAINS)</td></tr><tr><td>WALL MOUNTING</td><td>YES (WALL FIXING HOLES)</td></tr><tr><td>PLUG TYPE</td><td>UK TYPE G PLUG</td></tr><tr><td>COLOUR / FINISH</td><td>POLISHED BLACK (OR VARIANTS)</td></tr><tr><td>WARRANTY</td><td>~3 YEARS CONNECTED EQUIPMENT WARRANTY</td></tr></table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
<tr><td>I.4</td><td>CITYORK 11800MAH NP-F9900 BATTERY ATAU YANG SETARA
<table><tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr><tr><td>BATTERY TYPE</td><td>RECHARGEABLE LITHIUM-ION (SONY NP-F SERIES COMPATIBLE)</td></tr><tr><td>MODEL CLASS</td><td>NP-F990 EQUIVALENT HIGH-CAPACITY</td></tr><tr><td>CAPACITY</td><td>11800 MAH</td></tr><tr><td>NOMINAL VOLTAGE</td><td>7.4 V</td></tr><tr><td>ENERGY</td><td>~87 WH</td></tr><tr><td>CHARGING METHOD</td><td>EXTERNAL NP-F CHARGER / DUAL CHARGER DOCK</td></tr><tr><td>OUTPUT INTERFACE</td><td>STANDARD SONY NP-F PLATE CONTACT</td></tr><tr><td>PROTECTION CIRCUIT</td><td>OVER-CHARGE, OVER-DISCHARGE, SHORT-CIRCUIT PROTECTION</td></tr><tr><td>BATTERY INDICATOR</td><td>LED LEVEL INDICATOR BUTTON</td></tr><tr><td>COMPATIBILITY</td><td>FIELD MONITOR, WIRELESS VIDEO TX/RX, LED LIGHT, DSLR RIG</td></tr><tr><td>SIZE CLASS</td><td>LARGE CAPACITY NP-F BATTERY (LONG RUNTIME)</td></tr></table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>I.5</td><td>MAXELL CR2032 BATTERY ATAU YANG SETARA
<table>
<tr><td>ITEM</td><td>SPESIFIKASI MINIMUM</td></tr>
<tr><td>BATTERY TYPE</td><td>LITHIUM COIN CELL (PRIMARY / NON-RECHARGEABLE)</td></tr>
<tr><td>MODEL</td><td>CR2032</td></tr>
<tr><td>NOMINAL VOLTAGE</td><td>3 V DC</td></tr>
<tr><td>CAPACITY</td><td>±220–240 MAH</td></tr>
<tr><td>CHEMISTRY</td><td>LITHIUM MANGANESE DIOXIDE (LI-MNO2)</td></tr>
<tr><td>DIAMETER</td><td>20 MM</td></tr>
<tr><td>THICKNESS</td><td>3.2 MM</td></tr>
<tr><td>OPERATING TEMPERATURE</td><td>~20 °C TO +60 °C</td></tr>
<tr><td>SHELF LIFE</td><td>UP TO ±5–10 YEARS (SEALED STORAGE)</td></tr>
<tr><td>RECHARGEABLE</td><td>NO (SINGLE-USE BATTERY)</td></tr>
<tr><td>LEAK RESISTANCE</td><td>HIGH LEAK-RESISTANT SEALING DESIGN</td></tr>
</table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>I.6</td><td>LED DIGITAL TYPE POWER SUPPLY TESTER
<table>
<tr><td>ITEM</td><td>SPESIFIKASI MINIMUM</td></tr>
<tr><td>PRODUCT TYPE</td><td>COMPUTER ATX POWER SUPPLY DIAGNOSTIC TESTER</td></tr>
<tr><td>COMPATIBILITY</td><td>SUPPORT ATX, ITX, BTX STANDARD POWER SUPPLY</td></tr>
<tr><td>MAIN CONNECTOR SUPPORT</td><td>20-PIN & 24-PIN ATX CONNECTOR</td></tr>
<tr><td>ADDITIONAL CONNECTOR SUPPORT</td><td>4-PIN / 8-PIN CPU, PCIE 6-PIN, PCIE 8-PIN, SATA & MOLEX CONNECTOR</td></tr>
<tr><td>DISPLAY TYPE</td><td>INTEGRATED LCD DISPLAY SCREEN</td></tr>
<tr><td>VOLTAGE DETECTION</td><td>AUTOMATIC VOLTAGE DETECTION AND DISPLAY</td></tr>
<tr><td>DETECTED VOLTAGE RAILS</td><td>+12V, +5V, +3.3V, -12V, +5VSB</td></tr>
<tr><td>POWER-GOOD (PG) DETECTION</td><td>DISPLAY PG SIGNAL TIMING (MS)</td></tr>
<tr><td>ALARM INDICATOR</td><td>AUDIBLE BUZZER ALARM FOR ABNORMAL VOLTAGE</td></tr>
<tr><td>ACCURACY</td><td>VOLTAGE TOLERANCE DETECTION WITHIN ±0.1V</td></tr>
<tr><td>TEST METHOD</td><td>PLUG-AND-PLAY AUTOMATIC PSU STARTUP</td></tr>
<tr><td>POWER SOURCE</td><td>POWERED DIRECTLY FROM TESTED PSU (NO EXTERNAL ADAPTER REQUIRED)</td></tr>
<tr><td>SAFETY FEATURE</td><td>REVERSE CONNECTION PROTECTION & OVER-VOLTAGE ALERT</td></tr>
<tr><td>INDICATOR</td><td>VISUAL LCD READING AND AUDIBLE WARNING</td></tr>
<tr><td>MATERIAL</td><td>ABS INSULATED CASING</td></tr>
</table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
<tr><td colspan="5">JUMLAH KESELURUHAN (BIL I)</td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>J</td><td>PERALATAN KESELAMATAN</td><td></td><td></td><td></td><td></td></tr>
<tr><td>J.1</td><td>ZKTECO MULTIBIO 600/ID MULTI-BIOMETRIC ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>DEVICE TYPE</td><td>MULTI-BIOMETRIC ACCESS CONTROL & TIME ATTENDANCE TERMINAL</td></tr>
<tr><td>AUTHENTICATION METHOD</td><td>FINGERPRINT + RFID CARD + PASSWORD (PIN)</td></tr>
<tr><td>FINGERPRINT CAPACITY</td><td>UP TO ±3,000 FINGERPRINTS</td></tr>
<tr><td>CARD CAPACITY</td><td>UP TO ±10,000 RFID USERS</td></tr>
<tr><td>TRANSACTION LOG</td><td>UP TO ±100,000 RECORDS</td></tr>
<tr><td>FINGERPRINT SENSOR</td><td>OPTICAL FINGERPRINT SENSOR</td></tr>
<tr><td>CARD TYPE</td><td>125 KHZ RFID (EM CARD)</td></tr>
<tr><td>DISPLAY</td><td>2.8" TFT COLOR SCREEN</td></tr>
<tr><td>VERIFICATION TIME</td><td>< 1 SECOND</td></tr>
<tr><td>COMMUNICATION</td><td>TCP/IP LAN, USB HOST</td></tr>
<tr><td>ACCESS CONTROL OUTPUT</td><td>RELAY OUTPUT (NO/NC)</td></tr>
<tr><td>WIEGAND INTERFACE</td><td>WIEGAND INPUT & OUTPUT SUPPORTED</td></tr>
<tr><td>DOOR CONTROL</td><td>MAGLOCK / ELECTRIC STRIKE / DOOR RELEASE BUTTON</td></tr>
<tr><td>ALARM FUNCTION</td><td>DOOR OPEN TIMEOUT, TAMPER ALARM</td></tr>
</table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>J.2</td><td>TUYA WIFI RF433 DOOR EXIT BUTTON ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>PERANTI</td><td>SMART ACCESS CONTROL EXIT BUTTON</td></tr>
<tr><td>PLATFORM</td><td>TUYA SMART / SMART LIFE APP</td></tr>
<tr><td>WIRELESS</td><td>WIFI 2.4 GHZ + RF433 MHZ</td></tr>
<tr><td>RF FREQUENCY</td><td>433.92 MHZ</td></tr>
<tr><td>REMOTE DISTANCE</td><td>±30 M INDOOR / ±100 M OUTDOOR</td></tr>
<tr><td>WORKING VOLTAGE</td><td>DC 12V</td></tr>
<tr><td>CONTROL METHOD</td><td>PUSH BUTTON / MOBILE APP / RF REMOTE / VOICE CONTROL</td></tr>
<tr><td>APP SUPPORT</td><td>TUYA SMART / SMART LIFE</td></tr>
<tr><td>VOICE ASSISTANT</td><td>ALEXA & GOOGLE HOME</td></tr>
<tr><td>RELAY TYPE</td><td>DRY CONTACT (NO/NC OUTPUT)</td></tr>
<tr><td>OPERATING MODE</td><td>INCHING (MOMENTARY) & SELF-LOCKING (MANUALS+)</td></tr>
<tr><td>MATERIAL</td><td>FLAME-RETARDANT PLASTIC RESIN</td></tr>
<tr><td>LIFE CYCLE</td><td>±100,000 PRESSES</td></tr>
</table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>J.3</td><td>TP-LINK TAPO D235 SMART VIDEO DOORBELL ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>DEVICE TYPE</td><td>SMART WI-FI VIDEO DOORBELL (BATTERY POWERED)</td></tr>
<tr><td>CAMERA RESOLUTION</td><td>5MP (2K) HIGH-DEFINITION VIDEO</td></tr>
<tr><td>VIEWING ANGLE</td><td>180° ULTRA-WIDE HEAD-TO-TOE FIELD OF VIEW</td></tr>
<tr><td>NIGHT VISION</td><td>FULL-COLOR NIGHT VISION WITH SPOTLIGHT AND IR MODE</td></tr>
<tr><td>AUDIO</td><td>TWO-WAY AUDIO (BUILT-IN MICROPHONE & SPEAKER)</td></tr>
<tr><td>MOTION DETECTION</td><td>AI DETECTION: HUMAN, VEHICLE, PET & PACKAGE</td></tr>
<tr><td>NOTIFICATION</td><td>REAL-TIME PUSH NOTIFICATION VIA MOBILE APPLICATION</td></tr>
<tr><td>INDOOR ALERT</td><td>WIRELESS INDOOR CHIME UNIT INCLUDED</td></tr>
<tr><td>ALARM</td><td>BUILT-IN SIREN & CUSTOMIZABLE RINGTONE</td></tr>
<tr><td>WIRELESS STANDARD</td><td>IEEE 802.11 B/G/N</td></tr>
<tr><td>WI-FI FREQUENCY</td><td>2.4 GHZ WI-FI</td></tr>
<tr><td>MOBILE APPLICATION</td><td>TAPO APP (ANDROID & IOS)</td></tr>
<tr><td>SMART ASSISTANT</td><td>GOOGLE ASSISTANT & AMAZON ALEXA COMPATIBLE</td></tr>
<tr><td>LOCAL STORAGE</td><td>MICROSD CARD SUPPORT (UP TO 512GB)</td></tr>
<tr><td>CLOUD STORAGE</td><td>TAPO CARE CLOUD RECORDING</td></tr>
<tr><td>RECORDING TYPE</td><td>MOTION-TRIGGERED & MANUAL LIVE RECORDING</td></tr>
<tr><td>POWER SOURCE</td><td>RECHARGEABLE BATTERY OR WIRED DOORBELL SUPPLY</td></tr>
<tr><td>BATTERY TYPE</td><td>BUILT-IN LITHIUM RECHARGEABLE BATTERY</td></tr>
<tr><td>BATTERY LIFE</td><td>UP TO APPROXIMATELY 5–6 MONTHS (TYPICAL USAGE)</td></tr>
<tr><td>CHARGING METHOD</td><td>USB CHARGING</td></tr>
<tr><td>INSTALLATION</td><td>WALL MOUNTING BRACKET</td></tr>
<tr><td>WEATHER RESISTANCE</td><td>OUTDOOR WEATHER-RESISTANT HOUSING</td></tr>
<tr><td>COLOR</td><td>MATTE BLACK FINISH</td></tr>
</table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>J.4</td><td>5MP SRIHOME NVR WIFI TOUCH SCREEN MONITOR + 4PC 2K PTZ CAMERA NIGHT VISION 2-WAY AUDIO NVS010-IPC047 ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>PRODUCT TYPE</td><td>WIRELESS CCTV SURVEILLANCE KIT (NVR MONITOR + 4 WIFI PTZ IP CAMERA)</td></tr>
<tr><td>NVR TYPE</td><td>BUILT-IN WIFI NETWORK VIDEO RECORDER WITH TOUCH SCREEN MONITOR</td></tr>
<tr><td>MONITOR DISPLAY</td><td>MINIMUM 10.1 INCH IPS TOUCH SCREEN</td></tr>
<tr><td>VIDEO COMPRESSION</td><td>H.265 / H.265+</td></tr>
<tr><td>RECORDING RESOLUTION</td><td>UP TO 5MP (2592 × 1944)</td></tr>
<tr><td>CHANNEL SUPPORT</td><td>MINIMUM 4 CHANNEL WIRELESS IP CAMERA</td></tr>
<tr><td>STORAGE SUPPORT</td><td>1 × SATA HDD SLOT (SUPPORT UP TO 6TB)</td></tr>
<tr><td>NETWORK CONNECTIVITY</td><td>BUILT-IN 2.4GHZ WIFI HOTSPOT + LAN PORT</td></tr>
<tr><td>MOBILE MONITORING</td><td>ANDROID & IOS REMOTE VIEWING VIA MOBILE APPLICATION</td></tr>
<tr><td>RECORDING MODE</td><td>CONTINUOUS RECORDING & MOTION DETECTION RECORDING</td></tr>
<tr><td>CAMERA RESOLUTION</td><td>MINIMUM 2K / 3MP (2304 × 1296) PER CAMERA</td></tr>
<tr><td>CAMERA TYPE</td><td>OUTDOOR WIFI PTZ CAMERA</td></tr>
<tr><td>PTZ MOVEMENT</td><td>PAN 355° , TILT 90°</td></tr>
<tr><td>NIGHT VISION</td><td>INFRARED & FULL COLOR NIGHT VISION (MINIMUM 20M DISTANCE)</td></tr>
<tr><td>AUDIO</td><td>BUILT-IN MICROPHONE & SPEAKER (2-WAY AUDIO COMMUNICATION)</td></tr>
<tr><td>SMART DETECTION</td><td>HUMAN MOTION DETECTION WITH PUSH NOTIFICATION</td></tr>
<tr><td>WEATHER PROTECTION</td><td>MINIMUM IP66 WEATHERPROOF</td></tr>
<tr><td>VIDEO PLAYBACK</td><td>REMOTE PLAYBACK & VIDEO BACKUP VIA USB</td></tr>
<tr><td>POWER INPUT</td><td>DC ADAPTER POWERED (NVR & CAMERAS)</td></tr>
<tr><td>OPERATING FREQUENCY</td><td>2.4GHZ WIRELESS TRANSMISSION</td></tr>
<tr><td>ACCESSORIES</td><td>COMPLETE WITH 4 CAMERAS, POWER ADAPTER, MOUNTING KIT & ACCESSORIES</td></tr>
</table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
<tr><td colspan="5">JUMLAH KESELURUHAN (BIL J)</td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>K</td><td>AKSESORI PINTAR</td><td></td><td></td><td></td><td></td></tr>
<tr><td>K.1</td><td>PLAUD NOTE NB-100 AI VOICE RECORDER ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>DEVICE TYPE</td><td>AI-POWERED PORTABLE VOICE RECORDER</td></tr>
<tr><td>RECORDING METHOD</td><td>AIR CONDUCTION MICROPHONE + VIBRATION (PHONE CALL PICKUP)</td></tr>
<tr><td>STORAGE</td><td>64 GB INTERNAL MEMORY</td></tr>
<tr><td>RECORDING FORMAT</td><td>WAV / AI PROCESSED TRANSCRIPT</td></tr>
<tr><td>MICROPHONE</td><td>DUAL MEMS MICROPHONE ARRAY</td></tr>
<tr><td>NOISE REDUCTION</td><td>AI NOISE FILTERING & VOICE ENHANCEMENT</td></tr>
<tr><td>CONNECTIVITY</td><td>BLUETOOTH + MOBILE APP (IOS / ANDROID)</td></tr>
<tr><td>TRANSCRIPTION</td><td>AI SPEECH-TO-TEXT (MULTI-LANGUAGE SUPPORTED)</td></tr>
<tr><td>AI FEATURES</td><td>AUTO SUMMARY, MEETING NOTES, SPEAKER SEPARATION</td></tr>
<tr><td>BATTERY LIFE</td><td>UP TO ~30 HOURS RECORDING</td></tr>
<tr><td>CHARGING PORT</td><td>USB-C</td></tr>
<tr><td>MOUNTING</td><td>MAGNETIC ATTACH (BELAKANG PHONE / TABLE)</td></tr>
<tr><td>THICKNESS</td><td>~3 MM ULTRA-THIN DESIGN</td></tr>
</table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>K.2</td><td>PLAUD NOTEPIN AI VOICE RECORDER ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>DEVICE TYPE</td><td>WEARABLE AI VOICE RECORDER & TRANSCRIPTION ASSISTANT</td></tr>
<tr><td>RECORDING METHOD</td><td>DUAL MEMS MICROPHONE ARRAY (360° VOICE CAPTURE)</td></tr>
<tr><td>NOISE REDUCTION</td><td>AI NOISE FILTERING & VOICE ENHANCEMENT</td></tr>
<tr><td>STORAGE</td><td>BUILT-IN INTERNAL STORAGE (CLOUD SYNC VIA APP)</td></tr>
<tr><td>RECORDING FORMAT</td><td>HIGH-QUALITY DIGITAL AUDIO + AI TRANSCRIPT</td></tr>
<tr><td>CONNECTIVITY</td><td>BLUETOOTH LOW ENERGY (BLE) + MOBILE APP</td></tr>
<tr><td>MOBILE SUPPORT</td><td>ANDROID & IOS</td></tr>
<tr><td>AI FUNCTIONS</td><td>SPEECH-TO-TEXT TRANSCRIPTION, AUTO SUMMARY, ACTION ITEMS, SPEAKER SEPARATION</td></tr>
<tr><td>LANGUAGES</td><td>MULTI-LANGUAGE (SUPPORTS BAHASA MELAYU MIXED SPEECH)</td></tr>
<tr><td>BATTERY LIFE</td><td>±20–30 HOURS RECORDING (TYPICAL USAGE)</td></tr>
<tr><td>CHARGING METHOD</td><td>MAGNETIC CHARGING DOCK / CASE</td></tr>
<tr><td>CHARGING TIME</td><td>~2 HOURS</td></tr>
<tr><td>CONTROLS</td><td>ONE-BUTTON RECORD / STOP</td></tr>
<tr><td>INDICATOR</td><td>LED STATUS INDICATOR</td></tr>
<tr><td>MOUNTING</td><td>MAGNETIC CLIP / LANYARD WEARABLE</td></tr>
<tr><td>DESIGN</td><td>ULTRA-COMPACT WEARABLE SQUARE FORM FACTOR</td></tr>
</table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
<tr><td colspan="5">JUMLAH KESELURUHAN (BIL K)</td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>L</td><td>ERGONOMIK & AKSESORI MEJA</td><td></td><td></td><td></td><td></td></tr>
<tr><td>L.1</td><td>FLEXISPOT ALCOVERISE STANDING DESK CONVERTERS M7MB - 35INCH ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>PRODUCT TYPE</td><td>STANDING DESK CONVERTER (TABLETOP WORKSTATION RISER)</td></tr>
<tr><td>MODEL</td><td>FLEXISPOT ALCOVERISE M7MB</td></tr>
<tr><td>DESKTOP WIDTH</td><td>MINIMUM 35 INCH (±89 CM)</td></tr>
<tr><td>LOAD CAPACITY</td><td>MINIMUM 15 KG</td></tr>
<tr><td>HEIGHT ADJUSTMENT</td><td>GAS SPRING ASSISTED LIFT MECHANISM</td></tr>
<tr><td>HEIGHT RANGE</td><td>APPROXIMATELY 12 CM – 50 CM ADJUSTABLE</td></tr>
<tr><td>ADJUSTMENT METHOD</td><td>MANUAL LIFT WITH PNEUMATIC SPRING (SINGLE HANDLE)</td></tr>
<tr><td>KEYBOARD TRAY</td><td>INTEGRATED RETRACTABLE KEYBOARD & MOUSE TRAY</td></tr>
<tr><td>DESKTOP MATERIAL</td><td>HIGH-DENSITY PARTICLE BOARD / LAMINATED FINISH</td></tr>
<tr><td>FRAME MATERIAL</td><td>POWDER-COATED STEEL FRAME</td></tr>
<tr><td>ERGONOMIC FEATURE</td><td>SIT-STAND ERGONOMIC WORKING POSITION SUPPORT</td></tr>
<tr><td>MONITOR SUPPORT</td><td>SUPPORT SINGLE OR DUAL MONITOR SETUP</td></tr>
<tr><td>STABILITY</td><td>ANTI-WOBBLE STRUCTURE WITH X-FRAME SUPPORT</td></tr>
<tr><td>INSTALLATION</td><td>PRE-ASSEMBLED / MINIMAL INSTALLATION REQUIRED</td></tr>
<tr><td>SAFETY FEATURE</td><td>SMOOTH LIFT WITH LOCKING HEIGHT POSITIONS</td></tr>
<tr><td>COLOUR</td><td>BLACK (OR EQUIVALENT)</td></tr>
</table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>L.2</td><td>COOLER MASTER NOTEPAL ERGOSTAND IV LAPTOP COOLING PAD ATAU YANG SETARA
<table><tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr><tr><td>DESIGN</td><td>ERGONOMIC ADJUSTABLE STAND</td></tr><tr><td>COOLING SYSTEM</td><td>LARGE 200 MM COOLING FAN</td></tr><tr><td>SURFACE MATERIAL</td><td>MESH METAL SURFACE WITH ANTI-SLIP RUBBER PADS</td></tr><tr><td>POWER SOURCE</td><td>USB-POWERED (NO EXTERNAL ADAPTER REQUIRED)</td></tr><tr><td>CABLE MANAGEMENT</td><td>BUILT-IN CABLE ROUTING MANAGEMENT</td></tr><tr><td>AIRFLOW DIRECTION</td><td>UPWARD AIRFLOW FOR LAPTOP HEAT DISSIPATION</td></tr><tr><td>NOISE LEVEL</td><td>LOW-NOISE OPERATION</td></tr><tr><td>FAN CONTROL</td><td>ADJUSTABLE FAN SPEED CONTROLLER</td></tr><tr><td>COMPATIBILITY</td><td>SUITABLE FOR LAPTOPS UP TO 17-INCH DISPLAY</td></tr></table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>L.3</td><td>SPIRAL CABLE MANAGEMENT ORGANIZER (10MM) 9M ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>PRODUCT TYPE</td><td>SPIRAL CABLE WRAP / SPIRAL CABLE MANAGEMENT ORGANIZER</td></tr>
<tr><td>MATERIAL</td><td>FLEXIBLE POLYETHYLENE (PE) / POLYPROPYLENE (PP) INSULATION GRADE</td></tr>
<tr><td>STRUCTURE</td><td>HELICAL SPIRAL OPEN-WRAP DESIGN</td></tr>
<tr><td>FUNCTION</td><td>CABLE BUNDLING, PROTECTION & ROUTING MANAGEMENT</td></tr>
<tr><td>DIAMETER OPTIONS</td><td>10 MM</td></tr>
<tr><td>BUNDLE CAPACITY</td><td>SUPPORTS MULTIPLE CABLE GROUPING</td></tr>
<tr><td>LENGTH (TYPICAL)</td><td>5 M PER ROLL (CUTTABLE & EXTENDABLE)</td></tr>
<tr><td>OPERATING TEMPERATURE</td><td>-20 °C TO +80 °C</td></tr>
<tr><td>FLAME RESISTANCE</td><td>BASIC INSULATION GRADE (NON-CONDUCTIVE PROTECTIVE COVERING)</td></tr>
<tr><td>FLEXIBILITY</td><td>BENDABLE & REUSABLE (NON-PERMANENT INSTALLATION)</td></tr>
<tr><td>INSTALLATION METHOD</td><td>TOOL-FREE MANUAL WRAP INSTALLATION</td></tr>
<tr><td>CABLE EXIT</td><td>CABLES BOLEH KELUAR DI MANA-MANA TITIK TANPA POTONG WRAP</td></tr>
<tr><td>PROTECTION FUNCTION</td><td>ANTI-ABRASION, ANTI-KINK, DUST PROTECTION, MINOR IMPACT PROTECTION</td></tr>
<tr><td>ELECTRICAL PROPERTY</td><td>NON-CONDUCTIVE INSULATING MATERIAL</td></tr>
<tr><td>COLOR</td><td>BLACK</td></tr>
<tr><td>APPLICATION</td><td>OFFICE WORKSTATION, SERVER RACK, AV SYSTEM, CCTV, NETWORK CABLING</td></tr>
</table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>L.4</td><td>GBC FUSION 3000L A3 LAMINATOR ATAU YANG SETARA
<table><tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr><tr><td>PRODUCT TYPE</td><td>OFFICE LAMINATING MACHINE</td></tr><tr><td>MODEL</td><td>GBC FUSION 3000L</td></tr><tr><td>LAMINATING SIZE</td><td>UP TO A3</td></tr><tr><td>WARM-UP TIME</td><td>1 MINUTE</td></tr><tr><td>LAMINATING SPEED</td><td>MINIMUM 500 MM/MIN</td></tr><tr><td>POUCH THICKNESS</td><td>SUPPORT 75 – 125 MICRON LAMINATING POUCH</td></tr><tr><td>HEATING TECHNOLOGY</td><td>DUAL ROLLER HEAT SYSTEM</td></tr><tr><td>CONTROL INDICATOR</td><td>LED READY INDICATOR & AUDIBLE ALERT</td></tr><tr><td>OPERATION MODE</td><td>AUTOMATIC TEMPERATURE CONTROL</td></tr><tr><td>ANTI-JAM FEATURE</td><td>JAM RELEASE LEVER MECHANISM</td></tr><tr><td>POWER SUPPLY</td><td>220 – 240V AC, 50/60HZ</td></tr><tr><td>SAFETY FEATURE</td><td>AUTO SHUT-OFF AFTER IDLE PERIOD</td></tr><tr><td>USAGE CATEGORY</td><td>MEDIUM DUTY OFFICE USE</td></tr><tr><td>APPLICATION</td><td>SUITABLE FOR CERTIFICATES, ID NOTICE, SIGNAGE, POSTERS & DOCUMENTS</td></tr><tr><td>BUILD</td><td>COMPACT DESKTOP DESIGN</td></tr></table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>L.5</td><td>GREENWIPES ELECTRONIC CLEANING WIPES
<table><tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr><tr><td>PRODUCT TYPE</td><td>ELECTRONIC EQUIPMENT CLEANING WIPES</td></tr><tr><td>CLEANING TYPE</td><td>PRE-MOISTENED ANTI-STATIC CLEANING WIPES</td></tr><tr><td>CHEMICAL CONTENT</td><td>ALCOHOL-FREE / AMMONIA-FREE SOLUTION</td></tr><tr><td>SURFACE COMPATIBILITY</td><td>LCD/LED MONITOR, LAPTOP, KEYBOARD, MOUSE, PRINTER & ELECTRONIC DEVICES</td></tr><tr><td>ANTI-STATIC FEATURE</td><td>YES (SAFE FOR ELECTRONIC COMPONENTS & PCB SURFACE)</td></tr><tr><td>RESIDUE</td><td>NON-STREAK & NON-RESIDUE CLEANING</td></tr><tr><td>MATERIAL</td><td>NON-ABRASIVE LINT-FREE MICROFIBER WIPES</td></tr><tr><td>PACKAGING</td><td>SEALED CANISTER / DISPENSER TYPE</td></tr><tr><td>QUANTITY</td><td>MINIMUM 80 WIPES PER CANISTER</td></tr><tr><td>SAFETY</td><td>SAFE FOR COATED SCREEN & TOUCH SCREEN DISPLAY</td></tr><tr><td>APPLICATION</td><td>REMOVAL OF DUST, FINGERPRINT, OIL & LIGHT DIRT ON ELECTRONIC EQUIPMENT</td></tr><tr><td>STORAGE</td><td>RESEALABLE COVER TO PREVENT DRYING</td></tr></table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
<tr><td colspan="5">JUMLAH KESELURUHAN (BIL L)</td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>M</td><td>PERALATAN KHAS</td><td></td><td></td><td></td><td></td></tr>
<tr><td>M.1</td><td>CREALITY CR-SCAN FERRET PRO 3D SCANNER ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>PRODUCT TYPE</td><td>HANDHELD PORTABLE 3D SCANNER</td></tr>
<tr><td>MODEL</td><td>CREALITY CR-SCAN FERRET PRO</td></tr>
<tr><td>SCANNING TECHNOLOGY</td><td>STRUCTURED LIGHT / NIR (NEAR-INFRARED) OPTICAL SCANNING</td></tr>
<tr><td>SCANNING ACCURACY</td><td>UP TO 0.1 MM</td></tr>
<tr><td>RESOLUTION</td><td>UP TO 0.16 MM 3D POINT DISTANCE</td></tr>
<tr><td>SCAN RANGE</td><td>APPROX. 150 MM – 2000 MM OBJECT SIZE</td></tr>
<tr><td>FRAME RATE</td><td>UP TO 30 FPS SCANNING</td></tr>
<tr><td>COLOUR CAPTURE</td><td>FULL COLOUR TEXTURE SCANNING (RGB CAMERA)</td></tr>
<tr><td>TRACKING METHOD</td><td>VISUAL TRACKING + ANTI-SHAKE ALGORITHM</td></tr>
<tr><td>CONNECTIVITY</td><td>USB TYPE-C & WIFI WIRELESS CONNECTION</td></tr>
<tr><td>SUPPORTED DEVICE</td><td>WINDOWS PC, ANDROID & IOS SMARTPHONE</td></tr>
<tr><td>SOFTWARE</td><td>CREALITY SCAN SOFTWARE (REAL-TIME PREVIEW & MESH GENERATION)</td></tr>
<tr><td>OUTPUT FORMAT</td><td>STL / OBJ / PLY</td></tr>
<tr><td>LIGHT REQUIREMENT</td><td>WORKS IN INDOOR & OUTDOOR ENVIRONMENT</td></tr>
<tr><td>POWER SUPPLY</td><td>POWERED VIA USB (NO EXTERNAL POWER ADAPTER REQUIRED)</td></tr>
<tr><td>APPLICATION</td><td>REVERSE ENGINEERING, ASSET DIGITIZING, MODELLING & 3D PRINTING</td></tr>
<tr><td>PORTABILITY</td><td>LIGHTWEIGHT HANDHELD PORTABLE DESIGN</td></tr>
</table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
<tr><td colspan="5">JUMLAH KESELURUHAN (BIL M)</td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>N</td><td>AKSESORI PERANTI</td><td></td><td></td><td></td><td></td></tr>
<tr><td>N.1</td><td>ALATGANTI LAPTOP ASUS TUF FX505
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>PRODUCT TYPE</td><td>LAPTOP EXTERNAL CHASSIS / OUTER BODY REPLACEMENT PARTS</td></tr>
<tr><td>COMPATIBILITY</td><td>ASUS TUF FX505 SERIES</td></tr>
<tr><td>COMPONENT INCLUDED</td><td>BOTTOM COVER, PALMREST UPPER CASE, LCD BACK COVER (TOP LID) & SCREEN BEZEL FRAME</td></tr>
<tr><td>MATERIAL</td><td>ABS + POLYCARBONATE COMPOSITE (HIGH-IMPACT PLASTIC)</td></tr>
<tr><td>FINISH</td><td>MATTE / TEXTURED ANTI-SCRATCH SURFACE</td></tr>
<tr><td>COLOUR</td><td>BLACK / GUNMETAL ATAU SETARA ASAL</td></tr>
<tr><td>VENTILATION</td><td>INTEGRATED COOLING VENTILATION GRILLS (FACTORY DESIGN)</td></tr>
<tr><td>MOUNTING</td><td>COMPLETE INTERNAL SCREW MOUNTING POINTS & BRACKET ALIGNMENT</td></tr>
<tr><td>HINGE SUPPORT</td><td>COMPATIBLE WITH ORIGINAL DISPLAY HINGE ASSEMBLY</td></tr>
<tr><td>PORT ALIGNMENT</td><td>EXACT CUT-OUT FOR USB, HDMI, LAN, AUDIO & POWER PORT</td></tr>
<tr><td>KEYBOARD SUPPORT</td><td>COMPATIBLE WITH ORIGINAL K</td></tr>
</table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>N.2</td><td>MAGEASY COVERBUDDY LITE MAGNETIC CASE FOR IPAD PRO 11" ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>TECHNICAL SPECIFICATION</th></tr>
<tr><td>PRODUCT TYPE</td><td>MAGNETIC PROTECTIVE BACK CASE FOR TABLET</td></tr>
<tr><td>COMPATIBILITY</td><td>IPAD PRO 11" (2025 M5 / 2024 M4)</td></tr>
<tr><td>KEYBOARD COMPATIBILITY</td><td>FULLY COMPATIBLE WITH APPLE MAGIC KEYBOARD WITHOUT REMOVING THE CASE</td></tr>
<tr><td>CONNECTION TECHNOLOGY</td><td>SMART CONNECTOR PASS-THROUGH SUPPORT FOR SEAMLESS MAGIC KEYBOARD CONNECTIVITY</td></tr>
<tr><td>MAGNETIC SYSTEM</td><td>BUILT-IN STRONG MAGNETIC ATTACHMENT FOR SECURE CONNECTION WITH MAGIC KEYBOARD</td></tr>
<tr><td>MATERIAL</td><td>POLYCARBONATE (PC) WITH PU COATING</td></tr>
<tr><td>PRODUCT DIMENSIONS</td><td>APPROXIMATELY 252 × 176 × 8 MM</td></tr>
<tr><td>PROTECTION</td><td>PROTECTS THE BACK AND SIDES OF THE IPAD FROM SCRATCHES AND MINOR IMPACTS</td></tr>
<tr><td>DESIGN</td><td>SLIM AND LIGHTWEIGHT DESIGN THAT DOES NOT ADD SIGNIFICANT BULK</td></tr>
<tr><td>APPLE PENCIL SUPPORT</td><td>SUPPORTS APPLE PENCIL MAGNETIC ATTACHMENT AND WIRELESS CHARGING</td></tr>
<tr><td>INNER LINING</td><td>SOFT MICROFIBER INNER LAYER TO PREVENT SCRATCHES ON DEVICE SURFACE</td></tr>
<tr><td>MAGNETIC DESIGN</td><td>PRECISION MAGNETIC ALIGNMENT FOR QUICK AND SECURE INSTALLATION</td></tr>
</table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
<tr><td colspan="5">JUMLAH KESELURUHAN (BIL N)</td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>O</td><td>AKSESORI KAMERA</td><td></td><td></td><td></td><td></td></tr>
<tr><td>O.1</td><td>DJI OSMO MOBILE 7P ATAU YANG SETARA
<table><tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr><tr><td>DEVICE TYPE</td><td>3-AXIS SMARTPHONE STABILIZER (GIMBAL)</td></tr><tr><td>STABILIZATION</td><td>MECHANICAL 3-AXIS STABILIZATION (PAN, TILT, ROLL)</td></tr><tr><td>COMPATIBLE PHONE WIDTH</td><td>~67 – 84 MM SMARTPHONES</td></tr><tr><td>MAX PAYLOAD</td><td>±300 G SMARTPHONE</td></tr><tr><td>CONTROL CONNECTION</td><td>BLUETOOTH 5.0</td></tr><tr><td>COMPANION APP</td><td>DJI MIMO APP</td></tr><tr><td>TRACKING TECHNOLOGY</td><td>ACTIVETRACK AI SUBJECT TRACKING</td></tr><tr><td>OPERATING MODES</td><td>FOLLOW, TILT LOCK, FPV, SPINSHOT</td></tr><tr><td>GESTURE CONTROL</td><td>SUPPORTED (START/STOP RECORDING VIA HAND GESTURE)</td></tr><tr><td>BUILT-IN EXTENSION ROD</td><td>YES (EXTENDABLE SELFIE ROD)</td></tr><tr><td>TRIPOD MOUNT</td><td>1/4” SCREW TRIPOD SUPPORT</td></tr></table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>O.2</td><td>ULANZI ZERO V CARBON FIBER CAMERA TRIPOD
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>PRODUCT TYPE</td><td>PROFESSIONAL PORTABLE CAMERA TRIPOD</td></tr>
<tr><td>MODEL</td><td>ULANZI ZERO V CARBON FIBER</td></tr>
<tr><td>MATERIAL</td><td>CARBON FIBER LEGS + ALUMINIUM ALLOY COMPONENTS</td></tr>
<tr><td>MAXIMUM HEIGHT</td><td>MINIMUM 155 CM</td></tr>
<tr><td>MINIMUM HEIGHT</td><td>APPROXIMATELY 15–20 CM (LOW ANGLE SHOOTING)</td></tr>
<tr><td>FOLDED LENGTH</td><td>45 CM (COMPACT TRAVEL SIZE)</td></tr>
<tr><td>MAXIMUM LOAD CAPACITY</td><td>MINIMUM 18 KG</td></tr>
<tr><td>LEG SECTIONS</td><td>5 SECTION FOLDABLE LEGS</td></tr>
<tr><td>LOCK MECHANISM</td><td>QUICK TWIST LOCK SYSTEM</td></tr>
<tr><td>TRIPOD HEAD</td><td>BALL HEAD WITH 360° PANORAMIC ROTATION</td></tr>
<tr><td>QUICK RELEASE</td><td>ARCA-SWISS COMPATIBLE QUICK RELEASE PLATE</td></tr>
<tr><td>LEVEL INDICATOR</td><td>BUILT-IN BUBBLE LEVEL</td></tr>
<tr><td>LEG ADJUSTMENT</td><td>MULTI-ANGLE LEG ADJUSTMENT (LOW ANGLE/MACRO MODE)</td></tr>
<tr><td>MOUNTING THREAD</td><td>STANDARD 1/4” CAMERA SCREW</td></tr>
<tr><td>FEET TYPE</td><td>ANTI-SLIP RUBBER FEET</td></tr>
<tr><td>WEIGHT</td><td>1.2 KG</td></tr>
<tr><td>APPLICATION</td><td>DSLR / MIRRORLESS CAMERA / VIDEO RECORDING / PHOTOGRAPHY</td></tr>
</table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
<tr><td colspan="5">JUMLAH KESELURUHAN (BIL O)</td><td></td></tr>
</table>

<table>
<tr><th>BIL.</th><th>KETERANGAN</th><th>UNIT</th><th>KUANTITI</th><th>KADAR (RM)</th><th>AMAUN (RM)</th></tr>
<tr><td>P</td><td>PERANTI MUDAH ALIH</td><td></td><td></td><td></td><td></td></tr>
<tr><td>P.1</td><td>SANDISK ULTRA DUAL DRIVE 256GB ATAU YANG SETARA
<table>
<tr><th>ITEM</th><th>SPESIFIKASI MINIMUM</th></tr>
<tr><td>JENIS PERANTI</td><td>DUAL INTERFACE USB FLASH DRIVE</td></tr>
<tr><td>CAPACITY</td><td>256 GB</td></tr>
<tr><td>CONNECTOR 1</td><td>USB TYPE-C</td></tr>
<tr><td>CONNECTOR 2</td><td>USB TYPE-A (STANDARD PC PORT)</td></tr>
<tr><td>USB STANDARD</td><td>USB 3.1 / USB 3.2 GEN 1</td></tr>
<tr><td>MAX READ SPEED</td><td>UP TO ±150 MB/S (READ)</td></tr>
<tr><td>WRITE SPEED</td><td>UP TO ±40 MB/S</td></tr>
<tr><td>COMPATIBILITY</td><td>WINDOWS, MACOS, LINUX, ANDROID OTG</td></tr>
<tr><td>MOBILE SUPPORT</td><td>ANDROID PHONE/TABLET (USB-C OTG)</td></tr>
<tr><td>APP SUPPORT</td><td>SANDISK MEMORY ZONE (AUTO BACKUP PHONE)</td></tr>
<tr><td>PLUG & PLAY</td><td>YES</td></tr>
<tr><td>POWER SOURCE</td><td>BUS POWERED</td></tr>
</table></td><td>UNIT</td><td>0</td><td></td><td>RATE ONLY</td></tr>
<tr><td colspan="5">JUMLAH KESELURUHAN (BIL P)</td><td></td></tr>
</table>