

MEMBEKAL, MEMASANG, MENGUJI DAN MENTAULIAH KELENGKAPAN ICT UNTUK KEGUNAAN BANGUNAN PEJABAT MAJLIS
BANDARAYA ISKANDAR PUTERI BAGI TAHUN 2026

RINGKASAN SENARAI KUANTITI

BIL.	BAHAGIAN	MUKA SURAT	JUMLAH (RM)
1	DISPLAY & MOUNTING	2/28	
2	PRINTING & SCANNING	6/28	
3	INPUT & CONTROL DEVICES	10/28	
4	CAMERA & VISION	15/28	
5	STORAGE & MEMORY	18/28	
6	VIDEO WALL	22/28	
7	INFRASTRUCTURE	25/28	
JUMLAH KESELURUHAN			

BIL.	KETERANGAN	UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)																																		
A	DISPLAY & MOUNTING																																						
A.1	SAMSUNG ESSENTIAL MONITOR S3 S32GF 27" ATAU YANG SETARA <table><tr><td>ITEM</td><td>MINIMUM SPECIFICATION</td></tr><tr><td>DISPLAY SIZE</td><td>MINIMUM 27-INCH FLAT PANEL DISPLAY</td></tr><tr><td>PANEL TYPE</td><td>IPS PANEL OR EQUIVALENT</td></tr><tr><td>RESOLUTION</td><td>FULL HD (1920 × 1080)</td></tr><tr><td>REFRESH RATE</td><td>MINIMUM 120 HZ REFRESH RATE</td></tr><tr><td>RESPONSE TIME</td><td>MAXIMUM 5 MS (GTG)</td></tr><tr><td>BRIGHTNESS</td><td>MINIMUM 250 CD/M²</td></tr><tr><td>CONTRAST RATIO</td><td>MINIMUM 1000:1 STATIC CONTRAST RATIO</td></tr><tr><td>VIEWING ANGLE</td><td>MINIMUM 178° HORIZONTAL / 178° VERTICAL</td></tr><tr><td>ASPECT RATIO</td><td>16:9 WIDESCREEN FORMAT</td></tr><tr><td>COLOR SUPPORT</td><td>MINIMUM 16.7 MILLION COLORS</td></tr><tr><td>VIDEO INPUT</td><td>MINIMUM HDMI INPUT (2 PORTS)</td></tr><tr><td>VESA MOUNT</td><td>100 × 100 MM VESA WALL MOUNT SUPPORT</td></tr><tr><td>ERGONOMIC ADJUSTMENT</td><td>TILT ADJUSTMENT SUPPORT</td></tr><tr><td>EYE PROTECTION</td><td>LOW BLUE LIGHT / FLICKER-FREE TECHNOLOGY</td></tr><tr><td>POWER SUPPLY</td><td>EXTERNAL POWER ADAPTOR</td></tr><tr><td>WARRANTY</td><td>MINIMUM 3 YEARS MANUFACTURER WARRANTY</td></tr></table>	ITEM	MINIMUM SPECIFICATION	DISPLAY SIZE	MINIMUM 27-INCH FLAT PANEL DISPLAY	PANEL TYPE	IPS PANEL OR EQUIVALENT	RESOLUTION	FULL HD (1920 × 1080)	REFRESH RATE	MINIMUM 120 HZ REFRESH RATE	RESPONSE TIME	MAXIMUM 5 MS (GTG)	BRIGHTNESS	MINIMUM 250 CD/M²	CONTRAST RATIO	MINIMUM 1000:1 STATIC CONTRAST RATIO	VIEWING ANGLE	MINIMUM 178° HORIZONTAL / 178° VERTICAL	ASPECT RATIO	16:9 WIDESCREEN FORMAT	COLOR SUPPORT	MINIMUM 16.7 MILLION COLORS	VIDEO INPUT	MINIMUM HDMI INPUT (2 PORTS)	VESA MOUNT	100 × 100 MM VESA WALL MOUNT SUPPORT	ERGONOMIC ADJUSTMENT	TILT ADJUSTMENT SUPPORT	EYE PROTECTION	LOW BLUE LIGHT / FLICKER-FREE TECHNOLOGY	POWER SUPPLY	EXTERNAL POWER ADAPTOR	WARRANTY	MINIMUM 3 YEARS MANUFACTURER WARRANTY	UNIT	2		
ITEM	MINIMUM SPECIFICATION																																						
DISPLAY SIZE	MINIMUM 27-INCH FLAT PANEL DISPLAY																																						
PANEL TYPE	IPS PANEL OR EQUIVALENT																																						
RESOLUTION	FULL HD (1920 × 1080)																																						
REFRESH RATE	MINIMUM 120 HZ REFRESH RATE																																						
RESPONSE TIME	MAXIMUM 5 MS (GTG)																																						
BRIGHTNESS	MINIMUM 250 CD/M²																																						
CONTRAST RATIO	MINIMUM 1000:1 STATIC CONTRAST RATIO																																						
VIEWING ANGLE	MINIMUM 178° HORIZONTAL / 178° VERTICAL																																						
ASPECT RATIO	16:9 WIDESCREEN FORMAT																																						
COLOR SUPPORT	MINIMUM 16.7 MILLION COLORS																																						
VIDEO INPUT	MINIMUM HDMI INPUT (2 PORTS)																																						
VESA MOUNT	100 × 100 MM VESA WALL MOUNT SUPPORT																																						
ERGONOMIC ADJUSTMENT	TILT ADJUSTMENT SUPPORT																																						
EYE PROTECTION	LOW BLUE LIGHT / FLICKER-FREE TECHNOLOGY																																						
POWER SUPPLY	EXTERNAL POWER ADAPTOR																																						
WARRANTY	MINIMUM 3 YEARS MANUFACTURER WARRANTY																																						

BIL.	KETERANGAN	UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)																														
A.2	PRISM+ ARC STEALTH DUAL MONITOR ARM ATAU YANG SETARA <table><tr><td>ITEM</td><td>MINIMUM SPECIFICATION</td></tr><tr><td>DEVICE TYPE</td><td>DESK-MOUNTED DUAL MONITOR ARM SYSTEM</td></tr><tr><td>SUPPORTED MONITOR QUANTITY</td><td>SUPPORTS TWO (2) MONITORS</td></tr><tr><td>SUPPORTED MONITOR SIZE</td><td>MINIMUM 17" – 34" DISPLAY MONITORS</td></tr><tr><td>WEIGHT CAPACITY</td><td>MINIMUM 8 KG PER MONITOR ARM</td></tr><tr><td>MOUNTING TYPE</td><td>DESK CLAMP MOUNT AND GROMMET MOUNT INSTALLATION</td></tr><tr><td>VESA COMPATIBILITY</td><td>75 × 75 MM AND 100 × 100 MM VESA MOUNTING</td></tr><tr><td>TILT ADJUSTMENT</td><td>MINIMUM +90° TO 290° TILT RANGE</td></tr><tr><td>SWIVEL ADJUSTMENT</td><td>MINIMUM ±90° SWIVEL MOVEMENT</td></tr><tr><td>ROTATION</td><td>180° ROTATION (LANDSCAPE / PORTRAIT ORIENTATION)</td></tr><tr><td>ARM EXTENSION</td><td>ADJUSTABLE ARM EXTENSION FOR ERGONOMIC POSITIONING</td></tr><tr><td>CABLE MANAGEMENT</td><td>INTEGRATED CABLE MANAGEMENT SYSTEM</td></tr><tr><td>MATERIAL</td><td>HIGH-STRENGTH STEEL AND ALUMINIUM ALLOY CONSTRUCTION</td></tr><tr><td>FINISH</td><td>DURABLE MATTE BLACK POWDER-COATED FINISH</td></tr><tr><td>DESK COMPATIBILITY</td><td>SUITABLE FOR DESKS APPROXIMATELY 10–50 MM THICKNESS</td></tr></table>	ITEM	MINIMUM SPECIFICATION	DEVICE TYPE	DESK-MOUNTED DUAL MONITOR ARM SYSTEM	SUPPORTED MONITOR QUANTITY	SUPPORTS TWO (2) MONITORS	SUPPORTED MONITOR SIZE	MINIMUM 17" – 34" DISPLAY MONITORS	WEIGHT CAPACITY	MINIMUM 8 KG PER MONITOR ARM	MOUNTING TYPE	DESK CLAMP MOUNT AND GROMMET MOUNT INSTALLATION	VESA COMPATIBILITY	75 × 75 MM AND 100 × 100 MM VESA MOUNTING	TILT ADJUSTMENT	MINIMUM +90° TO 290° TILT RANGE	SWIVEL ADJUSTMENT	MINIMUM ±90° SWIVEL MOVEMENT	ROTATION	180° ROTATION (LANDSCAPE / PORTRAIT ORIENTATION)	ARM EXTENSION	ADJUSTABLE ARM EXTENSION FOR ERGONOMIC POSITIONING	CABLE MANAGEMENT	INTEGRATED CABLE MANAGEMENT SYSTEM	MATERIAL	HIGH-STRENGTH STEEL AND ALUMINIUM ALLOY CONSTRUCTION	FINISH	DURABLE MATTE BLACK POWDER-COATED FINISH	DESK COMPATIBILITY	SUITABLE FOR DESKS APPROXIMATELY 10–50 MM THICKNESS	UNIT	1		
ITEM	MINIMUM SPECIFICATION																																		
DEVICE TYPE	DESK-MOUNTED DUAL MONITOR ARM SYSTEM																																		
SUPPORTED MONITOR QUANTITY	SUPPORTS TWO (2) MONITORS																																		
SUPPORTED MONITOR SIZE	MINIMUM 17" – 34" DISPLAY MONITORS																																		
WEIGHT CAPACITY	MINIMUM 8 KG PER MONITOR ARM																																		
MOUNTING TYPE	DESK CLAMP MOUNT AND GROMMET MOUNT INSTALLATION																																		
VESA COMPATIBILITY	75 × 75 MM AND 100 × 100 MM VESA MOUNTING																																		
TILT ADJUSTMENT	MINIMUM +90° TO 290° TILT RANGE																																		
SWIVEL ADJUSTMENT	MINIMUM ±90° SWIVEL MOVEMENT																																		
ROTATION	180° ROTATION (LANDSCAPE / PORTRAIT ORIENTATION)																																		
ARM EXTENSION	ADJUSTABLE ARM EXTENSION FOR ERGONOMIC POSITIONING																																		
CABLE MANAGEMENT	INTEGRATED CABLE MANAGEMENT SYSTEM																																		
MATERIAL	HIGH-STRENGTH STEEL AND ALUMINIUM ALLOY CONSTRUCTION																																		
FINISH	DURABLE MATTE BLACK POWDER-COATED FINISH																																		
DESK COMPATIBILITY	SUITABLE FOR DESKS APPROXIMATELY 10–50 MM THICKNESS																																		

BIL.	KETERANGAN	UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)																																		
A.3	PRISM+ ARC STEALTH PRO DUAL WITH LAPTOP HOLDER ATAU YANG SETARA	UNIT	5																																				
	<table><tr><td>ITEM</td><td>MINIMUM SPECIFICATION</td></tr><tr><td>DEVICE TYPE</td><td>DESK MOUNTED DUAL MONITOR ARM WITH LAPTOP HOLDER TRAY</td></tr><tr><td>MOUNTING TYPE</td><td>DESK C-CLAMP OR GROMMET MOUNTING SYSTEM</td></tr><tr><td>SUPPORTED MONITOR SIZE</td><td>MINIMUM 17" – 34" MONITOR DISPLAY</td></tr><tr><td>WEIGHT CAPACITY</td><td>MINIMUM UP TO 8 KG PER ARM</td></tr><tr><td>LAPTOP HOLDER</td><td>ADJUSTABLE LAPTOP HOLDER TRAY SUPPORTING 13" – 17" LAPTOP</td></tr><tr><td>STRUCTURE</td><td>POLE-BASED MODULAR ARM SYSTEM WITH ADJUSTABLE MOUNTING HEIGHT</td></tr><tr><td>ARM EXTENSION</td><td>UP TO APPROXIMATELY 514 MM ARM EXTENSION</td></tr><tr><td>HEIGHT ADJUSTMENT</td><td>VERTICAL POLE ADJUSTMENT UP TO APPROXIMATELY 620 MM</td></tr><tr><td>VESA COMPATIBILITY</td><td>75 × 75 MM AND 100 × 100 MM VESA MOUNTING</td></tr><tr><td>TILT ADJUSTMENT</td><td>MINIMUM ±90° TILT ADJUSTMENT</td></tr><tr><td>SWIVEL ADJUSTMENT</td><td>MINIMUM ±90° SWIVEL MOVEMENT</td></tr><tr><td>ROTATION</td><td>180° / PORTRAIT-LANDSCAPE ROTATION</td></tr><tr><td>CABLE MANAGEMENT</td><td>INTEGRATED CABLE MANAGEMENT ROUTING SYSTEM</td></tr><tr><td>MATERIAL</td><td>HIGH-STRENGTH STEEL AND ALUMINIUM ALLOY CONSTRUCTION</td></tr><tr><td>DESK COMPATIBILITY</td><td>SUITABLE FOR DESK THICKNESS APPROXIMATELY 10 – 50 MM</td></tr><tr><td>FINISH</td><td>DURABLE MATTE BLACK POWDER-COATED FINISH</td></tr></table>	ITEM	MINIMUM SPECIFICATION	DEVICE TYPE	DESK MOUNTED DUAL MONITOR ARM WITH LAPTOP HOLDER TRAY	MOUNTING TYPE	DESK C-CLAMP OR GROMMET MOUNTING SYSTEM	SUPPORTED MONITOR SIZE	MINIMUM 17" – 34" MONITOR DISPLAY	WEIGHT CAPACITY	MINIMUM UP TO 8 KG PER ARM	LAPTOP HOLDER	ADJUSTABLE LAPTOP HOLDER TRAY SUPPORTING 13" – 17" LAPTOP	STRUCTURE	POLE-BASED MODULAR ARM SYSTEM WITH ADJUSTABLE MOUNTING HEIGHT	ARM EXTENSION	UP TO APPROXIMATELY 514 MM ARM EXTENSION	HEIGHT ADJUSTMENT	VERTICAL POLE ADJUSTMENT UP TO APPROXIMATELY 620 MM	VESA COMPATIBILITY	75 × 75 MM AND 100 × 100 MM VESA MOUNTING	TILT ADJUSTMENT	MINIMUM ±90° TILT ADJUSTMENT	SWIVEL ADJUSTMENT	MINIMUM ±90° SWIVEL MOVEMENT	ROTATION	180° / PORTRAIT-LANDSCAPE ROTATION	CABLE MANAGEMENT	INTEGRATED CABLE MANAGEMENT ROUTING SYSTEM	MATERIAL	HIGH-STRENGTH STEEL AND ALUMINIUM ALLOY CONSTRUCTION	DESK COMPATIBILITY	SUITABLE FOR DESK THICKNESS APPROXIMATELY 10 – 50 MM	FINISH	DURABLE MATTE BLACK POWDER-COATED FINISH				
ITEM	MINIMUM SPECIFICATION																																						
DEVICE TYPE	DESK MOUNTED DUAL MONITOR ARM WITH LAPTOP HOLDER TRAY																																						
MOUNTING TYPE	DESK C-CLAMP OR GROMMET MOUNTING SYSTEM																																						
SUPPORTED MONITOR SIZE	MINIMUM 17" – 34" MONITOR DISPLAY																																						
WEIGHT CAPACITY	MINIMUM UP TO 8 KG PER ARM																																						
LAPTOP HOLDER	ADJUSTABLE LAPTOP HOLDER TRAY SUPPORTING 13" – 17" LAPTOP																																						
STRUCTURE	POLE-BASED MODULAR ARM SYSTEM WITH ADJUSTABLE MOUNTING HEIGHT																																						
ARM EXTENSION	UP TO APPROXIMATELY 514 MM ARM EXTENSION																																						
HEIGHT ADJUSTMENT	VERTICAL POLE ADJUSTMENT UP TO APPROXIMATELY 620 MM																																						
VESA COMPATIBILITY	75 × 75 MM AND 100 × 100 MM VESA MOUNTING																																						
TILT ADJUSTMENT	MINIMUM ±90° TILT ADJUSTMENT																																						
SWIVEL ADJUSTMENT	MINIMUM ±90° SWIVEL MOVEMENT																																						
ROTATION	180° / PORTRAIT-LANDSCAPE ROTATION																																						
CABLE MANAGEMENT	INTEGRATED CABLE MANAGEMENT ROUTING SYSTEM																																						
MATERIAL	HIGH-STRENGTH STEEL AND ALUMINIUM ALLOY CONSTRUCTION																																						
DESK COMPATIBILITY	SUITABLE FOR DESK THICKNESS APPROXIMATELY 10 – 50 MM																																						
FINISH	DURABLE MATTE BLACK POWDER-COATED FINISH																																						

BIL.	KETERANGAN	UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)
JUMLAH KESELURUHAN (BIL A)					

BIL.	KETERANGAN	UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)																										
B	PRINTING & SCANNING																														
B.1	CANON IMAGECLASS LBP6030W ATAU YANG SETARA <table><tr><td>ITEM</td><td>MINIMUM SPECIFICATION</td></tr><tr><td>PRINTING METHOD</td><td>MONOCHROME LASER BEAM PRINTING</td></tr><tr><td>PRINT SPEED</td><td>MINIMUM 18 PAGES PER MINUTE (A4)</td></tr><tr><td>PRINT RESOLUTION</td><td>MINIMUM 600 × 600 DPI</td></tr><tr><td>PRINT QUALITY ENHANCEMENT</td><td>UP TO 2400 (EQUIVALENT) × 600 DPI</td></tr><tr><td>FIRST PRINT OUT TIME</td><td>APPROX. 8 SECONDS OR LESS</td></tr><tr><td>CONNECTIVITY</td><td>USB 2.0 AND WIRELESS (WI-FI 802.11 B/G/N)</td></tr><tr><td>PAPER INPUT CAPACITY</td><td>MINIMUM 150 SHEETS</td></tr><tr><td>SUPPORTED PAPER SIZE</td><td>A4, A5, B5, LEGAL, LETTER</td></tr><tr><td>MEMORY</td><td>MINIMUM 32 MB</td></tr><tr><td>MONTHLY DUTY CYCLE</td><td>UP TO 5,000 PAGES</td></tr><tr><td>OPERATING SYSTEM SUPPORT</td><td>WINDOWS / MACOS / LINUX COMPATIBLE</td></tr><tr><td>POWER REQUIREMENT</td><td>220–240V AC, 50/60HZ</td></tr></table> • CATATAN PEMBEKAL HENDAKLAH MENYEDIAKAN SEKALI 2 UNIT TONER TAMBAHAN UNTUK PENCETAK TERSEBUT	ITEM	MINIMUM SPECIFICATION	PRINTING METHOD	MONOCHROME LASER BEAM PRINTING	PRINT SPEED	MINIMUM 18 PAGES PER MINUTE (A4)	PRINT RESOLUTION	MINIMUM 600 × 600 DPI	PRINT QUALITY ENHANCEMENT	UP TO 2400 (EQUIVALENT) × 600 DPI	FIRST PRINT OUT TIME	APPROX. 8 SECONDS OR LESS	CONNECTIVITY	USB 2.0 AND WIRELESS (WI-FI 802.11 B/G/N)	PAPER INPUT CAPACITY	MINIMUM 150 SHEETS	SUPPORTED PAPER SIZE	A4, A5, B5, LEGAL, LETTER	MEMORY	MINIMUM 32 MB	MONTHLY DUTY CYCLE	UP TO 5,000 PAGES	OPERATING SYSTEM SUPPORT	WINDOWS / MACOS / LINUX COMPATIBLE	POWER REQUIREMENT	220–240V AC, 50/60HZ	UNIT	20		
ITEM	MINIMUM SPECIFICATION																														
PRINTING METHOD	MONOCHROME LASER BEAM PRINTING																														
PRINT SPEED	MINIMUM 18 PAGES PER MINUTE (A4)																														
PRINT RESOLUTION	MINIMUM 600 × 600 DPI																														
PRINT QUALITY ENHANCEMENT	UP TO 2400 (EQUIVALENT) × 600 DPI																														
FIRST PRINT OUT TIME	APPROX. 8 SECONDS OR LESS																														
CONNECTIVITY	USB 2.0 AND WIRELESS (WI-FI 802.11 B/G/N)																														
PAPER INPUT CAPACITY	MINIMUM 150 SHEETS																														
SUPPORTED PAPER SIZE	A4, A5, B5, LEGAL, LETTER																														
MEMORY	MINIMUM 32 MB																														
MONTHLY DUTY CYCLE	UP TO 5,000 PAGES																														
OPERATING SYSTEM SUPPORT	WINDOWS / MACOS / LINUX COMPATIBLE																														
POWER REQUIREMENT	220–240V AC, 50/60HZ																														

BIL.	KETERANGAN	UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)																																										
B.2	EPSON WORKFORCE ES-60W WIRELESS PORTABLE DOCUMENT SCANNER ATAU YANG SETARA	UNIT	3																																												
	<table><tr><td>ITEM</td><td>MINIMUM SPECIFICATION</td></tr><tr><td>DEVICE TYPE</td><td>WIRELESS PORTABLE SHEET-FED DOCUMENT SCANNER</td></tr><tr><td>SCANNING TECHNOLOGY</td><td>CONTACT IMAGE SENSOR (CIS)</td></tr><tr><td>OPTICAL RESOLUTION</td><td>MINIMUM 600 × 600 DPI</td></tr><tr><td>MAXIMUM RESOLUTION</td><td>UP TO 1200 DPI INTERPOLATED</td></tr><tr><td>SCAN SPEED</td><td>UP TO 4 SECONDS PER PAGE (SINGLE PAGE SCAN)</td></tr><tr><td>SCANNING MODE</td><td>COLOUR, GRAYSCALE AND MONOCHROME SCANNING</td></tr><tr><td>MAXIMUM DOCUMENT SIZE</td><td>UP TO A4 (216 × 1828 MM)</td></tr><tr><td>PAPER HANDLING</td><td>SUPPORTS PLAIN PAPER, RECEIPTS, BUSINESS CARDS AND PLASTIC ID CARDS</td></tr><tr><td>ADF CAPACITY</td><td>SINGLE-SHEET FEED SYSTEM</td></tr><tr><td>DAILY DUTY CYCLE</td><td>UP TO 300 PAGES PER DAY</td></tr><tr><td>CONNECTIVITY</td><td>USB 2.0 (MICRO-USB) AND WI-FI (802.11 B/G/N)</td></tr><tr><td>WIRELESS SCANNING</td><td>SUPPORTS SCANNING TO PC, MAC, IOS AND ANDROID DEVICES</td></tr><tr><td>BATTERY</td><td>BUILT-IN RECHARGEABLE LITHIUM-ION BATTERY</td></tr><tr><td>BATTERY CAPACITY</td><td>APPROX. 1140 MAH</td></tr><tr><td>BATTERY PERFORMANCE</td><td>UP TO 300 SCANS PER FULL CHARGE</td></tr><tr><td>CHARGING METHOD</td><td>RECHARGE VIA USB CONNECTION OR AC ADAPTER</td></tr><tr><td>DISPLAY</td><td>BUILT-IN STATUS LCD DISPLAY (WI-FI AND BATTERY INDICATOR)</td></tr><tr><td>SOFTWARE SUPPORT</td><td>EPSON SCANSMART SOFTWARE WITH OCR CAPABILITY</td></tr><tr><td>FILE OUTPUT</td><td>SUPPORTS PDF, SEARCHABLE PDF, JPEG, TIFF AND EDITABLE WORD/EXCEL FORMATS</td></tr><tr><td>OPERATING</td><td>COMPATIBLE WITH</td></tr></table>	ITEM	MINIMUM SPECIFICATION	DEVICE TYPE	WIRELESS PORTABLE SHEET-FED DOCUMENT SCANNER	SCANNING TECHNOLOGY	CONTACT IMAGE SENSOR (CIS)	OPTICAL RESOLUTION	MINIMUM 600 × 600 DPI	MAXIMUM RESOLUTION	UP TO 1200 DPI INTERPOLATED	SCAN SPEED	UP TO 4 SECONDS PER PAGE (SINGLE PAGE SCAN)	SCANNING MODE	COLOUR, GRAYSCALE AND MONOCHROME SCANNING	MAXIMUM DOCUMENT SIZE	UP TO A4 (216 × 1828 MM)	PAPER HANDLING	SUPPORTS PLAIN PAPER, RECEIPTS, BUSINESS CARDS AND PLASTIC ID CARDS	ADF CAPACITY	SINGLE-SHEET FEED SYSTEM	DAILY DUTY CYCLE	UP TO 300 PAGES PER DAY	CONNECTIVITY	USB 2.0 (MICRO-USB) AND WI-FI (802.11 B/G/N)	WIRELESS SCANNING	SUPPORTS SCANNING TO PC, MAC, IOS AND ANDROID DEVICES	BATTERY	BUILT-IN RECHARGEABLE LITHIUM-ION BATTERY	BATTERY CAPACITY	APPROX. 1140 MAH	BATTERY PERFORMANCE	UP TO 300 SCANS PER FULL CHARGE	CHARGING METHOD	RECHARGE VIA USB CONNECTION OR AC ADAPTER	DISPLAY	BUILT-IN STATUS LCD DISPLAY (WI-FI AND BATTERY INDICATOR)	SOFTWARE SUPPORT	EPSON SCANSMART SOFTWARE WITH OCR CAPABILITY	FILE OUTPUT	SUPPORTS PDF, SEARCHABLE PDF, JPEG, TIFF AND EDITABLE WORD/EXCEL FORMATS	OPERATING	COMPATIBLE WITH				
ITEM	MINIMUM SPECIFICATION																																														
DEVICE TYPE	WIRELESS PORTABLE SHEET-FED DOCUMENT SCANNER																																														
SCANNING TECHNOLOGY	CONTACT IMAGE SENSOR (CIS)																																														
OPTICAL RESOLUTION	MINIMUM 600 × 600 DPI																																														
MAXIMUM RESOLUTION	UP TO 1200 DPI INTERPOLATED																																														
SCAN SPEED	UP TO 4 SECONDS PER PAGE (SINGLE PAGE SCAN)																																														
SCANNING MODE	COLOUR, GRAYSCALE AND MONOCHROME SCANNING																																														
MAXIMUM DOCUMENT SIZE	UP TO A4 (216 × 1828 MM)																																														
PAPER HANDLING	SUPPORTS PLAIN PAPER, RECEIPTS, BUSINESS CARDS AND PLASTIC ID CARDS																																														
ADF CAPACITY	SINGLE-SHEET FEED SYSTEM																																														
DAILY DUTY CYCLE	UP TO 300 PAGES PER DAY																																														
CONNECTIVITY	USB 2.0 (MICRO-USB) AND WI-FI (802.11 B/G/N)																																														
WIRELESS SCANNING	SUPPORTS SCANNING TO PC, MAC, IOS AND ANDROID DEVICES																																														
BATTERY	BUILT-IN RECHARGEABLE LITHIUM-ION BATTERY																																														
BATTERY CAPACITY	APPROX. 1140 MAH																																														
BATTERY PERFORMANCE	UP TO 300 SCANS PER FULL CHARGE																																														
CHARGING METHOD	RECHARGE VIA USB CONNECTION OR AC ADAPTER																																														
DISPLAY	BUILT-IN STATUS LCD DISPLAY (WI-FI AND BATTERY INDICATOR)																																														
SOFTWARE SUPPORT	EPSON SCANSMART SOFTWARE WITH OCR CAPABILITY																																														
FILE OUTPUT	SUPPORTS PDF, SEARCHABLE PDF, JPEG, TIFF AND EDITABLE WORD/EXCEL FORMATS																																														
OPERATING	COMPATIBLE WITH																																														

BIL.	KETERANGAN	UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)																																												
B.3	EPSON LQ-590 II IMPACT PRINTER ATAU YANG SETARA	UNIT	5																																														
	<table><tr><td>ITEM</td><td>MINIMUM SPECIFICATION</td></tr><tr><td>PRINTER TYPE</td><td>24-PIN IMPACT DOT MATRIX PRINTER</td></tr><tr><td>PRINTING METHOD</td><td>SERIAL IMPACT DOT MATRIX</td></tr><tr><td>NUMBER OF PINS</td><td>24 PINS</td></tr><tr><td>PRINT DIRECTION</td><td>BIDIRECTIONAL WITH LOGIC SEEKING</td></tr><tr><td>PRINT WIDTH</td><td>80 COLUMNS</td></tr><tr><td>PRINT SPEED</td><td>UP TO 550 CPS (10 CPI) ULTRA SPEED DRAFT</td></tr><tr><td>DRAFT SPEED</td><td>UP TO 487 CPS (10 CPI) HIGH SPEED DRAFT</td></tr><tr><td>LETTER QUALITY SPEED</td><td>UP TO 145 CPS</td></tr><tr><td>PRINT RESOLUTION</td><td>UP TO 360 X 180 DPI</td></tr><tr><td>PRINT HEAD LIFE</td><td>MINIMUM 400 MILLION STROKES/WIRE</td></tr><tr><td>RIBBON LIFE</td><td>MINIMUM 5 MILLION CHARACTERS</td></tr><tr><td>MEAN TIME BETWEEN FAILURE (MTBF)</td><td>MINIMUM 25,000 POWER-ON HOURS</td></tr><tr><td>MULTIPART FORMS CAPABILITY</td><td>MINIMUM 1 ORIGINAL + 6 COPIES</td></tr><tr><td>PAPER HANDLING</td><td>CONTINUOUS FORMS, SINGLE SHEETS, MULTIPART FORMS, LABELS, ENVELOPES AND CARD STOCK</td></tr><tr><td>PAPER FEED PATH</td><td>FRONT, REAR AND BOTTOM FEED</td></tr><tr><td>CHARACTER SETS</td><td>STANDARD AND INTERNATIONAL CHARACTER SETS</td></tr><tr><td>BARCODE SUPPORT</td><td>CODE 39, CODE 128, EAN-8, EAN-13, UPC-A, UPC-E, INTERLEAVED 2 OF 5, POSTNET</td></tr><tr><td>PRINTER LANGUAGES</td><td>EPSON ESC/P2 AND IBM PPDS EMULATION</td></tr><tr><td>CONNECTIVITY</td><td>USB 2.0 HIGH-SPEED AND PARALLEL INTERFACE</td></tr><tr><td>OPERATING SYSTEMS SUPPORTED</td><td>MICROSOFT WINDOWS 10, WINDOWS 11 OR LATER</td></tr><tr><td>CONTROL PANEL</td><td>INTEGRATED CONTROL PANEL WITH STATUS</td></tr></table>	ITEM	MINIMUM SPECIFICATION	PRINTER TYPE	24-PIN IMPACT DOT MATRIX PRINTER	PRINTING METHOD	SERIAL IMPACT DOT MATRIX	NUMBER OF PINS	24 PINS	PRINT DIRECTION	BIDIRECTIONAL WITH LOGIC SEEKING	PRINT WIDTH	80 COLUMNS	PRINT SPEED	UP TO 550 CPS (10 CPI) ULTRA SPEED DRAFT	DRAFT SPEED	UP TO 487 CPS (10 CPI) HIGH SPEED DRAFT	LETTER QUALITY SPEED	UP TO 145 CPS	PRINT RESOLUTION	UP TO 360 X 180 DPI	PRINT HEAD LIFE	MINIMUM 400 MILLION STROKES/WIRE	RIBBON LIFE	MINIMUM 5 MILLION CHARACTERS	MEAN TIME BETWEEN FAILURE (MTBF)	MINIMUM 25,000 POWER-ON HOURS	MULTIPART FORMS CAPABILITY	MINIMUM 1 ORIGINAL + 6 COPIES	PAPER HANDLING	CONTINUOUS FORMS, SINGLE SHEETS, MULTIPART FORMS, LABELS, ENVELOPES AND CARD STOCK	PAPER FEED PATH	FRONT, REAR AND BOTTOM FEED	CHARACTER SETS	STANDARD AND INTERNATIONAL CHARACTER SETS	BARCODE SUPPORT	CODE 39, CODE 128, EAN-8, EAN-13, UPC-A, UPC-E, INTERLEAVED 2 OF 5, POSTNET	PRINTER LANGUAGES	EPSON ESC/P2 AND IBM PPDS EMULATION	CONNECTIVITY	USB 2.0 HIGH-SPEED AND PARALLEL INTERFACE	OPERATING SYSTEMS SUPPORTED	MICROSOFT WINDOWS 10, WINDOWS 11 OR LATER	CONTROL PANEL	INTEGRATED CONTROL PANEL WITH STATUS				
ITEM	MINIMUM SPECIFICATION																																																
PRINTER TYPE	24-PIN IMPACT DOT MATRIX PRINTER																																																
PRINTING METHOD	SERIAL IMPACT DOT MATRIX																																																
NUMBER OF PINS	24 PINS																																																
PRINT DIRECTION	BIDIRECTIONAL WITH LOGIC SEEKING																																																
PRINT WIDTH	80 COLUMNS																																																
PRINT SPEED	UP TO 550 CPS (10 CPI) ULTRA SPEED DRAFT																																																
DRAFT SPEED	UP TO 487 CPS (10 CPI) HIGH SPEED DRAFT																																																
LETTER QUALITY SPEED	UP TO 145 CPS																																																
PRINT RESOLUTION	UP TO 360 X 180 DPI																																																
PRINT HEAD LIFE	MINIMUM 400 MILLION STROKES/WIRE																																																
RIBBON LIFE	MINIMUM 5 MILLION CHARACTERS																																																
MEAN TIME BETWEEN FAILURE (MTBF)	MINIMUM 25,000 POWER-ON HOURS																																																
MULTIPART FORMS CAPABILITY	MINIMUM 1 ORIGINAL + 6 COPIES																																																
PAPER HANDLING	CONTINUOUS FORMS, SINGLE SHEETS, MULTIPART FORMS, LABELS, ENVELOPES AND CARD STOCK																																																
PAPER FEED PATH	FRONT, REAR AND BOTTOM FEED																																																
CHARACTER SETS	STANDARD AND INTERNATIONAL CHARACTER SETS																																																
BARCODE SUPPORT	CODE 39, CODE 128, EAN-8, EAN-13, UPC-A, UPC-E, INTERLEAVED 2 OF 5, POSTNET																																																
PRINTER LANGUAGES	EPSON ESC/P2 AND IBM PPDS EMULATION																																																
CONNECTIVITY	USB 2.0 HIGH-SPEED AND PARALLEL INTERFACE																																																
OPERATING SYSTEMS SUPPORTED	MICROSOFT WINDOWS 10, WINDOWS 11 OR LATER																																																
CONTROL PANEL	INTEGRATED CONTROL PANEL WITH STATUS																																																

BIL.	KETERANGAN	UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)
JUMLAH KESELURUHAN (BIL B)					

BIL.	KETERANGAN	UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)
C	INPUT & CONTROL DEVICES				

BIL.	KETERANGAN	UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)																														
C.1	APPLE MAGIC KEYBOARD FOR IPAD 11" M4/M5 ATAU YANG SETARA <table><tr><td>ITEM</td><td>MINIMUM SPECIFICATION</td></tr><tr><td>REFERENCE MODEL</td><td>APPLE MAGIC KEYBOARD FOR IPAD PRO 11-INCH OR EQUIVALENT</td></tr><tr><td>COMPATIBILITY</td><td>COMPATIBLE WITH IPAD PRO 11-INCH (LATEST GENERATION OR EQUIVALENT)</td></tr><tr><td>CONNECTION TYPE</td><td>SMART CONNECTOR WITH MAGNETIC ATTACHMENT</td></tr><tr><td>KEYBOARD TYPE</td><td>FULL-SIZE KEYBOARD WITH BACKLIT KEYS</td></tr><tr><td>KEY MECHANISM</td><td>SCISSOR-SWITCH MECHANISM</td></tr><tr><td>KEY TRAVEL</td><td>APPROXIMATELY 1 MM KEY TRAVEL</td></tr><tr><td>TRACKPAD</td><td>BUILT-IN MULTI-TOUCH TRACKPAD SUPPORTING IPADOS GESTURES</td></tr><tr><td>DESIGN</td><td>FLOATING CANTILEVER DESIGN ALLOWING ADJUSTABLE VIEWING ANGLES</td></tr><tr><td>FUNCTION ROW</td><td>INTEGRATED FUNCTION KEY ROW FOR BRIGHTNESS, VOLUME, MEDIA CONTROL, ETC.</td></tr><tr><td>CHARGING PORT</td><td>USB-C PASS-THROUGH CHARGING PORT</td></tr><tr><td>PROTECTION</td><td>PROVIDES FRONT AND BACK PROTECTION FOR THE IPAD</td></tr><tr><td>BUILD MATERIAL</td><td>PREMIUM KEYBOARD CASE WITH DURABLE HINGE MECHANISM</td></tr><tr><td>OPERATING SYSTEM SUPPORT</td><td>COMPATIBLE WITH IPADOS 17 OR LATER</td></tr><tr><td>ADDITIONAL FEATURES</td><td>SUPPORTS MULTI-TOUCH GESTURES AND CURSOR CONTROL VIA TRACKPAD</td></tr></table>	ITEM	MINIMUM SPECIFICATION	REFERENCE MODEL	APPLE MAGIC KEYBOARD FOR IPAD PRO 11-INCH OR EQUIVALENT	COMPATIBILITY	COMPATIBLE WITH IPAD PRO 11-INCH (LATEST GENERATION OR EQUIVALENT)	CONNECTION TYPE	SMART CONNECTOR WITH MAGNETIC ATTACHMENT	KEYBOARD TYPE	FULL-SIZE KEYBOARD WITH BACKLIT KEYS	KEY MECHANISM	SCISSOR-SWITCH MECHANISM	KEY TRAVEL	APPROXIMATELY 1 MM KEY TRAVEL	TRACKPAD	BUILT-IN MULTI-TOUCH TRACKPAD SUPPORTING IPADOS GESTURES	DESIGN	FLOATING CANTILEVER DESIGN ALLOWING ADJUSTABLE VIEWING ANGLES	FUNCTION ROW	INTEGRATED FUNCTION KEY ROW FOR BRIGHTNESS, VOLUME, MEDIA CONTROL, ETC.	CHARGING PORT	USB-C PASS-THROUGH CHARGING PORT	PROTECTION	PROVIDES FRONT AND BACK PROTECTION FOR THE IPAD	BUILD MATERIAL	PREMIUM KEYBOARD CASE WITH DURABLE HINGE MECHANISM	OPERATING SYSTEM SUPPORT	COMPATIBLE WITH IPADOS 17 OR LATER	ADDITIONAL FEATURES	SUPPORTS MULTI-TOUCH GESTURES AND CURSOR CONTROL VIA TRACKPAD	UNIT	7		
ITEM	MINIMUM SPECIFICATION																																		
REFERENCE MODEL	APPLE MAGIC KEYBOARD FOR IPAD PRO 11-INCH OR EQUIVALENT																																		
COMPATIBILITY	COMPATIBLE WITH IPAD PRO 11-INCH (LATEST GENERATION OR EQUIVALENT)																																		
CONNECTION TYPE	SMART CONNECTOR WITH MAGNETIC ATTACHMENT																																		
KEYBOARD TYPE	FULL-SIZE KEYBOARD WITH BACKLIT KEYS																																		
KEY MECHANISM	SCISSOR-SWITCH MECHANISM																																		
KEY TRAVEL	APPROXIMATELY 1 MM KEY TRAVEL																																		
TRACKPAD	BUILT-IN MULTI-TOUCH TRACKPAD SUPPORTING IPADOS GESTURES																																		
DESIGN	FLOATING CANTILEVER DESIGN ALLOWING ADJUSTABLE VIEWING ANGLES																																		
FUNCTION ROW	INTEGRATED FUNCTION KEY ROW FOR BRIGHTNESS, VOLUME, MEDIA CONTROL, ETC.																																		
CHARGING PORT	USB-C PASS-THROUGH CHARGING PORT																																		
PROTECTION	PROVIDES FRONT AND BACK PROTECTION FOR THE IPAD																																		
BUILD MATERIAL	PREMIUM KEYBOARD CASE WITH DURABLE HINGE MECHANISM																																		
OPERATING SYSTEM SUPPORT	COMPATIBLE WITH IPADOS 17 OR LATER																																		
ADDITIONAL FEATURES	SUPPORTS MULTI-TOUCH GESTURES AND CURSOR CONTROL VIA TRACKPAD																																		

BIL.	KETERANGAN	UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)																						
C.2	LOGITECH SPOTLIGHT WIRELESS PRESENTER ATAU YANG SETARA	UNIT	1																								
	<table><tr><td>ITEM</td><td>MINIMUM SPECIFICATION</td></tr><tr><td>DEVICE TYPE</td><td>WIRELESS PRESENTATION REMOTE / PRESENTER</td></tr><tr><td>CONNECTIVITY</td><td>BLUETOOTH LOW ENERGY OR USB RECEIVER (2.4 GHZ)</td></tr><tr><td>OPERATING RANGE</td><td>UP TO 30 M (100 FT)</td></tr><tr><td>POINTER TYPE</td><td>ADVANCED DIGITAL POINTER (HIGHLIGHT / MAGNIFY)</td></tr><tr><td>CONTROLS</td><td>NEXT, BACK, HIGHLIGHT BUTTONS</td></tr><tr><td>COMPATIBILITY</td><td>WINDOWS, MACOS, POWERPOINT, KEYNOTE, GOOGLE SLIDES</td></tr><tr><td>BATTERY</td><td>RECHARGEABLE LITHIUM-POLYMER BATTERY</td></tr><tr><td>CHARGING</td><td>USB-C CHARGING</td></tr><tr><td>BATTERY LIFE</td><td>UP TO 3 MONTHS PER FULL CHARGE</td></tr><tr><td>SENSORS</td><td>3D ACCELEROMETER & GYROSCOPE</td></tr></table>	ITEM	MINIMUM SPECIFICATION	DEVICE TYPE	WIRELESS PRESENTATION REMOTE / PRESENTER	CONNECTIVITY	BLUETOOTH LOW ENERGY OR USB RECEIVER (2.4 GHZ)	OPERATING RANGE	UP TO 30 M (100 FT)	POINTER TYPE	ADVANCED DIGITAL POINTER (HIGHLIGHT / MAGNIFY)	CONTROLS	NEXT, BACK, HIGHLIGHT BUTTONS	COMPATIBILITY	WINDOWS, MACOS, POWERPOINT, KEYNOTE, GOOGLE SLIDES	BATTERY	RECHARGEABLE LITHIUM-POLYMER BATTERY	CHARGING	USB-C CHARGING	BATTERY LIFE	UP TO 3 MONTHS PER FULL CHARGE	SENSORS	3D ACCELEROMETER & GYROSCOPE				
ITEM	MINIMUM SPECIFICATION																										
DEVICE TYPE	WIRELESS PRESENTATION REMOTE / PRESENTER																										
CONNECTIVITY	BLUETOOTH LOW ENERGY OR USB RECEIVER (2.4 GHZ)																										
OPERATING RANGE	UP TO 30 M (100 FT)																										
POINTER TYPE	ADVANCED DIGITAL POINTER (HIGHLIGHT / MAGNIFY)																										
CONTROLS	NEXT, BACK, HIGHLIGHT BUTTONS																										
COMPATIBILITY	WINDOWS, MACOS, POWERPOINT, KEYNOTE, GOOGLE SLIDES																										
BATTERY	RECHARGEABLE LITHIUM-POLYMER BATTERY																										
CHARGING	USB-C CHARGING																										
BATTERY LIFE	UP TO 3 MONTHS PER FULL CHARGE																										
SENSORS	3D ACCELEROMETER & GYROSCOPE																										

BIL.	KETERANGAN	UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)																																				
C.3	HONEYWELL XENON 1902G WIRELESS BARCODE SCANNER ATAU YANG SETARA <table><tr><td>ITEM</td><td>MINIMUM SPECIFICATION</td></tr><tr><td>DEVICE TYPE</td><td>WIRELESS HANDHELD 1D / 2D BARCODE SCANNER</td></tr><tr><td>SCANNING TECHNOLOGY</td><td>AREA-IMAGING TECHNOLOGY WITH ADAPTUS™ IMAGING TECHNOLOGY 6.0</td></tr><tr><td>SUPPORTED BARCODE TYPES</td><td>1D, 2D, PDF417, QR CODE, DATA MATRIX, AZTEC</td></tr><tr><td>CONNECTIVITY</td><td>BLUETOOTH WIRELESS COMMUNICATION</td></tr><tr><td>WIRELESS RANGE</td><td>MINIMUM 10 M (33 FT) OPERATING RANGE FROM BASE STATION</td></tr><tr><td>SCANNING PERFORMANCE</td><td>HIGH-SPEED OMNIDIRECTIONAL BARCODE SCANNING</td></tr><tr><td>SENSOR TYPE</td><td>CUSTOM AREA IMAGER OPTIMIZED FOR BARCODE SCANNING</td></tr><tr><td>MOBILE BARCODE SUPPORT</td><td>CAPABLE OF SCANNING BARCODES FROM SMARTPHONE AND TABLET SCREENS</td></tr><tr><td>SCANNING MODE</td><td>HANDHELD TRIGGER SCANNING</td></tr><tr><td>IMAGE CAPTURE</td><td>SUPPORTS IMAGE CAPTURE AND DIGITAL IMAGE PROCESSING</td></tr><tr><td>BATTERY</td><td>RECHARGEABLE LITHIUM-ION BATTERY</td></tr><tr><td>BATTERY LIFE</td><td>UP TO 14 HOURS OF CONTINUOUS OPERATION</td></tr><tr><td>DROP RESISTANCE</td><td>MINIMUM 1.8 M (6 FT) DROP RESISTANCE</td></tr><tr><td>ENVIRONMENTAL PROTECTION</td><td>INDUSTRIAL- GRADE RUGGED CONSTRUCTION</td></tr><tr><td>INDICATOR</td><td>LED INDICATOR AND AUDIBLE BEEPER FEEDBACK</td></tr><tr><td>HOST INTERFACE</td><td>USB / KEYBOARD WEDGE / RS-232 / IBM POS INTERFACE SUPPORT</td></tr><tr><td>CHARGING METHOD</td><td>CHARGING VIA COMMUNICATION BASE STATION OR</td></tr></table>	ITEM	MINIMUM SPECIFICATION	DEVICE TYPE	WIRELESS HANDHELD 1D / 2D BARCODE SCANNER	SCANNING TECHNOLOGY	AREA-IMAGING TECHNOLOGY WITH ADAPTUS™ IMAGING TECHNOLOGY 6.0	SUPPORTED BARCODE TYPES	1D, 2D, PDF417, QR CODE, DATA MATRIX, AZTEC	CONNECTIVITY	BLUETOOTH WIRELESS COMMUNICATION	WIRELESS RANGE	MINIMUM 10 M (33 FT) OPERATING RANGE FROM BASE STATION	SCANNING PERFORMANCE	HIGH-SPEED OMNIDIRECTIONAL BARCODE SCANNING	SENSOR TYPE	CUSTOM AREA IMAGER OPTIMIZED FOR BARCODE SCANNING	MOBILE BARCODE SUPPORT	CAPABLE OF SCANNING BARCODES FROM SMARTPHONE AND TABLET SCREENS	SCANNING MODE	HANDHELD TRIGGER SCANNING	IMAGE CAPTURE	SUPPORTS IMAGE CAPTURE AND DIGITAL IMAGE PROCESSING	BATTERY	RECHARGEABLE LITHIUM-ION BATTERY	BATTERY LIFE	UP TO 14 HOURS OF CONTINUOUS OPERATION	DROP RESISTANCE	MINIMUM 1.8 M (6 FT) DROP RESISTANCE	ENVIRONMENTAL PROTECTION	INDUSTRIAL- GRADE RUGGED CONSTRUCTION	INDICATOR	LED INDICATOR AND AUDIBLE BEEPER FEEDBACK	HOST INTERFACE	USB / KEYBOARD WEDGE / RS-232 / IBM POS INTERFACE SUPPORT	CHARGING METHOD	CHARGING VIA COMMUNICATION BASE STATION OR	UNIT	2		
ITEM	MINIMUM SPECIFICATION																																								
DEVICE TYPE	WIRELESS HANDHELD 1D / 2D BARCODE SCANNER																																								
SCANNING TECHNOLOGY	AREA-IMAGING TECHNOLOGY WITH ADAPTUS™ IMAGING TECHNOLOGY 6.0																																								
SUPPORTED BARCODE TYPES	1D, 2D, PDF417, QR CODE, DATA MATRIX, AZTEC																																								
CONNECTIVITY	BLUETOOTH WIRELESS COMMUNICATION																																								
WIRELESS RANGE	MINIMUM 10 M (33 FT) OPERATING RANGE FROM BASE STATION																																								
SCANNING PERFORMANCE	HIGH-SPEED OMNIDIRECTIONAL BARCODE SCANNING																																								
SENSOR TYPE	CUSTOM AREA IMAGER OPTIMIZED FOR BARCODE SCANNING																																								
MOBILE BARCODE SUPPORT	CAPABLE OF SCANNING BARCODES FROM SMARTPHONE AND TABLET SCREENS																																								
SCANNING MODE	HANDHELD TRIGGER SCANNING																																								
IMAGE CAPTURE	SUPPORTS IMAGE CAPTURE AND DIGITAL IMAGE PROCESSING																																								
BATTERY	RECHARGEABLE LITHIUM-ION BATTERY																																								
BATTERY LIFE	UP TO 14 HOURS OF CONTINUOUS OPERATION																																								
DROP RESISTANCE	MINIMUM 1.8 M (6 FT) DROP RESISTANCE																																								
ENVIRONMENTAL PROTECTION	INDUSTRIAL- GRADE RUGGED CONSTRUCTION																																								
INDICATOR	LED INDICATOR AND AUDIBLE BEEPER FEEDBACK																																								
HOST INTERFACE	USB / KEYBOARD WEDGE / RS-232 / IBM POS INTERFACE SUPPORT																																								
CHARGING METHOD	CHARGING VIA COMMUNICATION BASE STATION OR																																								

BIL.	KETERANGAN	UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)
JUMLAH KESELURUHAN (BIL C)					

BIL.	KETERANGAN	UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)
D	CAMERA & VISION				

BIL.	KETERANGAN	UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)																																				
D.1	INSTA360 LINK 2 PRO AI 4K WEBCAM ATAU YANG SETARA	UNIT	23																																						
	<table><tr><td>ITEM</td><td>MINIMUM SPECIFICATION</td></tr><tr><td>DEVICE TYPE</td><td>AI-POWERED 4K WEBCAM WITH INTELLIGENT TRACKING</td></tr><tr><td>IMAGE SENSOR</td><td>MINIMUM 1/1.3-INCH CMOS SENSOR</td></tr><tr><td>VIDEO RESOLUTION</td><td>UP TO 4K UHD (3840 × 2160) @30FPS</td></tr><tr><td>ALTERNATIVE RESOLUTION</td><td>1080P @60FPS, 720P VIDEO MODES</td></tr><tr><td>LENS APERTURE</td><td>APPROX. F/1.9 APERTURE</td></tr><tr><td>FIELD OF VIEW</td><td>APPROXIMATELY 84° WIDE VIEWING ANGLE</td></tr><tr><td>FOCUS SYSTEM</td><td>PHASE DETECTION AUTOFOCUS (12 CM – ∞)</td></tr><tr><td>AI TRACKING</td><td>AI SUBJECT TRACKING WITH MOTORIZED 2-AXIS GIMBAL</td></tr><tr><td>AUTO FRAMING</td><td>AI AUTO FRAMING FOR INDIVIDUAL OR GROUP PARTICIPANTS</td></tr><tr><td>AI FEATURES</td><td>AI TRACKING, GESTURE CONTROL, DESKVIEW MODE, WHITEBOARD MODE, PORTRAIT MODE, VIRTUAL BACKGROUND</td></tr><tr><td>HDR SUPPORT</td><td>HDR VIDEO SUPPORT FOR IMPROVED LIGHTING BALANCE</td></tr><tr><td>ZOOM</td><td>UP TO 4× DIGITAL ZOOM</td></tr><tr><td>AUDIO</td><td>DUAL MICROPHONES WITH BEAMFORMING AND AI NOISE CANCELLATION</td></tr><tr><td>CONNECTIVITY</td><td>USB-C INTERFACE (USB-C TO USB-A ADAPTER SUPPORTED)</td></tr><tr><td>MOUNTING</td><td>MAGNETIC MOUNT WITH 1/4" TRIPOD THREAD COMPATIBILITY</td></tr><tr><td>ORIENTATION</td><td>SUPPORTS LANDSCAPE AND PORTRAIT ORIENTATION</td></tr><tr><td>SOFTWARE SUPPORT</td><td>COMPATIBLE WITH ZOOM, MICROSOFT</td></tr></table>	ITEM	MINIMUM SPECIFICATION	DEVICE TYPE	AI-POWERED 4K WEBCAM WITH INTELLIGENT TRACKING	IMAGE SENSOR	MINIMUM 1/1.3-INCH CMOS SENSOR	VIDEO RESOLUTION	UP TO 4K UHD (3840 × 2160) @30FPS	ALTERNATIVE RESOLUTION	1080P @60FPS, 720P VIDEO MODES	LENS APERTURE	APPROX. F/1.9 APERTURE	FIELD OF VIEW	APPROXIMATELY 84° WIDE VIEWING ANGLE	FOCUS SYSTEM	PHASE DETECTION AUTOFOCUS (12 CM – ∞)	AI TRACKING	AI SUBJECT TRACKING WITH MOTORIZED 2-AXIS GIMBAL	AUTO FRAMING	AI AUTO FRAMING FOR INDIVIDUAL OR GROUP PARTICIPANTS	AI FEATURES	AI TRACKING, GESTURE CONTROL, DESKVIEW MODE, WHITEBOARD MODE, PORTRAIT MODE, VIRTUAL BACKGROUND	HDR SUPPORT	HDR VIDEO SUPPORT FOR IMPROVED LIGHTING BALANCE	ZOOM	UP TO 4× DIGITAL ZOOM	AUDIO	DUAL MICROPHONES WITH BEAMFORMING AND AI NOISE CANCELLATION	CONNECTIVITY	USB-C INTERFACE (USB-C TO USB-A ADAPTER SUPPORTED)	MOUNTING	MAGNETIC MOUNT WITH 1/4" TRIPOD THREAD COMPATIBILITY	ORIENTATION	SUPPORTS LANDSCAPE AND PORTRAIT ORIENTATION	SOFTWARE SUPPORT	COMPATIBLE WITH ZOOM, MICROSOFT				
ITEM	MINIMUM SPECIFICATION																																								
DEVICE TYPE	AI-POWERED 4K WEBCAM WITH INTELLIGENT TRACKING																																								
IMAGE SENSOR	MINIMUM 1/1.3-INCH CMOS SENSOR																																								
VIDEO RESOLUTION	UP TO 4K UHD (3840 × 2160) @30FPS																																								
ALTERNATIVE RESOLUTION	1080P @60FPS, 720P VIDEO MODES																																								
LENS APERTURE	APPROX. F/1.9 APERTURE																																								
FIELD OF VIEW	APPROXIMATELY 84° WIDE VIEWING ANGLE																																								
FOCUS SYSTEM	PHASE DETECTION AUTOFOCUS (12 CM – ∞)																																								
AI TRACKING	AI SUBJECT TRACKING WITH MOTORIZED 2-AXIS GIMBAL																																								
AUTO FRAMING	AI AUTO FRAMING FOR INDIVIDUAL OR GROUP PARTICIPANTS																																								
AI FEATURES	AI TRACKING, GESTURE CONTROL, DESKVIEW MODE, WHITEBOARD MODE, PORTRAIT MODE, VIRTUAL BACKGROUND																																								
HDR SUPPORT	HDR VIDEO SUPPORT FOR IMPROVED LIGHTING BALANCE																																								
ZOOM	UP TO 4× DIGITAL ZOOM																																								
AUDIO	DUAL MICROPHONES WITH BEAMFORMING AND AI NOISE CANCELLATION																																								
CONNECTIVITY	USB-C INTERFACE (USB-C TO USB-A ADAPTER SUPPORTED)																																								
MOUNTING	MAGNETIC MOUNT WITH 1/4" TRIPOD THREAD COMPATIBILITY																																								
ORIENTATION	SUPPORTS LANDSCAPE AND PORTRAIT ORIENTATION																																								
SOFTWARE SUPPORT	COMPATIBLE WITH ZOOM, MICROSOFT																																								

BIL.	KETERANGAN	UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)
JUMLAH KESELURUHAN (BIL D)					

BIL.	KETERANGAN	UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)																												
E	STORAGE & MEMORY																																
E.1	SANDISK ULTRA DUAL DRIVE GO ATAU YANG SETARA	UNIT	8																														
	<table><tr><td>ITEM</td><td>MINIMUM SPECIFICATION</td></tr><tr><td>DEVICE TYPE</td><td>USB FLASH DRIVE WITH DUAL CONNECTOR (USB-C AND USB-A)</td></tr><tr><td>STORAGE CAPACITY</td><td>MINIMUM 256 GB FLASH STORAGE</td></tr><tr><td>INTERFACE</td><td>USB TYPE-C AND USB TYPE-A CONNECTORS</td></tr><tr><td>USB STANDARD</td><td>USB 3.2 GEN 1 / USB 3.1 GEN 1</td></tr><tr><td>READ SPEED</td><td>UP TO 150 MB/S READ SPEED</td></tr><tr><td>COMPATIBILITY</td><td>COMPATIBLE WITH WINDOWS, MACOS, ANDROID AND USB-C MOBILE DEVICES</td></tr><tr><td>OTG SUPPORT</td><td>SUPPORTS USB ON-THE-GO (OTG) DEVICES</td></tr><tr><td>DESIGN</td><td>SWIVEL DESIGN TO PROTECT CONNECTORS</td></tr><tr><td>BACKUP SUPPORT</td><td>COMPATIBLE WITH SANDISK MEMORY ZONE APPLICATION FOR FILE BACKUP</td></tr><tr><td>BUILD MATERIAL</td><td>DURABLE PLASTIC HOUSING</td></tr><tr><td>ATTACHMENT</td><td>INTEGRATED KEYRING HOLE FOR PORTABILITY</td></tr><tr><td>OPERATING TEMPERATURE</td><td>TYPICAL CONSUMER FLASH DRIVE OPERATING RANGE</td></tr><tr><td>WARRANTY</td><td>MINIMUM 5-YEAR LIMITED MANUFACTURER WARRANTY</td></tr></table>	ITEM	MINIMUM SPECIFICATION	DEVICE TYPE	USB FLASH DRIVE WITH DUAL CONNECTOR (USB-C AND USB-A)	STORAGE CAPACITY	MINIMUM 256 GB FLASH STORAGE	INTERFACE	USB TYPE-C AND USB TYPE-A CONNECTORS	USB STANDARD	USB 3.2 GEN 1 / USB 3.1 GEN 1	READ SPEED	UP TO 150 MB/S READ SPEED	COMPATIBILITY	COMPATIBLE WITH WINDOWS, MACOS, ANDROID AND USB-C MOBILE DEVICES	OTG SUPPORT	SUPPORTS USB ON-THE-GO (OTG) DEVICES	DESIGN	SWIVEL DESIGN TO PROTECT CONNECTORS	BACKUP SUPPORT	COMPATIBLE WITH SANDISK MEMORY ZONE APPLICATION FOR FILE BACKUP	BUILD MATERIAL	DURABLE PLASTIC HOUSING	ATTACHMENT	INTEGRATED KEYRING HOLE FOR PORTABILITY	OPERATING TEMPERATURE	TYPICAL CONSUMER FLASH DRIVE OPERATING RANGE	WARRANTY	MINIMUM 5-YEAR LIMITED MANUFACTURER WARRANTY				
ITEM	MINIMUM SPECIFICATION																																
DEVICE TYPE	USB FLASH DRIVE WITH DUAL CONNECTOR (USB-C AND USB-A)																																
STORAGE CAPACITY	MINIMUM 256 GB FLASH STORAGE																																
INTERFACE	USB TYPE-C AND USB TYPE-A CONNECTORS																																
USB STANDARD	USB 3.2 GEN 1 / USB 3.1 GEN 1																																
READ SPEED	UP TO 150 MB/S READ SPEED																																
COMPATIBILITY	COMPATIBLE WITH WINDOWS, MACOS, ANDROID AND USB-C MOBILE DEVICES																																
OTG SUPPORT	SUPPORTS USB ON-THE-GO (OTG) DEVICES																																
DESIGN	SWIVEL DESIGN TO PROTECT CONNECTORS																																
BACKUP SUPPORT	COMPATIBLE WITH SANDISK MEMORY ZONE APPLICATION FOR FILE BACKUP																																
BUILD MATERIAL	DURABLE PLASTIC HOUSING																																
ATTACHMENT	INTEGRATED KEYRING HOLE FOR PORTABILITY																																
OPERATING TEMPERATURE	TYPICAL CONSUMER FLASH DRIVE OPERATING RANGE																																
WARRANTY	MINIMUM 5-YEAR LIMITED MANUFACTURER WARRANTY																																

BIL.	KETERANGAN	UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)																												
E.2	SANDISK ULTRA DUAL DRIVE LUXE ATAU YANG SETARA	UNIT	1																														
	<table><tr><td>ITEM</td><td>MINIMUM SPECIFICATION</td></tr><tr><td>DEVICE TYPE</td><td>USB FLASH DRIVE WITH DUAL CONNECTOR (USB-C AND USB-A)</td></tr><tr><td>STORAGE CAPACITY</td><td>MINIMUM 512 GB FLASH STORAGE</td></tr><tr><td>INTERFACE</td><td>USB TYPE-C AND USB TYPE-A CONNECTORS</td></tr><tr><td>USB STANDARD</td><td>USB 3.2 GEN 1 / USB 3.1 INTERFACE</td></tr><tr><td>READ SPEED</td><td>UP TO 400 MB/S READ SPEED (DEPENDING ON CAPACITY)</td></tr><tr><td>COMPATIBILITY</td><td>COMPATIBLE WITH WINDOWS, MACOS, ANDROID, AND USB-C MOBILE DEVICES</td></tr><tr><td>OTG SUPPORT</td><td>SUPPORTS USB ON-THE-GO (OTG) DEVICES</td></tr><tr><td>DESIGN</td><td>DUAL SWIVEL DESIGN TO PROTECT CONNECTORS</td></tr><tr><td>BUILD MATERIAL</td><td>ALL-METAL HOUSING FOR DURABILITY</td></tr><tr><td>ATTACHMENT</td><td>INTEGRATED KEYRING HOLE FOR PORTABILITY</td></tr><tr><td>SOFTWARE SUPPORT</td><td>COMPATIBLE WITH SANDISK MEMORY ZONE APP FOR BACKUP AND FILE MANAGEMENT</td></tr><tr><td>OPERATING SYSTEM SUPPORT</td><td>WINDOWS 10/11, MACOS, ANDROID</td></tr><tr><td>WARRANTY</td><td>MINIMUM 5-YEAR LIMITED MANUFACTURER WARRANTY</td></tr></table>	ITEM	MINIMUM SPECIFICATION	DEVICE TYPE	USB FLASH DRIVE WITH DUAL CONNECTOR (USB-C AND USB-A)	STORAGE CAPACITY	MINIMUM 512 GB FLASH STORAGE	INTERFACE	USB TYPE-C AND USB TYPE-A CONNECTORS	USB STANDARD	USB 3.2 GEN 1 / USB 3.1 INTERFACE	READ SPEED	UP TO 400 MB/S READ SPEED (DEPENDING ON CAPACITY)	COMPATIBILITY	COMPATIBLE WITH WINDOWS, MACOS, ANDROID, AND USB-C MOBILE DEVICES	OTG SUPPORT	SUPPORTS USB ON-THE-GO (OTG) DEVICES	DESIGN	DUAL SWIVEL DESIGN TO PROTECT CONNECTORS	BUILD MATERIAL	ALL-METAL HOUSING FOR DURABILITY	ATTACHMENT	INTEGRATED KEYRING HOLE FOR PORTABILITY	SOFTWARE SUPPORT	COMPATIBLE WITH SANDISK MEMORY ZONE APP FOR BACKUP AND FILE MANAGEMENT	OPERATING SYSTEM SUPPORT	WINDOWS 10/11, MACOS, ANDROID	WARRANTY	MINIMUM 5-YEAR LIMITED MANUFACTURER WARRANTY				
ITEM	MINIMUM SPECIFICATION																																
DEVICE TYPE	USB FLASH DRIVE WITH DUAL CONNECTOR (USB-C AND USB-A)																																
STORAGE CAPACITY	MINIMUM 512 GB FLASH STORAGE																																
INTERFACE	USB TYPE-C AND USB TYPE-A CONNECTORS																																
USB STANDARD	USB 3.2 GEN 1 / USB 3.1 INTERFACE																																
READ SPEED	UP TO 400 MB/S READ SPEED (DEPENDING ON CAPACITY)																																
COMPATIBILITY	COMPATIBLE WITH WINDOWS, MACOS, ANDROID, AND USB-C MOBILE DEVICES																																
OTG SUPPORT	SUPPORTS USB ON-THE-GO (OTG) DEVICES																																
DESIGN	DUAL SWIVEL DESIGN TO PROTECT CONNECTORS																																
BUILD MATERIAL	ALL-METAL HOUSING FOR DURABILITY																																
ATTACHMENT	INTEGRATED KEYRING HOLE FOR PORTABILITY																																
SOFTWARE SUPPORT	COMPATIBLE WITH SANDISK MEMORY ZONE APP FOR BACKUP AND FILE MANAGEMENT																																
OPERATING SYSTEM SUPPORT	WINDOWS 10/11, MACOS, ANDROID																																
WARRANTY	MINIMUM 5-YEAR LIMITED MANUFACTURER WARRANTY																																

BIL.	KETERANGAN	UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)																																		
E.3	WD MY PASSPORT 4TB PORTABLE EXTERNAL HARD DRIVE ATAU YANG SETARA	UNIT	3																																				
	<table><tr><td>ITEM</td><td>MINIMUM SPECIFICATION</td></tr><tr><td>DEVICE TYPE</td><td>PORTABLE EXTERNAL HARD DISK DRIVE</td></tr><tr><td>STORAGE CAPACITY</td><td>MINIMUM 4 TB</td></tr><tr><td>DRIVE TYPE</td><td>2.5-INCH PORTABLE HARD DISK DRIVE (HDD)</td></tr><tr><td>INTERFACE</td><td>USB 3.2 GEN 1 / USB 3.0 INTERFACE</td></tr><tr><td>CONNECTOR TYPE</td><td>USB-C WITH USB-A ADAPTER CABLE</td></tr><tr><td>DATA TRANSFER RATE</td><td>UP TO 5 GB/S (USB 3.2 GEN 1)</td></tr><tr><td>READ/WRITE SPEED</td><td>APPROX. 120–140 MB/S TYPICAL TRANSFER SPEED</td></tr><tr><td>POWER SOURCE</td><td>USB POWERED (NO EXTERNAL POWER ADAPTER REQUIRED)</td></tr><tr><td>SECURITY</td><td>256-BIT AES HARDWARE ENCRYPTION WITH PASSWORD PROTECTION</td></tr><tr><td>SOFTWARE SUPPORT</td><td>COMPATIBLE WITH WD BACKUP SOFTWARE AND DEVICE MANAGEMENT UTILITIES</td></tr><tr><td>COMPATIBILITY</td><td>SUPPORTS WINDOWS, MACOS (REFORMAT REQUIRED)</td></tr><tr><td>DESIGN</td><td>COMPACT PALM-SIZE PORTABLE DESIGN</td></tr><tr><td>BUILD</td><td>DURABLE PLASTIC ENCLOSURE</td></tr><tr><td>OPERATING SYSTEM SUPPORT</td><td>WINDOWS 10/11, MACOS (VIA REFORMAT)</td></tr><tr><td>OPERATING TEMPERATURE</td><td>TYPICAL PORTABLE STORAGE OPERATING RANGE</td></tr><tr><td>WARRANTY</td><td>MINIMUM 3-YEAR MANUFACTURER LIMITED WARRANTY</td></tr></table>	ITEM	MINIMUM SPECIFICATION	DEVICE TYPE	PORTABLE EXTERNAL HARD DISK DRIVE	STORAGE CAPACITY	MINIMUM 4 TB	DRIVE TYPE	2.5-INCH PORTABLE HARD DISK DRIVE (HDD)	INTERFACE	USB 3.2 GEN 1 / USB 3.0 INTERFACE	CONNECTOR TYPE	USB-C WITH USB-A ADAPTER CABLE	DATA TRANSFER RATE	UP TO 5 GB/S (USB 3.2 GEN 1)	READ/WRITE SPEED	APPROX. 120–140 MB/S TYPICAL TRANSFER SPEED	POWER SOURCE	USB POWERED (NO EXTERNAL POWER ADAPTER REQUIRED)	SECURITY	256-BIT AES HARDWARE ENCRYPTION WITH PASSWORD PROTECTION	SOFTWARE SUPPORT	COMPATIBLE WITH WD BACKUP SOFTWARE AND DEVICE MANAGEMENT UTILITIES	COMPATIBILITY	SUPPORTS WINDOWS, MACOS (REFORMAT REQUIRED)	DESIGN	COMPACT PALM-SIZE PORTABLE DESIGN	BUILD	DURABLE PLASTIC ENCLOSURE	OPERATING SYSTEM SUPPORT	WINDOWS 10/11, MACOS (VIA REFORMAT)	OPERATING TEMPERATURE	TYPICAL PORTABLE STORAGE OPERATING RANGE	WARRANTY	MINIMUM 3-YEAR MANUFACTURER LIMITED WARRANTY				
ITEM	MINIMUM SPECIFICATION																																						
DEVICE TYPE	PORTABLE EXTERNAL HARD DISK DRIVE																																						
STORAGE CAPACITY	MINIMUM 4 TB																																						
DRIVE TYPE	2.5-INCH PORTABLE HARD DISK DRIVE (HDD)																																						
INTERFACE	USB 3.2 GEN 1 / USB 3.0 INTERFACE																																						
CONNECTOR TYPE	USB-C WITH USB-A ADAPTER CABLE																																						
DATA TRANSFER RATE	UP TO 5 GB/S (USB 3.2 GEN 1)																																						
READ/WRITE SPEED	APPROX. 120–140 MB/S TYPICAL TRANSFER SPEED																																						
POWER SOURCE	USB POWERED (NO EXTERNAL POWER ADAPTER REQUIRED)																																						
SECURITY	256-BIT AES HARDWARE ENCRYPTION WITH PASSWORD PROTECTION																																						
SOFTWARE SUPPORT	COMPATIBLE WITH WD BACKUP SOFTWARE AND DEVICE MANAGEMENT UTILITIES																																						
COMPATIBILITY	SUPPORTS WINDOWS, MACOS (REFORMAT REQUIRED)																																						
DESIGN	COMPACT PALM-SIZE PORTABLE DESIGN																																						
BUILD	DURABLE PLASTIC ENCLOSURE																																						
OPERATING SYSTEM SUPPORT	WINDOWS 10/11, MACOS (VIA REFORMAT)																																						
OPERATING TEMPERATURE	TYPICAL PORTABLE STORAGE OPERATING RANGE																																						
WARRANTY	MINIMUM 3-YEAR MANUFACTURER LIMITED WARRANTY																																						

BIL.	KETERANGAN	UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)																														
E.4	SANDISK EXTREME PRO 512GB UHS-I SDXC ATAU YANG SETARA <table><tr><td>ITEM</td><td>MINIMUM SPECIFICATION</td></tr><tr><td>DEVICE TYPE</td><td>SECURE DIGITAL SDXC MEMORY CARD</td></tr><tr><td>STORAGE CAPACITY</td><td>MINIMUM 512 GB</td></tr><tr><td>CARD TYPE</td><td>SDXC (SECURE DIGITAL EXTENDED CAPACITY)</td></tr><tr><td>BUS INTERFACE</td><td>UHS-I</td></tr><tr><td>SPEED CLASS</td><td>CLASS 10, UHS SPEED CLASS 3 (U3)</td></tr><tr><td>VIDEO SPEED CLASS</td><td>V30</td></tr><tr><td>MAXIMUM READ SPEED</td><td>UP TO 200 MB/S READ SPEED</td></tr><tr><td>MAXIMUM WRITE SPEED</td><td>UP TO 140 MB/S WRITE SPEED</td></tr><tr><td>APPLICATION</td><td>SUITABLE FOR DSLR, MIRRORLESS CAMERAS, ACTION CAMERAS AND PROFESSIONAL PHOTOGRAPHY</td></tr><tr><td>VIDEO RECORDING SUPPORT</td><td>SUPPORTS FULL HD AND 4K UHD VIDEO RECORDING</td></tr><tr><td>BURST PHOTOGRAPHY</td><td>SUPPORTS CONTINUOUS BURST SHOOTING AND RAW IMAGE CAPTURE</td></tr><tr><td>DURABILITY</td><td>WATERPROOF, TEMPERATURE-PROOF, SHOCKPROOF AND X-RAY PROOF</td></tr><tr><td>PHYSICAL PROTECTION</td><td>BUILT-IN WRITE-PROTECT SWITCH</td></tr><tr><td>WARRANTY</td><td>LIMITED LIFETIME MANUFACTURER WARRANTY</td></tr></table>	ITEM	MINIMUM SPECIFICATION	DEVICE TYPE	SECURE DIGITAL SDXC MEMORY CARD	STORAGE CAPACITY	MINIMUM 512 GB	CARD TYPE	SDXC (SECURE DIGITAL EXTENDED CAPACITY)	BUS INTERFACE	UHS-I	SPEED CLASS	CLASS 10, UHS SPEED CLASS 3 (U3)	VIDEO SPEED CLASS	V30	MAXIMUM READ SPEED	UP TO 200 MB/S READ SPEED	MAXIMUM WRITE SPEED	UP TO 140 MB/S WRITE SPEED	APPLICATION	SUITABLE FOR DSLR, MIRRORLESS CAMERAS, ACTION CAMERAS AND PROFESSIONAL PHOTOGRAPHY	VIDEO RECORDING SUPPORT	SUPPORTS FULL HD AND 4K UHD VIDEO RECORDING	BURST PHOTOGRAPHY	SUPPORTS CONTINUOUS BURST SHOOTING AND RAW IMAGE CAPTURE	DURABILITY	WATERPROOF, TEMPERATURE-PROOF, SHOCKPROOF AND X-RAY PROOF	PHYSICAL PROTECTION	BUILT-IN WRITE-PROTECT SWITCH	WARRANTY	LIMITED LIFETIME MANUFACTURER WARRANTY	UNIT	8		
ITEM	MINIMUM SPECIFICATION																																		
DEVICE TYPE	SECURE DIGITAL SDXC MEMORY CARD																																		
STORAGE CAPACITY	MINIMUM 512 GB																																		
CARD TYPE	SDXC (SECURE DIGITAL EXTENDED CAPACITY)																																		
BUS INTERFACE	UHS-I																																		
SPEED CLASS	CLASS 10, UHS SPEED CLASS 3 (U3)																																		
VIDEO SPEED CLASS	V30																																		
MAXIMUM READ SPEED	UP TO 200 MB/S READ SPEED																																		
MAXIMUM WRITE SPEED	UP TO 140 MB/S WRITE SPEED																																		
APPLICATION	SUITABLE FOR DSLR, MIRRORLESS CAMERAS, ACTION CAMERAS AND PROFESSIONAL PHOTOGRAPHY																																		
VIDEO RECORDING SUPPORT	SUPPORTS FULL HD AND 4K UHD VIDEO RECORDING																																		
BURST PHOTOGRAPHY	SUPPORTS CONTINUOUS BURST SHOOTING AND RAW IMAGE CAPTURE																																		
DURABILITY	WATERPROOF, TEMPERATURE-PROOF, SHOCKPROOF AND X-RAY PROOF																																		
PHYSICAL PROTECTION	BUILT-IN WRITE-PROTECT SWITCH																																		
WARRANTY	LIMITED LIFETIME MANUFACTURER WARRANTY																																		
JUMLAH KESELURUHAN (BIL E)																																			

BIL.	KETERANGAN	UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)
F	VIDEO WALL				

BIL.	KETERANGAN		UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)
F.1	VIDEOWALL 2X2(4 PANELS)		UNIT	1		
	LG 55VM5J-H ATAU SETARA	ITEM	MINIMUM SPECIFICATION			
		SYSTEM TYPE	VIDEO WALL SYSTEM CONFIGURATION 2x2 (4 PANELS) COMPLETE WITH CONTROLLER, MOUNTING SYSTEM AND INSTALLATION ACCESSORIES			
		MAIN DISPLAY	PROFESSIONAL VIDEO WALL DISPLAY			
		DISPLAY SIZE	MINIMUM 55 INCH			
		PANEL TYPE	IPS LCD PANEL OR EQUIVALENT			
		RESOLUTION	1920 × 1080 (FULL HD)			
		BRIGHTNESS	MINIMUM 500 NITS			
		BEZEL	ULTRA-NARROW BEZEL MAXIMUM ?1.8 MM BEZEL-TO-BEZEL			
		VIEWING ANGLE	MINIMUM 178° (H/V)			
		OPERATION	SUPPORTS 24/7 CONTINUOUS OPERATION			
		VIDEO INPUT	HDMI / DISPLAYPORT / DVI OR EQUIVALENT			
		NUMBER OF PANELS	4 UNITS FOR 2x2 CONFIGURATION			
		DISPLAY ARRANGEMENT	SUPPORTS VIDEO WALL MATRIX 2x2			
	DRIGER 4K VIDEO WALL CONTROLLER 2x2 ATAU SETARA	ITEM	MINIMUM SPECIFICATION			
		DEVICE TYPE	VIDEO WALL CONTROLLER / PROCESSOR			
		REFERENCE MODEL	DRIGER 4K VIDEO WALL CONTROLLER			

BIL.	KETERANGAN	UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)
JUMLAH KESELURUHAN (BIL F)					

BIL.	KETERANGAN	UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)
G	INFRASTRUCTURE				

BIL.	KETERANGAN	UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)																																												
G.1	FINGERTEC FACE ID 5 ATAU YANG SETARA	UNIT	8																																														
	<table><tr><td>ITEM</td><td>MINIMUM SPECIFICATION</td></tr><tr><td>DEVICE TYPE</td><td>BIOMETRIC ACCESS CONTROL & TIME ATTENDANCE TERMINAL</td></tr><tr><td>AUTHENTICATION METHODS</td><td>FACE RECOGNITION, FINGERPRINT, PALM, NFC MI-FARE CARD, QR CODE</td></tr><tr><td>CAMERA</td><td>2MP WDR LOW-LIGHT CAMERA</td></tr><tr><td>FINGERPRINT SENSOR</td><td>HIGH RESOLUTION OPTICAL SENSOR</td></tr><tr><td>PROCESSOR (CPU)</td><td>DUAL-CORE PROCESSOR (? 900 MHZ)</td></tr><tr><td>MEMORY</td><td>? 512MB RAM, ? 8GB FLASH STORAGE</td></tr><tr><td>FACE CAPACITY</td><td>? 6,000 USERS</td></tr><tr><td>FINGERPRINT CAPACITY</td><td>? 6,000 TEMPLATES</td></tr><tr><td>PALM CAPACITY</td><td>? 3,000 TEMPLATES</td></tr><tr><td>TRANSACTION LOGS</td><td>? 200,000 RECORDS</td></tr><tr><td>VERIFICATION METHODS</td><td>FACE (1:N), FINGERPRINT (1:1 & 1:N), PALM, CARD</td></tr><tr><td>VERIFICATION SPEED</td><td>FACE ? 2 SECONDS, FINGERPRINT ? 1 SECOND</td></tr><tr><td>DISPLAY</td><td>? 5-INCH TFT COLOR TOUCH SCREEN</td></tr><tr><td>COMMUNICATION</td><td>TCP/IP, RS485, WIFI</td></tr><tr><td>SOFTWARE INTEGRATION</td><td>COMPATIBLE WITH INGRESS SOFTWARE</td></tr><tr><td>ADDITIONAL FEATURES</td><td>MASK DETECTION, ANTI-SPOOFING TECHNOLOGY, LOW-LIGHT RECOGNITION</td></tr><tr><td>MATERIAL</td><td>GLASS FRONT PANEL WITH ALUMINIUM FRAME</td></tr><tr><td>INSTALLATION</td><td>WALL MOUNT / BRACKET MOUNT</td></tr><tr><td>POWER SUPPLY</td><td>DC 12V ADAPTER / P.O.E</td></tr><tr><td>BACKUP POWER</td><td>UPS INSTALLATION FOR POWER FAILURE PROTECTION</td></tr><tr><td>WARRANTY</td><td>MINIMUM 2 YEARS</td></tr></table>	ITEM	MINIMUM SPECIFICATION	DEVICE TYPE	BIOMETRIC ACCESS CONTROL & TIME ATTENDANCE TERMINAL	AUTHENTICATION METHODS	FACE RECOGNITION, FINGERPRINT, PALM, NFC MI-FARE CARD, QR CODE	CAMERA	2MP WDR LOW-LIGHT CAMERA	FINGERPRINT SENSOR	HIGH RESOLUTION OPTICAL SENSOR	PROCESSOR (CPU)	DUAL-CORE PROCESSOR (? 900 MHZ)	MEMORY	? 512MB RAM, ? 8GB FLASH STORAGE	FACE CAPACITY	? 6,000 USERS	FINGERPRINT CAPACITY	? 6,000 TEMPLATES	PALM CAPACITY	? 3,000 TEMPLATES	TRANSACTION LOGS	? 200,000 RECORDS	VERIFICATION METHODS	FACE (1:N), FINGERPRINT (1:1 & 1:N), PALM, CARD	VERIFICATION SPEED	FACE ? 2 SECONDS, FINGERPRINT ? 1 SECOND	DISPLAY	? 5-INCH TFT COLOR TOUCH SCREEN	COMMUNICATION	TCP/IP, RS485, WIFI	SOFTWARE INTEGRATION	COMPATIBLE WITH INGRESS SOFTWARE	ADDITIONAL FEATURES	MASK DETECTION, ANTI-SPOOFING TECHNOLOGY, LOW-LIGHT RECOGNITION	MATERIAL	GLASS FRONT PANEL WITH ALUMINIUM FRAME	INSTALLATION	WALL MOUNT / BRACKET MOUNT	POWER SUPPLY	DC 12V ADAPTER / P.O.E	BACKUP POWER	UPS INSTALLATION FOR POWER FAILURE PROTECTION	WARRANTY	MINIMUM 2 YEARS				
ITEM	MINIMUM SPECIFICATION																																																
DEVICE TYPE	BIOMETRIC ACCESS CONTROL & TIME ATTENDANCE TERMINAL																																																
AUTHENTICATION METHODS	FACE RECOGNITION, FINGERPRINT, PALM, NFC MI-FARE CARD, QR CODE																																																
CAMERA	2MP WDR LOW-LIGHT CAMERA																																																
FINGERPRINT SENSOR	HIGH RESOLUTION OPTICAL SENSOR																																																
PROCESSOR (CPU)	DUAL-CORE PROCESSOR (? 900 MHZ)																																																
MEMORY	? 512MB RAM, ? 8GB FLASH STORAGE																																																
FACE CAPACITY	? 6,000 USERS																																																
FINGERPRINT CAPACITY	? 6,000 TEMPLATES																																																
PALM CAPACITY	? 3,000 TEMPLATES																																																
TRANSACTION LOGS	? 200,000 RECORDS																																																
VERIFICATION METHODS	FACE (1:N), FINGERPRINT (1:1 & 1:N), PALM, CARD																																																
VERIFICATION SPEED	FACE ? 2 SECONDS, FINGERPRINT ? 1 SECOND																																																
DISPLAY	? 5-INCH TFT COLOR TOUCH SCREEN																																																
COMMUNICATION	TCP/IP, RS485, WIFI																																																
SOFTWARE INTEGRATION	COMPATIBLE WITH INGRESS SOFTWARE																																																
ADDITIONAL FEATURES	MASK DETECTION, ANTI-SPOOFING TECHNOLOGY, LOW-LIGHT RECOGNITION																																																
MATERIAL	GLASS FRONT PANEL WITH ALUMINIUM FRAME																																																
INSTALLATION	WALL MOUNT / BRACKET MOUNT																																																
POWER SUPPLY	DC 12V ADAPTER / P.O.E																																																
BACKUP POWER	UPS INSTALLATION FOR POWER FAILURE PROTECTION																																																
WARRANTY	MINIMUM 2 YEARS																																																

BIL.	KETERANGAN	UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)																																																				
G.2	IANZ V1 SMART DOOR LOCK ATAU YANG SETARA <table><tr><td>ITEM</td><td>MINIMUM SPECIFICATION</td></tr><tr><td>PRODUCT TYPE</td><td>SMART DIGITAL DOOR LOCK</td></tr><tr><td>UNLOCK METHODS</td><td>FINGERPRINT, PIN CODE, RFID CARD, MOBILE APPLICATION, MECHANICAL KEY</td></tr><tr><td>FINGERPRINT SENSOR</td><td>SEMICONDUCTOR FINGERPRINT SENSOR</td></tr><tr><td>FINGERPRINT CAPACITY</td><td>MINIMUM 100 FINGERPRINTS</td></tr><tr><td>PIN CODE CAPACITY</td><td>MINIMUM 100 USER PIN CODES</td></tr><tr><td>RFID CARD CAPACITY</td><td>MINIMUM 100 RFID CARDS</td></tr><tr><td>MOBILE ACCESS</td><td>WI-FI OR BLUETOOTH APP CONTROL</td></tr><tr><td>MOBILE APPLICATION</td><td>ANDROID AND IOS SUPPORTED</td></tr><tr><td>REMOTE UNLOCK</td><td>SUPPORTED VIA MOBILE APPLICATION</td></tr><tr><td>TEMPORARY ACCESS CODE</td><td>SUPPORTED</td></tr><tr><td>ACCESS LOG / AUDIT TRAIL</td><td>SUPPORTED</td></tr><tr><td>AUTO LOCK FUNCTION</td><td>SUPPORTED</td></tr><tr><td>MANUAL LOCK FUNCTION</td><td>SUPPORTED</td></tr><tr><td>ANTI-PEEP PASSWORD</td><td>SUPPORTED</td></tr><tr><td>FAKE PIN PROTECTION</td><td>SUPPORTED</td></tr><tr><td>WRONG ATTEMPT ALARM</td><td>SUPPORTED</td></tr><tr><td>LOW BATTERY ALERT</td><td>SUPPORTED</td></tr><tr><td>EMERGENCY POWER SUPPLY</td><td>USB TYPE-C EMERGENCY CHARGING PORT</td></tr><tr><td>MECHANICAL OVERRIDE KEY</td><td>INCLUDED</td></tr><tr><td>DOOR THICKNESS SUPPORTED</td><td>35 MM – 90 MM</td></tr><tr><td>DOOR MATERIAL COMPATIBILITY</td><td>WOODEN, METAL AND COMPOSITE DOORS</td></tr><tr><td>LOCK BODY TYPE</td><td>MORTISE LOCK</td></tr><tr><td>POWER SUPPLY</td><td>4 × AA ALKALINE BATTERIES</td></tr><tr><td>BATTERY LIFE</td><td>UP TO 12 MONTHS</td></tr><tr><td>INDOOR/OUTDOOR INSTALLATION</td><td>SUITABLE FOR COVERED INDOOR AND OUTDOOR AREAS</td></tr></table>	ITEM	MINIMUM SPECIFICATION	PRODUCT TYPE	SMART DIGITAL DOOR LOCK	UNLOCK METHODS	FINGERPRINT, PIN CODE, RFID CARD, MOBILE APPLICATION, MECHANICAL KEY	FINGERPRINT SENSOR	SEMICONDUCTOR FINGERPRINT SENSOR	FINGERPRINT CAPACITY	MINIMUM 100 FINGERPRINTS	PIN CODE CAPACITY	MINIMUM 100 USER PIN CODES	RFID CARD CAPACITY	MINIMUM 100 RFID CARDS	MOBILE ACCESS	WI-FI OR BLUETOOTH APP CONTROL	MOBILE APPLICATION	ANDROID AND IOS SUPPORTED	REMOTE UNLOCK	SUPPORTED VIA MOBILE APPLICATION	TEMPORARY ACCESS CODE	SUPPORTED	ACCESS LOG / AUDIT TRAIL	SUPPORTED	AUTO LOCK FUNCTION	SUPPORTED	MANUAL LOCK FUNCTION	SUPPORTED	ANTI-PEEP PASSWORD	SUPPORTED	FAKE PIN PROTECTION	SUPPORTED	WRONG ATTEMPT ALARM	SUPPORTED	LOW BATTERY ALERT	SUPPORTED	EMERGENCY POWER SUPPLY	USB TYPE-C EMERGENCY CHARGING PORT	MECHANICAL OVERRIDE KEY	INCLUDED	DOOR THICKNESS SUPPORTED	35 MM – 90 MM	DOOR MATERIAL COMPATIBILITY	WOODEN, METAL AND COMPOSITE DOORS	LOCK BODY TYPE	MORTISE LOCK	POWER SUPPLY	4 × AA ALKALINE BATTERIES	BATTERY LIFE	UP TO 12 MONTHS	INDOOR/OUTDOOR INSTALLATION	SUITABLE FOR COVERED INDOOR AND OUTDOOR AREAS	UNIT	1		
ITEM	MINIMUM SPECIFICATION																																																								
PRODUCT TYPE	SMART DIGITAL DOOR LOCK																																																								
UNLOCK METHODS	FINGERPRINT, PIN CODE, RFID CARD, MOBILE APPLICATION, MECHANICAL KEY																																																								
FINGERPRINT SENSOR	SEMICONDUCTOR FINGERPRINT SENSOR																																																								
FINGERPRINT CAPACITY	MINIMUM 100 FINGERPRINTS																																																								
PIN CODE CAPACITY	MINIMUM 100 USER PIN CODES																																																								
RFID CARD CAPACITY	MINIMUM 100 RFID CARDS																																																								
MOBILE ACCESS	WI-FI OR BLUETOOTH APP CONTROL																																																								
MOBILE APPLICATION	ANDROID AND IOS SUPPORTED																																																								
REMOTE UNLOCK	SUPPORTED VIA MOBILE APPLICATION																																																								
TEMPORARY ACCESS CODE	SUPPORTED																																																								
ACCESS LOG / AUDIT TRAIL	SUPPORTED																																																								
AUTO LOCK FUNCTION	SUPPORTED																																																								
MANUAL LOCK FUNCTION	SUPPORTED																																																								
ANTI-PEEP PASSWORD	SUPPORTED																																																								
FAKE PIN PROTECTION	SUPPORTED																																																								
WRONG ATTEMPT ALARM	SUPPORTED																																																								
LOW BATTERY ALERT	SUPPORTED																																																								
EMERGENCY POWER SUPPLY	USB TYPE-C EMERGENCY CHARGING PORT																																																								
MECHANICAL OVERRIDE KEY	INCLUDED																																																								
DOOR THICKNESS SUPPORTED	35 MM – 90 MM																																																								
DOOR MATERIAL COMPATIBILITY	WOODEN, METAL AND COMPOSITE DOORS																																																								
LOCK BODY TYPE	MORTISE LOCK																																																								
POWER SUPPLY	4 × AA ALKALINE BATTERIES																																																								
BATTERY LIFE	UP TO 12 MONTHS																																																								
INDOOR/OUTDOOR INSTALLATION	SUITABLE FOR COVERED INDOOR AND OUTDOOR AREAS																																																								

27/28

BIL.	KETERANGAN	UNIT	KUANTITI	KADAR (RM)	AMAUN (RM)
JUMLAH KESELURUHAN (BIL G)					